

2412 Multi-Conductor - Enhanced Category 6 Nonbonded-Pair Cables



For more Information
please call

1-800-Belden1



General Description:

CAT6+ (350MHz), 4-Pair, U/UTP-Unshielded, Riser-CMR, Premise Horizontal Cable, 23 AWG Solid Bare Copper Conductors, Polyolefin Insulation, Tape Separator, Ripcord, PVC Jacket

Usage (Overall)

Suitable Applications: Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM

Physical Characteristics (Overall)

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
4	23	Solid	BC - Bare Copper

Total Number of Conductors: 8

Insulation

Insulation Material:

Insulation Material
PO - Polyolefin

Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Diameter:

Nom. Dia. (in.)
0.220

Outer Jacket Ripcord: Yes

Overall Cable

Overall Cabling Separator Material: Patented Dielectric Tape

Overall Nominal Diameter: 0.220 in.

Pair

Pair Color Code Chart:

Number	Color
1	White/Blue Stripe and Blue
2	White/Orange Stripe and Orange
3	White/Green Stripe and Green
4	White/Brown Stripe and Brown

Mechanical Characteristics (Overall)

Storage Temperature Range: -20°C To +75°C

Installation Temperature Range: +5°C To +50°C

Operating Temperature Range: 0°C To +75°C

Bulk Cable Weight: 24 lbs/1000 ft.

Max. Recommended Pulling Tension: 40 lbs.

Min. Bend Radius/Minor Axis: 0.750 in.

Min. Bend/Installation: 2.250 in.

2412 Multi-Conductor - Enhanced Category 6 Nonbonded-Pair Cables

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMR
EU Directive 2011/65/EU (ROHS II):	Yes
Other Standards:	ISO/IEC 11801 ed 2.1 (2008) Class E
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Telecommunications Standards:	Category 6 - TIA 568.C.2
Other Specification:	Third party verified to Category 6

Applicable Patents:

Country

www.belden.com/p

Flame Test

UL Flame Test:	UL1666 Vertical Riser
C(UL) Flame Test:	FT4
CSA Flame Test:	FT4

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	2413

Electrical Characteristics (Overall)

Nom. Mutual Capacitance:

Capacitance (pF/ft)

17.000

Maximum Capacitance Unbalance (pF/100 m):	330
---	-----

Nominal Velocity of Propagation:

VP (%)

70

Maximum Delay:

Delay (ns/100 m)

537 @ 100MHz

Max. Delay Skew:

Delay Skew (ns/100 m)

35.000

Maximum Conductor DC Resistance:

DCR @ 20°C (Ohm/100 m)

7.800

Max. Operating Voltage - UL:

Voltage

300 V RMS

Maximum DCR Unbalanced:

DCR Unbalance @ 20°C (%)

3.000

Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

Freq. (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min RL (dB)
1	2.000	75.3	75.3	73.3	73.3	20.000
4	3.700	66.3	66.3	62.6	62.6	23.000

2412 Multi-Conductor - Enhanced Category 6 Nonbonded-Pair Cables

8	5.200	61.8	61.8	56.6	56.6	24.500
10	5.800	60.3	60.3	54.5	54.5	25.000
16	7.400	57.2	57.2	49.9	49.9	25.000
20	8.300	55.8	55.8	47.5	47.5	25.000
25	9.300	54.3	54.3	45.1	45.1	24.300
31.25	10.400	52.9	52.9	42.5	42.5	23.600
62.5	15.000	48.4	48.4	33.4	33.4	21.500
100	19.300	45.3	45.3	26.0	26.0	20.800
155	24.600	42.4	42.4	17.9	17.9	19.500
200	28.300	40.8	40.8	12.5	12.5	18.700
250	32.100	39.3	39.3	7.2	7.2	18.000
300	35.600	38.1	36.1	0.5	0.5	17.500
350	38.900	37.1	35.1	-1.7	-3.7	17.000
400	42.000	36.3	34.3	-5.7	-7.7	16.600
450	45.000	35.5	33.5	-9.5	-11.5	16.200
500	47.900	34.8	32.8	-13.0	-15.0	15.900
550	50.600	34.2	32.2	-16.4	-18.4	15.600

Premise Cable Electrical Table 2:

Freq. (MHz)	Input (Unfitted) Imp. (Ohms)	Fitted Impedance	Min. ACRF (dB)	Min. PSACRF (dB)
1	100 ± 15	102 ± 15	70.8	67.8
4	100 ± 15	100 ± 15	58.8	55.8
8	100 ± 15	100 ± 15	52.7	49.7
10	100 ± 15	100 ± 15	50.8	47.8
16	100 ± 15	100 ± 15	46.7	43.7
20	100 ± 15	100 ± 15	44.8	41.8
25	100 ± 15	100 ± 15	42.8	39.8
31.25	100 ± 15	100 ± 15	40.9	37.9
62.5	100 ± 15	100 ± 15	34.9	31.9
100	100 ± 15	100 ± 15	30.8	27.8
155	100 ± 22	100 ± 15	27.0	24.0
200	100 ± 22	100 ± 15	24.8	21.8
250	100 ± 32	100 ± 15	22.8	19.8
300	100 ± 32	100 ± 15	21.3	18.3
350	100 ± 32	100 ± 15	19.9	16.9
400	100 ± 32	100 ± 15	18.8	15.8
450	100 ± 32	100 ± 15	17.7	14.7
500	100 ± 32	100 ± 15	16.8	13.8
550	100 ± 32	100 ± 15	16.0	13.0

Notes (Overall)

Notes: Jacket sequentially marked at 2 ft./1m intervals. Third party verified to ANSI/TIA-568-C.2, Category 6. Values above 350 MHz are for Engineering Information Only. In addition to the colors below, Pink is also available as a special, p/n 2412 012 U1000, or 2412 012 A1000.

Reference (Overall)

Previous Part Number:

24566415, 25066515T, 24566745, 24566745T, 24566745T+HU, 24566736T, 24566715, 24566715T, 25066885, 25066885T, 25066815T, 24566945, 24566945T, 24566945T+HU, 24566931, 24566931T, 24566931T+HU, 24566936T, 24566915, 24566915T, 24566915T+HU, 24566015, 24566015T, 24566P15, 24566P15T, 24566185, 24566185T, 24566185T+HU, 24566115T, 24566345, 24566345T, 24566345T+HU, 24566336T, 24566315, 24566315T, 24566315T+HU, 24566485, 24566485T, 24566415T, 24566415T

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
2412 002A1000	1,000 FT	27.000 LB	RED	C	CAT6+ 4PR U/UTP CMR RIB
2412 003A1000	1,000 FT	27.000 LB	ORANGE		CAT6+ 4PR U/UTP CMR RIB
2412 003U1000	1,000 FT	24.000 LB	ORANGE		CAT6+ 4PR U/UTP CMR BOX
2412 004A1000	1,000 FT	27.000 LB	YELLOW		CAT6+ 4PR U/UTP CMR RIB
2412 004U1000	1,000 FT	24.000 LB	YELLOW		CAT6+ 4PR U/UTP CMR BOX
2412 004I1000	1,000 FT	24.000 LB	YELLOW		CAT6+ 4PR U/UTP CMR REEL
2412 0042500	2,500 FT	60.000 LB	YELLOW		CAT6+ 4PR U/UTP CMR REEL
2412 005A1000	1,000 FT	27.000 LB	GREEN, DARK		CAT6+ 4PR U/UTP CMR RIB
2412 005U1000	1,000 FT	24.000 LB	GREEN, DARK		CAT6+ 4PR U/UTP CMR BOX
2412 005I1000	1,000 FT	24.000 LB	GREEN, DARK		CAT6+ 4PR U/UTP CMR REEL
2412 006A1000	1,000 FT	27.000 LB	BLUE, LIGHT		CAT6+ 4PR U/UTP CMR RIB
2412 006U1000	1,000 FT	24.000 LB	BLUE, LIGHT		CAT6+ 4PR U/UTP CMR BOX
2412 006I1000	1,000 FT	24.000 LB	BLUE, LIGHT		CAT6+ 4PR U/UTP CMR REEL
2412 0061400	1,400 FT	35.000 LB	BLUE, LIGHT		CAT6+ 4PR U/UTP CMR REEL

2412 Multi-Conductor - Enhanced Category 6 Nonbonded-Pair Cables

2412 0062500	2,500 FT	60.000 LB	BLUE, LIGHT		CAT6+ 4PR U/UTP CMR REEL
2412 0065000	5,000 FT	125.000 LB	BLUE, LIGHT	C	CAT6+ 4PR U/UTP CMR REEL
2412 007A1000	1,000 FT	27.000 LB	VIOLET		CAT6+ 4PR U/UTP CMR RIB
2412 007U1000	1,000 FT	24.000 LB	VIOLET		CAT6+ 4PR U/UTP CMR BOX
2412 008A1000	1,000 FT	27.000 LB	GRAY		CAT6+ 4PR U/UTP CMR RIB
2412 008U1000	1,000 FT	24.000 LB	GRAY		CAT6+ 4PR U/UTP CMR BOX
2412 0081000	1,000 FT	24.000 LB	GRAY		CAT6+ 4PR U/UTP CMR REEL
2412 009A1000	1,000 FT	27.000 LB	WHITE		CAT6+ 4PR U/UTP CMR RIB
2412 009U1000	1,000 FT	24.000 LB	WHITE		CAT6+ 4PR U/UTP CMR BOX
2412 0091000	1,000 FT	24.000 LB	WHITE		CAT6+ 4PR U/UTP CMR REEL
2412 0092500	2,500 FT	60.000 LB	WHITE		CAT6+ 4PR U/UTP CMR REEL
2412 0095000	5,000 FT	125.000 LB	WHITE	C	CAT6+ 4PR U/UTP CMR REEL
2412 010A1000	1,000 FT	27.000 LB	BLACK		CAT6+ 4PR U/UTP CMR RIB
2412 010U1000	1,000 FT	24.000 LB	BLACK		CAT6+ 4PR U/UTP CMR BOX
2412 0101000	1,000 FT	24.000 LB	BLACK		CAT6+ 4PR U/UTP CMR REEL

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 6 Revision Date: 02-27-2014

© 2014 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

[2412 006U1000](#) [2412 008U1000](#) [2412 009U1000](#) [2412 002A1000](#) [2412 003A1000](#) [2412 004A1000](#) [2412 0041000](#)
[2412 0042500](#) [2412 005A1000](#) [2412 0051000](#) [2412 006A1000](#) [2412 0061000](#) [2412 0061400](#) [2412 0062500](#) [2412](#)
[007A1000](#) [2412 008A1000](#) [2412 0081000](#) [2412 009A1000](#) [2412 0091000](#) [2412 0092500](#) [2412 010A1000](#) [2412](#)
[0101000](#)