

Part Number: 2424

CAT6+ Horizontal, 4pr, UTP, LSZH Jkt



Product Description

CAT6+ (350MHz), 4-Pair, U/UTP-unshielded, Zero Halogen, Premise Horizontal cable, 23 AWG solid bare copper conductors, polyolefin insulation, patented tape separator, ripcord, LSZH jacket.

Technical Specifications

Product Overview

Environmental Space:	LSZH
Suitable Applications:	Premise Horizontal Cable, POE, POE+, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU, Digital Video, RS-422

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Pairs
23	Solid	BC - Bare Copper	4

Total Number of Conductors:	8
-----------------------------	---

Insulation

Material
PO - Polyolefin

Color Chart

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

Outer Shield Material

Material
N/A

Outer Jacket Material

Material	Material Trade Name	Nominal Diameter	Ripcord	Separator Material
LSZH - Low Smoke Zero Halogen	Haloarrest®	0.221 in	Yes	Patented Dielectric Tape

Electrical Characteristics

Capacitance

Max. Capacitance Unbalance	Nom.Mutual Capacitance
330 pF/100m	17 pF/ft

Shielding:	UTP - Unshielded
------------	------------------

Construction and Dimensions

Total Number of Pairs:	4
------------------------	---

Conductor DCR

Max. Conductor DCR	Max. DCR Unbalance
7.8 Ohm/100m	3 %

Delay

Max. Delay	Max. Delay Skew	Nominal Velocity of Propagation (VP) [%]
@ 100 MHz 537.6 ns/100m	35 ns/100m	70 %

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Max./Min. Input Impedance (unFitted)	Max./Min. Fitted Impedance	Min. TCL [dB]	Min. ELTCTL [dB]
1 MHz	2.0 dB/100m	75.3 dB	75.3 dB	73.3 dB	73.3 dB	70.8 dB	67.8 dB	20.0 dB	100 ± 15 Ohm	102 ± 15 Ohm	40.0 dB	35.0 dB
4 MHz	3.7 dB/100m	66.3 dB	66.3 dB	62.5 dB	62.5 dB	58.8 dB	55.8 dB	23.0 dB	100 ± 15 Ohm	100 ± 15 Ohm	40.0 dB	23.0 dB
8 MHz	5.3 dB/100m	61.8 dB	61.8 dB	56.5 dB	56.5 dB	52.7 dB	49.7 dB	24.5 dB	100 ± 15 Ohm	100 ± 15 Ohm	40.0 dB	16.9 dB
10 MHz	5.9 dB/100m	60.3 dB	60.3 dB	54.4 dB	54.4 dB	50.8 dB	47.8 dB	25.0 dB	100 ± 15 Ohm	100 ± 15 Ohm	40.0 dB	15.0 dB
16 MHz	7.4 dB/100m	57.2 dB	57.2 dB	49.8 dB	49.8 dB	46.7 dB	43.7 dB	25.0 dB	100 ± 15 Ohm	100 ± 15 Ohm	38.0 dB	10.9 dB
20 MHz	8.3 dB/100m	55.8 dB	55.8 dB	47.4 dB	47.4 dB	44.8 dB	41.8 dB	25.0 dB	100 ± 15 Ohm	100 ± 15 Ohm	37.0 dB	9.0 dB
25 MHz	9.4 dB/100m	54.3 dB	54.3 dB	45.0 dB	45.0 dB	42.8 dB	39.8 dB	24.3 dB	100 ± 15 Ohm	100 ± 15 Ohm	36.0 dB	7.0 dB
31.25 MHz	10.5 dB/100m	52.9 dB	52.9 dB	42.4 dB	42.4 dB	40.9 dB	37.9 dB	23.6 dB	100 ± 15 Ohm	100 ± 15 Ohm	35.1 dB	5.1 dB
62.5 MHz	15.1 dB/100m	48.4 dB	48.4 dB	33.3 dB	33.3 dB	34.9 dB	31.9 dB	21.5 dB	100 ± 15 Ohm	100 ± 15 Ohm	32.0 dB	
100 MHz	19.3 dB/100m	45.3 dB	45.3 dB	26.0 dB	26.0 dB	30.8 dB	27.8 dB	20.8 dB	100 ± 15 Ohm	100 ± 15 Ohm	30.0 dB	
155 MHz	24.5 dB/100m	42.4 dB	42.4 dB	17.9 dB	17.9 dB	27.0 dB	24.0 dB	19.5 dB	100 ± 22 Ohm	100 ± 15 Ohm	28.1 dB	
200 MHz	28.2 dB/100m	40.8 dB	40.8 dB	12.6 dB	12.6 dB	24.8 dB	21.8 dB	18.7 dB	100 ± 22 Ohm	100 ± 15 Ohm	27.0 dB	
250 MHz	31.8 dB/100m	39.3 dB	39.3 dB	7.5 dB	7.5 dB	22.8 dB	19.8 dB	18.0 dB	100 ± 32 Ohm	100 ± 15 Ohm	26.0 dB	
300 MHz	35.2 dB/100m	38.1 dB	36.1 dB	2.9 dB	0.9 dB	21.3 dB	18.3 dB	17.5 dB	100 ± 32 Ohm	100 ± 15 Ohm	25.2 dB	
350 MHz	38.4 dB/100m	37.1 dB	35.1 dB			19.9 dB	16.9 dB	17.0 dB	100 ± 32 Ohm	100 ± 15 Ohm	24.6 dB	
400 MHz	41.5 dB/100m	36.3 dB	34.3 dB			18.8 dB	15.8 dB	16.6 dB	100 ± 32 Ohm	100 ± 15 Ohm	24.0 dB	
450 MHz	44.3 dB/100m	35.5 dB	33.5 dB			17.7 dB	14.7 dB	16.2 dB	100 ± 32 Ohm	100 ± 15 Ohm	23.5 dB	
500 MHz	47.1 dB/100m	34.8 dB	32.8 dB			16.8 dB	13.8 dB	15.9 dB	100 ± 32 Ohm	100 ± 15 Ohm	23.0 dB	
550 MHz	49.7 dB/100m	34.2 dB	32.2 dB			16.0 dB	13.0 dB	15.6 dB	100 ± 32 Ohm	100 ± 15 Ohm		

Voltage

UL Voltage Rating
300V RMS

Applicable Standards & Environmental Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	Yes
Third Party Performance Verification:	Category 6
EU CE Mark:	No
EU REACH SVHC Compliance (yyyy-mm-dd):	2017-07-10
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CPR Euroclass:	Eca
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Telecommunications Standards:	ANSI/TIA-568-C.2 Category 6
Patent:	http://www.belden.com/p

Standards

ISO/IEC Compliance:	11801 ed 2.2 (2011) Class E
ANSI/TIA Category:	Category 6
ANSI Compliance:	S-116-732-2013 Category 6, ANSI/NEMA WC-66 Category 6
IEEE Specification:	POE per 802.3af & POE+ per 802.3at-2009
NEC/(UL) Specification:	N/A

Safety

UL Voltage Rating:	300 V RMS
--------------------	-----------

Suitability

Suitability - Aerial:	No
Suitability - Burial:	No
Suitability - Hazardous Locations:	No
Suitability - Indoor:	Yes
Suitability - Non-Halogenated:	Yes
Suitability - Oil Resistance:	No
Suitability - Outdoor:	No
Suitability - Sunlight Resistance:	No

Mechanical Characteristics

Storage Temp Range:	-20°C To +75°C
Installation Temp Range:	+5°C To +50°C
Operating Temp Range:	-20°C To +75°C
Bulk Cable Weight:	23(lbs/1000ft)
Max Recommended Pulling Tension:	25(lbs)
Min Bend Radius/Minor Axis:	1.0(in)
Min Bend Radius/Installation:	2.25(in)

Temperature Range

Non-UL Temp Rating:	+75°C
---------------------	-------

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	2413

Part Number

Non-Plenum Number:	2412
--------------------	------

History

Variants

Item #	Color
2424.06305	BLUE
2424.08305	BLUE
2424 0061000	BLUE
2424.07305	PURPLE
2424 0071000	PURPLE
2424.071000	PURPLE
2424.02500	RED
2424 0091000	WHITE

© 2017 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be instock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

[2424 0061000](#) [2424 0071000](#) [2424 0091000](#)