



CONNECTOR HOUSINGS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**



TE CONNECTIVITY (TE)

05P CMNL PLUG M/M BLK HT

[MATE-N-LOK](#) | [Commercial MATE-N-LOK](#)

2-480390-1

TE Internal Number: 2-480390-1

[Always EU RoHS/ELV Compliant](#)

Connector System **Wire-to-Wire**

Centerline **4.95 mm [.195 in]**

Number of Positions **5**

Number of Rows **1**

Housing Material **Nylon**

Product Drawings

[5 Circuit Mate-N-Lok Plug](#)

PDF ([TIFF AVAILABLE](#))
English

[5 Circuit Mate-N-Lok Plug](#)

PDF ([TIFF AVAILABLE](#))
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Product Specifications

Application Specification

[MATE-N-LOK Commercial Pin And Socket Contacts](#)

PDF
Japanese

[MATE-N-LOK Commercial Pin And Socket Contacts](#)

TIF
Japanese

[Commercial MATE-N-LOK Pin And Socket Contacts](#)

PDF
English

Instruction Sheets

Instruction Sheet (U.S.)

[10 CIRCUIT MATE-N-LOK CONNECTOR](#)

PDF
English

[10 CIRCUIT MATE-N-LOK CONNECTOR](#)

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Connector System	Wire-to-Wire
	Sealed	No
	Product Type	Connector
	Connector Type	Housing
	Applies To	Wire/Cable
Configuration Features	Number of Positions	5
	Number of Rows	1
Electrical Characteristics	Operating Voltage (VAC)	250
Contact Features	Contact Type	Socket
	Contact Layout	Inline
Mechanical Attachment	Panel Mount Retention	Without
Housing Features	Centerline	4.95 mm [.195 in]
	Housing Material	Nylon
	Housing Color	Black
Usage Conditions	Operating Temperature Range	-55 – 105 °C [-67 – 221 °F]
Operation/Application	For Use With	Pin (Cap) Housing
Identification Marking	Circuit Identification Feature	With
Industry Standards	UL Rating	Certified, Recognized
	VDE Tested	No
	Agency/Standard	CSA, UL
	UL File Number	E28476
	CSA File Number	LR16455
	UL Flammability Rating	UL 94V-2

Packaging Features

Packaging Quantity

1

Packaging Method

Package

Product Compliance

[Statement of Compliance](#)

PDF

[VIEW ALL PRODUCT COMPLIANCE](#)