





On the bottom menu bar, click **Page by Page** to access a page index or **Pages-at-a-Glance** to access a section index. View single pages in order by clicking **Previous** or **Next**. For improved print clarity, click **Page in PDF**. To **Print a PDF** be sure to select **Current Page** in your print monitor. Click **Email to a friend** to send a page to a third party. **Search** by 9 digit (54.003.7553) or 5-digit (54003) part number, series (WKC), or type of product (PCB connectors).

Insulated headers for PC boards
Spacings: 7.50/7.62 mm

codable

Rated current:
12 A

400 V/6 kV/3 – Overvoltage category III
690 V/6 kV/2 – Overvoltage category II
1000 V/6 kV/1 – Overvoltage category I



Solder pin 1 x 1 mm
Bore hole Ø 1.4 mm
closed version

Type 8313 S/... W, 8413 S/... W
horizontal mount



Solder pin 1 x 1 mm
Bore hole Ø 1.4 mm

with screw flange

Type 8313 S/... WF, 8413 S/... WF
horizontal mount

Rated voltages: VDE 0110

UL ratings

CSA ratings

Approvals



300 V	15 A
300 V	15 A

300 V	15 A
300 V	15 A

[illegible]

Spacing: 7.62 mm					unmarked	unmarked		
	100	14.52	7.62	2	25.392.3253.0	25.68	7.62	25.398.2253.0
	100	22.14	15.24	3	25.392.3353.0	33.25	15.24	25.398.2353.0
	50	29.76	22.86	4	25.392.3453.0	40.90	22.86	25.398.2453.0
	50	37.38	30.48	5	25.392.3553.0	48.52	30.48	25.398.2553.0
	50	45.00	38.10	6	25.392.3653.0	56.14	38.10	25.398.2653.0
	50	52.62	45.72	7	25.392.3753.0	63.76	45.72	25.398.2753.0
	50	60.24	53.34	8	25.392.3853.0	71.38	53.34	25.398.2853.0
	50	67.86	60.64	9	25.392.3953.0	79.00	60.64	25.398.2953.0
	50	75.48	68.58	10	25.392.4053.0	86.62	68.58	25.398.3053.0
	50	83.10	76.20	11	25.392.4153.0	94.24	76.20	25.398.3153.0
	50	90.72	83.82	12	25.392.4253.0	101.86	83.82	25.398.3253.0
Accessories:								
Coding piece (strip)	100				05.561.0053.0	05.561	0053.0	
Fixing device assembly - for screw flanges on both sides of the header	100				25.523.2453.0			

301