

DULUX S 11 W/830

OSRAM DULUX S | Short CFLni, with 2-pin base for CCG operation



Areas of application

- Ideal for cost-effective creative illumination and decoration
- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants

Product benefits

- Extremly economical
- Good quality of light
- Extremely low profile
- Long service life
- Improved maintenance

Product features

- Average life: 10,000 h
- Color rendering index R_a for lamps with white light: 80...89
- Also available in red, green and blue
- Short and compact pin-base lamps with single-turn tubes
- Single-ended two-pin plug-in G23 base



Product datasheet

Technical data


Electrical data

Nominal wattage	11.8 W
-----------------	--------

Photometrical data

Light color	830	
Light color as per EN 12464-1	LUMILUX Warm White	
Luminous flux at 25 °C	900 lm	
Luminance	2.7 cd/cm ²	
Color rendering group	1B	

Dimensions & weight







Tube diameter	12 mm
Length	237.0 mm
Length acc. to IEC standard	215 mm

Lifespan


Lifespan	10000 h ¹⁾

¹⁾ With CCG/LLCG

Additional product data

Base (standard designation)	G23
Appropriate disposal acc. to WEEE	Yes


Light Distribution




Spectral power distribution

Equipment / Accessories

- Suitable for operation on conventional control gear





Circuit diagram

Circuit diagram

Logistical Data

Product code	Product description	Packaging unit	Dimensions (length	Volume	Gross weight
		(Pieces/Unit)	x width x height)		

Product datasheet

4050300025759	DULUX S 11 W/830	Shipping carton box		2.68 dm ³	546.77 g
		10	250 mm		

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.