

Cabtite KT 19**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Cabtite enables you to feed pre-assembled lines through the electrical cabinet wall while maintaining IP54-level protection. As the cable does not have to be split, the manufacturer's guarantee is not invalidated.

General ordering data

Order No.	1826320000
Type	Cabtite KT 19
Version	Cable grommet, Plastic
GTIN (EAN)	4032248329144
Qty.	10 pc(s).

Cabtite KT 19**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

Technical data**Dimensions and weights**

Net weight	34 g
------------	------

General information

Clamping range, max.	20 mm	Clamping range, min.	19 mm
Material	Plastic	Operating temperature range, max.	80 °C
Operating temperature range, min.	-20 °C		

Classifications

ETIM 2.0	EC000441	ETIM 3.0	EC000441
UNSPSC	30-21-18-01	eClass 4.1	27-14-12-96
eClass 5.1	27-14-92-01	eClass 6.0	27-14-92-01
eClass 7.0	27-14-92-01		

Approvals

Approvals