

SPECIFICATION CONTROL DRAWING


55PC6279

TITLE THREE CONDUCTOR CABLE, DOUBLE SHIELDED, JACKETED, GENERAL PURPOSE, 600 VOLT

Date 11-1-06

Revision C

This specification sheet forms a part of the latest issue of Raychem Specification 55PC.



CONSTRUCTION DETAILS

PART NUMBER 1/	CONDUCTOR SIZE (AWG)	INNER SHIELD SIZE (AWG)	OUTER SHIELD SIZE (AWG)	JACKET THICKNESS (in.)		DIAMETER (in.)			WEIGHT (lbs/1000 ft.)		
				LOWER SPEC LIMIT	TARGET WALL	LOWER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT	LOWERSPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT
55PC6279-22-*	22	38	38	.0060	.0075	.136	.146	.154	21.45	23.64	27.17
55PC6279-20-*	20	38	38	.0060	.0080	.158	.167	.174	28.10	29.38	31.10
55PC6279-18-*	18	38	38	.0060	.0080	.175	.185	.194	37.00	38.37	40.10
55PC6279-16-*	16	38	38	.0060	.0080	.189	.201	.210	44.18	45.81	48.19
55PC6279-14-*	14	38	38	.0070	.0080	.223	.235	.244	61.42	63.33	66.25
55PC6279-12-*	12	38	38	.0070	.0085	.261	.275	.286	86.73	88.26	94.11
55PC6279-10-*	10	36	36	.0080	.0090	.320	.336	.350	128.60	136.90	145.10
55PC6279- 8-*	8	36	34	.0080	.0090	.467	.488	.506	228.75	243.08	256.66

CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 150°C

Maximum continuous conductor temperature
VOLTAGE RATING: 600 volts (rms) at sea level
DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz
CROSSLINK VERIFICATION: 300 ± 3°C for 1 hour
JACKET COLOR: White preferred

JACKET ELONGATION AND TENSILE STRENGTH:

Elongation, 50% (minimum)
Tensile Strength, 5000 lbf/in² (minimum)

JACKET FLAWS:

Spark Test, 2500 volts (rms)
Impulse Dielectric Test, 6.0 kV (peak)

SHIELD COVERAGE: 85% (minimum) (each)

VOLTAGE WITHSTAND TEST (Post Environmental):
1000 volts (rms), 60 Hz, 1 minute

PART NUMBER:

The "*" in the part numbers above shall be replaced by color code designators with a slash separating the component wire colors and a dash separating the component wire colors from the jacket color. Colors shown do not necessarily reflect the sequence of manufacturing.

1/ Example: AWG 22, black, brown and red component wires; white jacket:
55PC6279-22-0/1/2-9

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice.
Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.

1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "Axxx".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[55PC6279-14-2/4/6-9CS2502](#) [55PC6279-16-2/4/6-9CS2970](#) [55PC6279-18-2/4/6-9CS2502](#) [55PC6279-16-2/4/6-9CS2502](#) [55PC6279-22-2/4/6-9CS2970](#)