

Relay socket - PR3-BSC1/3X21 - 2833615

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Relay socket PR3..., for octal relay REL-OR with 3 PDT, screw connections, connection facility for input/interference suppression modules, for mounting on NS 35/7.5



Product Features

- Relay base family that can be fitted with 2 PDT or 3 PDT relays



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
Weight per Piece (excluding packing)	66.0 g
Custom tariff number	85366990
Country of origin	China

Technical data

Dimensions

Width	38 mm
Height	75 mm
Depth with retaining bracket	84 mm (EL3-M52)

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

Connection data, input side

Connection name	Input side
Connection method	Screw connection
Stripping length	10 mm

Relay socket - PR3-BSC1/3X21 - 2833615

Technical data

Connection data, input side

Screw thread	M3
Conductor cross section solid	0.2 mm² ... 2.5 mm²
	0.2 mm² ... 2.5 mm² (2 conductors with the same cross-section)
Conductor cross section flexible	0.2 mm² ... 2.5 mm²
	0.2 mm² ... 2.5 mm² (2 conductors with the same cross-section)
Conductor cross section AWG	26 ... 14
	26 ... 14 (2 conductors with the same cross-section)

Connection data, output side

Connection name	Output side
Connection method	Screw connection
Stripping length	10 mm
Screw thread	M3
Conductor cross section solid	0.2 mm² ... 2.5 mm²
	0.2 mm² ... 2.5 mm² (2 conductors with the same cross-section)
Conductor cross section flexible	0.2 mm² ... 2.5 mm²
	0.2 mm² ... 2.5 mm² (2 conductors with the same cross-section)
Conductor cross section AWG	26 ... 14
	26 ... 14 (2 conductors with the same cross-section)

General

Nominal voltage U_N	400 V AC/DC
Nominal current I_N	10 A
Color	green

Standards and Regulations

Connection in acc. with standard	CSA
----------------------------------	-----

Classifications

eCl@ss

eCl@ss 4.0	27371102
eCl@ss 4.1	27371102
eCl@ss 5.0	27371603
eCl@ss 5.1	27371603
eCl@ss 6.0	27371603
eCl@ss 7.0	27371603
eCl@ss 8.0	27371603
eCl@ss 9.0	27371603

Relay socket - PR3-BSC1/3X21 - 2833615

Classifications

ETIM

ETIM 2.0	EC001456
ETIM 3.0	EC001456
ETIM 4.0	EC001456
ETIM 5.0	EC001456

UNSPSC

UNSPSC 6.01	30211917
UNSPSC 7.0901	39121516
UNSPSC 11	39121516
UNSPSC 12.01	39121516
UNSPSC 13.2	39121516

Approvals

Approvals


Approvals


UL Recognized / cUL Recognized / CSA / EAC / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

UL Recognized 


cUL Recognized 
--

CSA 

Relay socket - PR3-BSC1/3X21 - 2833615

Approvals

EAC

cULus Recognized 

Accessories

Required add-on products

Single relay - REL-OR- 24DC/3X21 - 2834274



Pluggable octal relay with power contacts, 3 PDT, test button, mechanical switching position indication, coil voltage 24 V DC

Single relay - REL-OR- 24AC/3X21 - 2834287



Pluggable octal relay with power contacts, 3 PDT, test button, mechanical switching position indication, coil voltage 24 V AC

Single relay - REL-OR-120AC/3X21 - 2834290



Pluggable octal relay with power contacts, 3 PDT, test button, mechanical switching position indication, coil voltage 120 V AC

Single relay - REL-OR-230AC/3X21 - 2834300



Pluggable octal relay with power contacts, 3 PDT, test button, mechanical switching position indication, input voltage: 230 V AC

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[2833615](#)