

# IB IL 24 DO 2-PAC

Order No.: 2861470



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2861470>

Inline digital output terminal block, complete with accessories (connector and labeling field), 2 outputs, 24 V DC, 500 mA, 4-wire connection method



## Commercial data

|                          |                                                                                                       |
|--------------------------|-------------------------------------------------------------------------------------------------------|
| GTIN (EAN)               | <br>4 017918 894399 |
| sales group              | K411                                                                                                  |
| Pack                     | 1 pcs.                                                                                                |
| Customs tariff           | 85389091                                                                                              |
| Catalog page information | Page 184 (AX-2011)                                                                                    |

## Product notes

WEEE/RoHS-compliant since:  
06/02/2008



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Product description

The digital Inline output terminals are designed for the connection of digital actuators, such as electromagnetic valves, contactors or visual indicators.

All the typical applications are covered by the standard automation terminals.

The I/O equipment is connected by a simple or an extended Inline connector, depending on the number of channels. The multi-wire connection method is available in both cases.

The Inline terminals can be labeled using hinged labeling fields. The fields have insert cards that can be labeled individually to suit the application. Additionally, there is the proven ZBFM-6... Zack strip for labeling the terminal points.

#### Technical data

##### General data

|                                          |                                                                                                                                             |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| Width                                    | 12.2 mm                                                                                                                                     |
| Height                                   | 119.8 mm                                                                                                                                    |
| Depth                                    | 71.5 mm                                                                                                                                     |
| Note on dimensions                       | Housing dimensions                                                                                                                          |
| Weight                                   | 41 g                                                                                                                                        |
| Note on weight specifications            | Without plug                                                                                                                                |
| Mounting type                            | DIN rail                                                                                                                                    |
| Ambient temperature (operation)          | -25 °C ... 55 °C                                                                                                                            |
| Ambient temperature (storage/transport)  | -25 °C ... 85 °C                                                                                                                            |
| Permissible humidity (operation)         | 10 % ... 95 % (according to DIN EN 61131-2)                                                                                                 |
| Permissible humidity (storage/transport) | 10 % ... 95 % (according to DIN EN 61131-2)                                                                                                 |
| Air pressure (operation)                 | 70 kPa ... 106 kPa (up to 3000 m above sea level)                                                                                           |
| Air pressure (storage/transport)         | 70 kPa ... 106 kPa (up to 3000 m above sea level)                                                                                           |
| Degree of protection                     | IP20                                                                                                                                        |
| Protection class                         | III, IEC 61140, EN 61140, VDE 0140-1                                                                                                        |
| Test section                             | 5 V supply incoming remote bus/7.5 V supply (bus logic) 500 V AC 50 Hz 1 min                                                                |
|                                          | 5 V supply outgoing remote bus/7.5 V supply (bus logic) 500 V AC 50 Hz 1 min                                                                |
|                                          | 7.5 V supply (bus logics)/24 V supply (I/O) 500 V AC 50 Hz 1 min                                                                            |
|                                          | 24 V supply (I/O) / functional earth ground 500 V AC 50 Hz 1 min                                                                            |
| Diagnostics messages                     | Short-circuit / overload of the digital outputs Error message in the diagnostic code (bus) and display (2 Hz) via the LED (D) on the module |

##### Interface

|                    |                    |
|--------------------|--------------------|
| Fieldbus system    | Lokalbus           |
| Name               | Inline local bus   |
| Connection method  | Inline data jumper |
| Transmission speed | 500 kBaud          |

##### Power supply for module electronics

|                      |                                                                    |
|----------------------|--------------------------------------------------------------------|
| Supply voltage       | 24 V DC (via voltage jumper)                                       |
| Supply voltage range | 19.2 V DC ... 30 V DC (including all tolerances, including ripple) |

|                            |                                 |
|----------------------------|---------------------------------|
| Communications power $U_L$ | 7.5 V (via voltage jumper)      |
| Current consumption        | max. 33 mA (from the local bus) |

#### Inline potential routing

|                                |                         |
|--------------------------------|-------------------------|
| Communications power $U_L$     | 7.5 V DC                |
| Current consumption from $U_L$ | max. 33 mA              |
| Main circuit supply $U_M$      | 24 V DC                 |
| Segment supply voltage $U_S$   | 24 V DC (nominal value) |
| Current consumption from $U_S$ | max. 1 A                |

#### Digital outputs

|                                    |                                                          |
|------------------------------------|----------------------------------------------------------|
| Output name                        | Digital outputs                                          |
| Connection method                  | Spring-cage connection                                   |
|                                    | 2, 3, 4-wire                                             |
| Number of outputs                  | 2                                                        |
| Protective circuit                 | Overload protection, short-circuit protection of outputs |
| Output voltage                     | 24 V DC ( $U_S - 1$ V)                                   |
| Nominal output voltage             | 24 V DC (voltage difference at $I_{nom} \leq 1$ V)       |
| Maximum output current per channel | 500 mA                                                   |
| Maximum output current per module  | 1 A                                                      |
| Nominal load, inductive            | 12 W                                                     |
| Nominal load, lamp                 | 12 W                                                     |
| Nominal load, ohmic                | 12 VA                                                    |

#### Certificates / Approvals



Certification

ABS, BV, CUL, DNV, GL, GOST, LR, UL

Certification Ex:

CUL-EX LIS, UL-EX LIS

## Accessories

| Item | Designation | Description |
|------|-------------|-------------|
|------|-------------|-------------|

### Marking


|         |               |                                                             |
|---------|---------------|-------------------------------------------------------------|
| 0809492 | ESL 62X10     | Insert strip for laser printer, lettering field: 62 x 10 mm |
| 0809502 | ESL 62X46     | Insert strip for laser printer, lettering field: 62 x 46 mm |
| 2727501 | IB IL FIELD 2 | Labeling field, width: 12.2 mm                              |
| 2727515 | IB IL FIELD 8 | Labeling field, width: 48.8 mm                              |

### Plug/Adapter


|         |                |                                                           |
|---------|----------------|-----------------------------------------------------------|
| 2726337 | IB IL SCN-8    | Connector, for digital 1, 2 or 8-channel Inline terminals |
| 2727608 | IB IL SCN-8-CP | Inline connector, colored                                 |

## Diagrams/Drawings


Connection diagram



#### Block diagram



#### Dimensioned drawing



**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;