

Antenna cable - RAD-CAB-EF393- 5M - 2867652

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Antenna cable, outside diameter: 10 mm (0.4 in.), inner conductor: stranded, attenuation: 1.6 / 2.9 / 5.0 dB at 0.9 / 2.4 / 5.8 GHz, connection: 2 x N (male), cable length: 5 m (16 ft.)



The figure shows a version of the product

Your advantages

- ✓ Easy installation, thanks to flexible inner conductor
- ✓ UV resistant
- ✓ Oil-resistant
- ✓ Halogen-free
- ✓ Flame-retardant

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 939021
GTIN	4017918939021

Technical data

Dimensions

Fixed cable length	5 m
External diameter	10.00 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 105 °C
Ambient temperature (storage/transport)	-40 °C ... 105 °C

General

Connection 1	Connector connection
Connection method	N (male)
Note	Both sides

Antenna cable - RAD-CAB-EF393- 5M - 2867652

Technical data

General

Connection method	N (male)
Cable type	EF 393
Outer sheath, material	RADOX®(LSFH)
External sheath, color	black
Minimum bending radius	50.00 mm
Frequency range	0.3 GHz ... 6 GHz
Impedance	50 Ω

Attenuation

868 / 900 MHz	approx. 1.6 dB
2.4 GHz	2.9 dB
5 GHz	5 dB

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 25;
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		EAC-Zulassung
-----	---	---------------

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>