

FEATURES

AC PERFORMANCE

Unity Gain Bandwidth: 34 MHz

Fast Settling: 135 ns to 0.01%

Slew Rate: 250 V/ μ s

Stable at Gains of 1 or Greater

Full Power Bandwidth: 3.9 MHz

DC PERFORMANCE

Input Offset Voltage: 1 mV max (AD843K/B)

Input Bias Current: 0.6 nA typ

Input Voltage Noise: 19 nV/ $\sqrt{\text{Hz}}$

Open Loop Gain: 30 V/mV into a 500 Ω Load

Output Current: 50 mA min

Supply Current: 13 mA max

Available in 8-Pin Plastic Mini-DIP & Cerdip, 16-Pin SOIC, 20-Pin LCC and 12-Pin Hermetic Metal Can Packages

Available in Tape and Reel in Accordance with EIA-481A Standard

Chips and MIL-STD-883B Parts Also Available

APPLICATIONS

High Speed Sample-and-Hold Amplifiers

High Bandwidth Active Filters

High Speed Integrators

High Frequency Signal Conditioning

PRODUCT DESCRIPTION


The AD843 is a fast settling, 34 MHz, CBFET input op amp. The AD843 combines the low (0.6 nA) input bias currents characteristic of a FET input amplifier while still providing a 34 MHz bandwidth and a 135 ns settling time (to within 0.01% of final value for a 10 volt step). The AD843 is a member of the Analog Devices' family of wide bandwidth operational amplifiers. These devices are fabricated using Analog Devices' junction isolated complementary bipolar (CB) process. This process permits a combination of dc precision and wideband ac performance previously unobtainable in a monolithic op amp.

The 250 V/ μ s slew rate and 0.6 nA input bias current of the AD843 ensure excellent performance in high speed sample-and-hold applications and in high speed integrators. This amplifier is also ideally suited for high bandwidth active filters and high frequency signal conditioning circuits.

Unlike many high frequency amplifiers, the AD843 requires no external compensation and it remains stable over its full operating temperature range. It is available in five performance grades: the AD843J and AD843K are rated over the commercial temperature range of 0°C to +70°C. The AD843A and AD843B are rated over the industrial temperature range of -40°C to +85°C. The AD843S is rated over the military temperature range of -55°C to +125°C and is available processed to MIL-STD-883B, Rev. C.


CONNECTION DIAGRAMS

16-Pin SOIC (R-16) Package




NC = NO CONNECT

Plastic (N-8) and Cerdip (Q-8) Package




NC = NO CONNECT

LCC (E-20A) Package



NC = NO CONNECT

TO-8 (H-12A) Package



NOTE: CAN TIED TO V_s
NC = NO CONNECT

The AD843 is offered in either 8-pin plastic DIP or hermetic cerdip packages, in 16-pin SOIC, 20-Pin LCC, or in a 12-pin metal can. Chips are also available.

PRODUCT HIGHLIGHTS

1. The high slew rate, fast settling time and low input bias current of the AD843 make it the ideal amplifier for 12-bit D/A and A/D buffers, for high speed sample-and-hold amplifiers and for high speed integrator circuits. The AD843 can replace many FET input hybrid amplifiers such as the LH0032, LH4104 and OPA600.
2. Fully differential inputs provide outstanding performance in all standard high frequency op amp applications such as signal conditioning and active filters.
3. Laser wafer trimming reduces the input offset voltage to 1 mV max (AD843K and AD843B).
4. Although external offset nulling is unnecessary in many applications, offset null pins are provided.
5. The AD843 does not require external compensation at closed loop gains of 1 or greater.

SPECIFICATIONS (@ T_A +25°C and ± 15 V dc, unless otherwise noted)

AD843

Model	Conditions	AD843J/A			AD843K/B			AD843S ¹			Units
		Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
INPUT OFFSET VOLTAGE ¹ Offset Drift	$T_{min}-T_{max}$	1.0	2.0		0.5	1.0		1.0	2.0		mV
		1.7	4.0		1.2	2.0		3.0	4.5		mV
		12			12	35		12			$\mu\text{V}/^\circ\text{C}$
INPUT BIAS CURRENT	Initial ($T_J = +25^\circ\text{C}$)	50			40			50			pA
	Warmed-Up ²	0.8	2.5		0.6	1.0		0.8	2.5		nA
	$T_{min}-T_{max}$		60/160			23/65			2600		nA
INPUT OFFSET CURRENT	Initial ($T_J = +25^\circ\text{C}$)	30			20			30			pA
	Warmed-Up ²	0.25	1.0		0.2	0.4		0.25	1.0		nA
	$T_{min}-T_{max}$		23/64			9/26			1025		nA
INPUT CHARACTERISTICS Input Resistance Input Capacitance			10^{10}			10^{10}			10^{10}		Ω pF
			6			6			6		
INPUT VOLTAGE RANGE Common Mode		± 10	+12, -13		± 10	+12, -13		± 10	+12, -13		V
COMMON MODE REJECTION	$V_{CM} = \pm 10$ V	60	72		70	76		60	72		dB
	$T_{min}-T_{max}$	60	72		68	76		60	72		dB
INPUT VOLTAGE NOISE Wideband Noise	$f = 10$ kHz		19			19			19		$\text{nV}/\sqrt{\text{Hz}}$
	10 Hz to 10 MHz		60			60			60		$\mu\text{V rms}$
OPEN LOOP GAIN	$V_O = \pm 10$ V		25		20	30			30		V/mV
	$R_{LOAD} \geq 500 \Omega$	15	25		10	25		15	25		V/mV
	$T_{min}-T_{max}$	10	20		10	25		10	25		
OUTPUT CHARACTERISTICS Voltage Current Output Resistance	$R_{LOAD} \geq 500 \Omega$	± 10	+11.5, -12.6		± 10	+11.5, -12.6		± 10	+11.5, -12.6		V
	$V_{OUT} = \pm 10$ V	50			50			50			mA
	Open Loop	12			12			12			Ω
FREQUENCY RESPONSE Unity Gain Bandwidth Full Power Bandwidth ³ Rise Time Overshoot Slew Rate Settling Time Overdrive Recovery Differential Gain Differential Phase	$V_{OUT} = 90$ mV p-p $V_O = 20$ V p-p $R_I \geq 500 \Omega$		34			34			34		MHz
		2.5	3.9		2.5	3.9		2.5	3.9		MHz
	$A_{VCL} = -1$		10			10			10		ns
	$A_{VCL} = -1$		15			15			15		%
	$A_{VCL} = -1$ 10 V Step	160	250		160	250		160	250		V/ μs
	$A_{VCL} = -1$ to 0.1%		95			95			95		ns
	to 0.01%		135			135			135		ns
	-Overdrive		200			200			200		ns
	+Overdrive		700			700			700		ns
	Differential Gain	$f = 4.4$ MHz		0.025			0.025			0.025	
Differential Phase	$f = 4.4$ MHz		0.025			0.025			0.025		Degree
POWER SUPPLY Rated Performance Operating Range Quiescent Current Rejection Ratio Rejection Ratio			± 15			± 15			± 15		V
		± 4.5		± 18	± 4.5		± 18	± 4.5		± 18	V
			12	13		12	13		12	13	mA
	$T_{min}-T_{max}$		12.3	14		12.3	14		12.5	16	mA
	± 5 V to ± 18 V	65	76		70	80		65	76		dB
	$T_{min}-T_{max}$	62	76		68	80		62	76		dB
TEMPERATURE RANGE Operating, Rated Performance Commercial (0 to +70°C) Industrial (-40°C to +85°C) Military (-55°C to +125°C) ⁴			AD843J AD843A			AD843K AD843B			AD843S		
			AD843JN AD843AQ			AD843KN AD843BQ AD843BH			AD843SQ, AD843SQ/883B AD843SH, AD843SH/883B AD843SE/883B		
			AD843JR AD843JR-REEL AD843JChips								
									AD843SChips		
PACKAGE OPTIONS ⁵ Plastic (N-8) Cerdip (Q-8) Metal Can (H-12A) LCC (E-20A) SOIC (R-16) Tape & Reel Chips			AD843JN AD843AQ			AD843KN AD843BQ AD843BH			AD843SQ, AD843SQ/883B AD843SH, AD843SH/883B AD843SE/883B		
			AD843JR AD843JR-REEL AD843JChips								

9

AD843

NOTES

¹Standard Military Drawings Available: 5962-9098001M2A (SE/883B), 5962-9098001MXA (SH/883B), 5962-9098001MPA (SQ/883B).

²Specifications are guaranteed after 5 minutes at $T_A = +25^\circ\text{C}$.

³Full power bandwidth = Slew Rate/2 π V peak.

⁴All "S" grade T_{\min} - T_{\max} specifications are tested with automatic test equipment at $T_A = -55^\circ\text{C}$ and $T_A = +125^\circ\text{C}$.

⁵For outline information see Package Information section.

Specifications subject to change without notice.

Specifications in **boldface** are tested on all production units at final electrical test. Results from those tests are used to calculate outgoing quality levels.

All min and max specifications are guaranteed although only those shown in **boldface** are tested on all production units.

ABSOLUTE MAXIMUM RATINGS¹

Supply Voltage	$\pm 18\text{ V}$
Internal Power Dissipation ²	
Plastic Package	1.50 Watts
Cerdip Package	1.35 Watts
12-Pin Header Package	1.80 Watts
16-Pin SOIC Package	1.50 Watts
20-Pin LCC Package	1.00 Watt
Input Voltage	$\pm V_S$
Output Short Circuit Duration	Indefinite
Differential Input Voltage	$+V_S$ and $-V_S$
Storage Temperature Range (N, R)	-65°C to $+125^\circ\text{C}$
Storage Temperature Range (Q, H, E)	-65°C to $+150^\circ\text{C}$
Operating Temperature Range	
AD843J/K	0 to $+70^\circ\text{C}$
AD843A/B	-40°C to $+85^\circ\text{C}$
AD843S	-55°C to $+125^\circ\text{C}$
Lead Temperature Range (Soldering 60 sec)	$+300^\circ\text{C}$
ESD Rating	500 V

NOTES

¹Stresses above those listed under "Absolute Maximum Ratings" may cause permanent damage to the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

²8-Pin Plastic Package: $\theta_{JA} = 100^\circ\text{C}/\text{Watt}$

8-Pin Cerdip Package: $\theta_{JA} = 110^\circ\text{C}/\text{Watt}$

12-Pin Header Package: $\theta_{JA} = 80^\circ\text{C}/\text{Watt}$

16-Pin SOIC Package: $\theta_{JA} = 100^\circ\text{C}/\text{Watt}$

20-Pin LCC Package: $\theta_{JA} = 150^\circ\text{C}/\text{Watt}$

METALIZATION PHOTOGRAPH

Contact factory for latest dimensions.
Dimensions shown in inches and (mm).

