

2N3903, 2N3904

2N3903 is a Preferred Device

General Purpose Transistors

NPN Silicon

Features

- Pb-Free Package May be Available. The G-Suffix Denotes a Pb-Free Lead Finish


MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector-Emitter Voltage	V_{CEO}	40	Vdc
Collector-Base Voltage	V_{CBO}	60	Vdc
Emitter-Base Voltage	V_{EBO}	6.0	Vdc
Collector Current - Continuous	I_C	200	mA dc
Total Device Dissipation @ $T_A = 25^\circ\text{C}$ Derate above 25°C	P_D	625 5.0	mW mW/ $^\circ\text{C}$
Total Device Dissipation @ $T_C = 25^\circ\text{C}$ Derate above 25°C	P_D	1.5 12	W mW/ $^\circ\text{C}$
Operating and Storage Junction Temperature Range	T_J, T_{stg}	-55 to +150	$^\circ\text{C}$

THERMAL CHARACTERISTICS (Note 1)

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction-to-Ambient	$R_{\theta JA}$	200	$^\circ\text{C/W}$
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	83.3	$^\circ\text{C/W}$

1. Indicates Data in addition to JEDEC Requirements.




*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.




ON Semiconductor®

<http://onsemi.com>



TO-92
CASE 29
STYLE 1

MARKING DIAGRAMS



ORDERING INFORMATION

Device	Package	Shipping [†]
2N3903	TO-92	5000 Units/Box
2N3903RLRM	TO-92	2000/Ammo Pack
2N3904	TO-92	5000 Units/Box
2N3904RLRA	TO-92	2000/Tape & Reel
2N3904RLRE	TO-92	2000/Tape & Reel
2N3904RLRM	TO-92	2000/Ammo Pack
2N3904RLRMG	TO-92	2000/Ammo Pack
2N3904RLRP	TO-92	2000/Ammo Pack
2N3904RL1	TO-92	2000/Tape & Reel
2N3904ZL1	TO-92	2000/Ammo Pack

[†]For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

Preferred devices are recommended choices for future use and best overall value.

2N3903, 2N3904

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
----------------	--------	-----	-----	------

OFF CHARACTERISTICS

Collector–Emitter Breakdown Voltage (Note 2) (I _C = 1.0 mA _{DC} , I _B = 0)	V _{(BR)CEO}	40	–	V _{DC}
Collector–Base Breakdown Voltage (I _C = 10 μA _{DC} , I _E = 0)	V _{(BR)CBO}	60	–	V _{DC}
Emitter–Base Breakdown Voltage (I _E = 10 μA _{DC} , I _C = 0)	V _{(BR)EBO}	6.0	–	V _{DC}
Base Cutoff Current (V _{CE} = 30 V _{DC} , V _{EB} = 3.0 V _{DC})	I _{BL}	–	50	nA _{DC}
Collector Cutoff Current (V _{CE} = 30 V _{DC} , V _{EB} = 3.0 V _{DC})	I _{CEX}	–	50	nA _{DC}

ON CHARACTERISTICS

DC Current Gain (Note 2)	h _{FE}				–
(I _C = 0.1 mA _{DC} , V _{CE} = 1.0 V _{DC})					
2N3903					
2N3904					
(I _C = 1.0 mA _{DC} , V _{CE} = 1.0 V _{DC})					
2N3903					
2N3904					
(I _C = 10 mA _{DC} , V _{CE} = 1.0 V _{DC})					
2N3903					
2N3904					
(I _C = 50 mA _{DC} , V _{CE} = 1.0 V _{DC})					
2N3903					
2N3904					
(I _C = 100 mA _{DC} , V _{CE} = 1.0 V _{DC})					
2N3903					
2N3904					
Collector–Emitter Saturation Voltage (Note 2)	V _{CE(sat)}				V _{DC}
(I _C = 10 mA _{DC} , I _B = 1.0 mA _{DC})					
(I _C = 50 mA _{DC} , I _B = 5.0 mA _{DC})					
Base–Emitter Saturation Voltage (Note 2)	V _{BE(sat)}				V _{DC}
(I _C = 10 mA _{DC} , I _B = 1.0 mA _{DC})					
(I _C = 50 mA _{DC} , I _B = 5.0 mA _{DC})					

SMALL–SIGNAL CHARACTERISTICS


Current–Gain – Bandwidth Product	2N3903 2N3904	f _T	250 300	– –	MHz
(I _C = 10 mA _{DC} , V _{CE} = 20 V _{DC} , f = 100 MHz)					
Output Capacitance (V _{CB} = 5.0 V _{DC} , I _E = 0, f = 1.0 MHz)		C _{obo}	–	4.0	pF
Input Capacitance (V _{EB} = 0.5 V _{DC} , I _C = 0, f = 1.0 MHz)		C _{ibo}	–	8.0	pF
Input Impedance	2N3903 2N3904	h _{ie}	1.0 1.0	8.0 10	k Ω
(I _C = 1.0 mA _{DC} , V _{CE} = 10 V _{DC} , f = 1.0 kHz)					
Voltage Feedback Ratio	2N3903 2N3904	h _{re}	0.1 0.5	5.0 8.0	X 10 ^{–4}
(I _C = 1.0 mA _{DC} , V _{CE} = 10 V _{DC} , f = 1.0 kHz)					
Small–Signal Current Gain	2N3903 2N3904	h _{fe}	50 100	200 400	–
(I _C = 1.0 mA _{DC} , V _{CE} = 10 V _{DC} , f = 1.0 kHz)					
Output Admittance (I _C = 1.0 mA _{DC} , V _{CE} = 10 V _{DC} , f = 1.0 kHz)		h _{oe}	1.0	40	μmhos
Noise Figure	2N3903 2N3904	NF	– –	6.0 5.0	dB
(I _C = 100 μA _{DC} , V _{CE} = 5.0 V _{DC} , R _S = 1.0 k Ω, f = 1.0 kHz)					

SWITCHING CHARACTERISTICS


Delay Time	(V _{CC} = 3.0 V _{DC} , V _{BE} = 0.5 V _{DC} , I _C = 10 mA _{DC} , I _{B1} = 1.0 mA _{DC})	t _d	–	35	ns
Rise Time		t _r	–	35	ns
Storage Time	(V _{CC} = 3.0 V _{DC} , I _C = 10 mA _{DC} , I _{B1} = I _{B2} = 1.0 mA _{DC})	t _s	– –	175 200	ns
Fall Time		t _f	–	50	ns

2. Pulse Test: Pulse Width ≤ 300 μs; Duty Cycle ≤ 2%.

2N3903, 2N3904



**Figure 1. Delay and Rise Time
Equivalent Test Circuit**



**Figure 2. Storage and Fall Time
Equivalent Test Circuit**

* Total shunt capacitance of test jig and connectors

TYPICAL TRANSIENT CHARACTERISTICS

— $T_J = 25^\circ\text{C}$
 - - - $T_J = 125^\circ\text{C}$




Figure 3. Capacitance




Figure 4. Charge Data




Figure 5. Turn-On Time




Figure 6. Rise Time




Figure 7. Storage Time




Figure 8. Fall Time

TYPICAL AUDIO SMALL-SIGNAL CHARACTERISTICS NOISE FIGURE VARIATIONS

($V_{CE} = 5.0$ Vdc, $T_A = 25^\circ\text{C}$, Bandwidth = 1.0 Hz)




Figure 9.




Figure 10.

h PARAMETERS

($V_{CE} = 10$ Vdc, $f = 1.0$ kHz, $T_A = 25^\circ\text{C}$)




Figure 11. Current Gain




Figure 12. Output Admittance




Figure 13. Input Impedance




Figure 14. Voltage Feedback Ratio

2N3903, 2N3904

TYPICAL STATIC CHARACTERISTICS




Figure 15. DC Current Gain




Figure 16. Collector Saturation Region




Figure 17. "ON" Voltages






Figure 18. Temperature Coefficients

2N3903, 2N3904

PACKAGE DIMENSIONS

TO-92
TO-226AA
CASE 29-11
ISSUE AL



NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.175	0.205	4.45	5.20
B	0.170	0.210	4.32	5.33
C	0.125	0.165	3.18	4.19
D	0.016	0.021	0.407	0.533
G	0.045	0.055	1.15	1.39
H	0.095	0.105	2.42	2.66
J	0.015	0.020	0.39	0.50
K	0.500	---	12.70	---
L	0.250	---	6.35	---
N	0.080	0.105	2.04	2.66
P	---	0.100	---	2.54
R	0.115	---	2.93	---
V	0.135	---	3.43	---

STYLE 1:

- PIN 1. EMITTER
2. BASE
3. COLLECTOR

STYLE 14:

- PIN 1. EMITTER
2. COLLECTOR
3. BASE

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA

Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada

Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada

Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada

Japan: ON Semiconductor, Japan Customer Focus Center
2-9-1 Kamimeguro, Meguro-ku, Tokyo, Japan 153-0051
Phone: 81-3-5773-3850

ON Semiconductor Website: <http://onsemi.com>

Order Literature: <http://www.onsemi.com/litorder>

For additional information, please contact your
local Sales Representative.