


Honeywell Sensing and Control

Home> Products > MICRO SWITCH™ Toggle Switches > TL > Product Page

■ Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

2TL5-7



TL Series Toggle Switch, 2 pole, 3 position, Screw terminal, Tab Lever

Search for product and support information.

All Sensing and Contro

Keyword Search

Product Search

Part number search:

Use (*) to expand search

Specification Search

Actual product appearance may vary.

Features

Environment proof sealing
1,2, and 4 pole circuitry
Standard and pull-to-unlock levers
2 and 3 position, maintained and
momentary toggle action
Temperature range:-85? F to +160? F
Completely sealed switching chamber
Step-design case provides added
space between terminals to help
prevent shorting
UL recognized, CSA certified
CE approved

Potential Applications

Industrial machinery and equipment
Military and commercial aviation
Construction equipment
Test instruments
Agricultural machinery
Process control
Medical instrumentation

Description

MICRO SWITCH™TL Series toggle switches have high strength, temperature resistant, non-tracking case material and silver cadmium oxide contacts. Pułto-Unlock toggle levers prevent accidental operation; the lever must be pulled approx. 2,3 mm (0.09 inches) to change positions.

Supporting Documentation

Accessory: Lever Sleeve

Accessory: Seals

Accessory: Nuts

Engineering Drawing

Product Specifications		
Circuitry/Operating action	Keyway Momentary Center Position Position 1 2 3 1 2 3 6 5 4 6 5 4 ON OFF	Opposite Keyway Momentary Position 1 2 3 6 5 4 ON
Product Type	MICRO SWITCH™ Toggle Switch	
Ampere/Voltage Range (Resistive Load)	0.75 A at 115 Vdc,0.5 A at 250 Vdc,0.5 A to 10 A at 0.5 Vac to 277 Vac,0.5 A to 18 A at 0.5 Vdc to 28 Vdc	
Circuitry	DPDT	
Action	3 position	
Mounting	Bushing 15/32 in	
Termination	Screw	
Lever Type	Tab	
UL/CSA Rating Code	L192: 10 A -125, 250, 277 Vac; 1/4 Hp Hp - 250, 277 Vac; 3 A -125 Vac "L"	-125 Vac; 1/2
Comment	Bright chrome lever	
Availability	Global	
UNSPSC Code	30211908	
UNSPSC Commodity	30211908 Toggle switches	
Series Name	TL	