

## Bolt connection terminal block - RSC 6 - 3075870

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Feed-through terminal block with bolt connection method, cross section: 2.5 - 35 mm<sup>2</sup>, AWG: 12 - 2, width 17 mm, color: gray

### Product Features

- Easy grouping of flange terminal blocks
- Flange terminal blocks for direct mounting in control boxes



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 40 pc    |
| Weight per Piece (excluding packing) | 37.5 g   |
| Custom tariff number                 | 85369010 |
| Country of origin                    | India    |

### Technical data

#### General

|  |                    |
|--|--------------------|
| Number of levels                       | 1                  |
| Number of connections                  | 2                  |
| Potentials                             | 1                  |
| Nominal cross section                  | 35 mm <sup>2</sup> |
| Color                                  | gray               |
| Insulating material                    | PA                 |
| Flammability rating according to UL 94 | V0                 |
| Rated surge voltage                    | 8 kV               |
| Degree of pollution                    | 3                  |
| Overvoltage category                   | III                |
| Insulating material group              | I                  |

# Bolt connection terminal block - RSC 6 - 3075870

## Technical data

### General

|   |   |
|---|---|
| Maximum load current  | 125 A (with 35 mm <sup>2</sup> conductor cross section) |
| Nominal current I <sub>N</sub>  | 125 A   |
| Nominal voltage U <sub>N</sub>  | 800 V   |
| Open side panel   | No  |
| Result of surge voltage test  | Test passed   |
| Surge voltage test setpoint   | 9.8 kV  |
| Result of power-frequency withstand voltage test  | Test passed   |
| Power frequency withstand voltage setpoint  | 2 kV  |
| Result of the test for mechanical stability of terminal points (5 x conductor connection) | Test passed   |
| Result of tight fit on support  | Test passed   |
| Tight fit on carrier  | NS 35/NS 32   |
| Setpoint  | 10 N  |
| Result of voltage-drop test   | Test passed   |
| Requirements, voltage drop  | ≤ 3.2 mV  |
| Result of temperature-rise test   | Test passed   |
| Short circuit stability result  | Test passed   |
| Conductor cross section short circuit testing   | 35 mm <sup>2</sup>                                      |
| Short-time current  | 4.2 kA  |
| Result of thermal test  | Test passed   |
| Proof of thermal characteristics (needle flame) effective duration                        | 30 s  |
| Oscillation, broadband noise test result  | Test passed   |
| Test specification, oscillation, broadband noise  | DIN EN 50155 (VDE 0115-200):2008-03                     |
| Test spectrum   | Service life test category 1, class B, body mounted     |
| Test frequency  | f <sub>1</sub> = 5 Hz to f <sub>2</sub> = 150 Hz        |
| ASD level   | 1.857 (m/s <sup>2</sup> ) <sup>2</sup> /Hz              |
| Acceleration  | 0,8 g   |
| Test duration per axis  | 5 h   |
| Test directions   | X-, Y- and Z-axis                                       |
| Shock test result   | Test passed   |
| Test specification, shock test  | DIN EN 50155 (VDE 0115-200):2008-03                     |
| Shock form  | Half-sine   |
| Acceleration  | 5 g   |
| Shock duration  | 30 ms   |
| Number of shocks per direction  | 3   |
| Test directions   | X-, Y- and Z-axis (pos. and neg.)                       |
| Relative insulation material temperature index (Elec., UL 746 B)                          | 130 °C  |

## Bolt connection terminal block - RSC 6 - 3075870

### Technical data

#### General

|   |        |
|---|--------|
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C |
| Static insulating material application in cold                          | -60 °C |

#### Dimensions

|                  |          |
|------------------|----------|
| Width            | 17 mm    |
| End cover width  | 2.2 mm   |
| Length           | 80.8 mm  |
| Height NS 35/7,5 | 49.8 mm  |
| Height NS 35/15  | 57.3 mm  |
| Height NS 32     | 54.8 mm  |
| Pitch            | 17.00 mm |

#### Connection data

|   |                     |
|---|---------------------|
| Note  | Connection bolts    |
| Connection method                           | Bolt connection     |
| Connection in acc. with standard            | IEC 60947-7-1       |
| Conductor cross section solid min.          | 2.5 mm <sup>2</sup> |
| Conductor cross section solid max.          | 35 mm <sup>2</sup>  |
| Conductor cross section AWG min.            | 12                  |
| Conductor cross section AWG max.            | 2                   |
| Conductor cross section flexible min.       | 2.5 mm <sup>2</sup> |
| Conductor cross section flexible max.       | 35 mm <sup>2</sup>  |
| Min. AWG conductor cross section, flexible  | 12                  |
| Max. AWG conductor cross section, flexible  | 2                   |
| Cable lug connection according to standard  | DIN 46 234          |
| Min. cross section for cable lug connection | 6 mm <sup>2</sup>   |
| Max. cross section for cable lug connection | 35 mm <sup>2</sup>  |
| Hole diameter, min.                         | 6.5 mm              |
| Cable lug width, max.                       | 15 mm               |
| Bolt diameter                               | 6 mm                |
| Cable lug connection according to standard  | DIN 46237           |
| Min. cross section for cable lug connection | 2.5 mm <sup>2</sup> |
| Max. cross section for cable lug connection | 6 mm <sup>2</sup>   |
| Hole diameter, min.                         | 6.5 mm              |
| Cable lug width, max.                       | 11 mm               |
| Bolt diameter                               | 6 mm                |
| Screw thread                                | M6                  |
| Tightening torque, min                      | 3.2 Nm              |

## Bolt connection terminal block - RSC 6 - 3075870

### Technical data

#### Connection data

|                       |        |
|-----------------------|--------|
| Tightening torque max | 3.7 Nm |
|-----------------------|--------|

#### Standards and Regulations

|  |               |
|--|---------------|
| Connection in acc. with standard       | CUL           |
|  | IEC 60947-7-1 |
|  | DIN 46 234    |
|  | DIN 46237     |
| Flammability rating according to UL 94 | V0            |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141120 |
| eCl@ss 4.1 | 27141120 |
| eCl@ss 5.0 | 27141120 |
| eCl@ss 5.1 | 27141120 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 7.0 | 27141120 |
| eCl@ss 8.0 | 27141120 |
| eCl@ss 9.0 | 27141120 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC000897 |
| ETIM 5.0 | EC000897 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

### Approvals

#### Approvals

---

## Bolt connection terminal block - RSC 6 - 3075870

### Approvals


#### Approvals


UL Recognized / cUL Recognized / EAC / CSA / cULus Recognized

#### Ex Approvals


#### Approvals submitted


#### Approval details

|   |       |       |
|---|-------|-------|
| UL Recognized  |       |       |
|   | B     | C     |
| Nominal current I <sub>N</sub>  | 115 A | 115 A |
| Nominal voltage U <sub>N</sub>  | 600 V | 600 V |

|  |       |       |   |
|--|-------|-------|---|
| cUL Recognized  |       |       |   |
|  | B     | C     | D |
| Nominal current I <sub>N</sub>   | 115 A | 115 A |   |
| Nominal voltage U <sub>N</sub>   | 600 V | 600 V |   |

|     |
|-----|
| EAC |
|-----|

|   |       |       |
|---|-------|-------|
| CSA  |       |       |
|   | B     | C     |
| mm <sup>2</sup> /AWG/kcmil  | 12-2  | 12-2  |
| Nominal current I <sub>N</sub>  | 115 A | 115 A |
| Nominal voltage U <sub>N</sub>  | 600 V | 600 V |

|  |  |
|--|--|
| cULus Recognized  |  |
|--|--|

## Bolt connection terminal block - RSC 6 - 3075870

### Drawings

Circuit diagram

