

Cable tie - WT-HF 3,6X290 BK-L - 3240754

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable binders for quick and secure bundling, standard version

RoHS

Key Commercial Data

Packing unit	1 STK
Minimum order quantity	500 STK
GTIN	 4 046356 704700
GTIN	4046356704700
Weight per Piece (excluding packing)	1.320 g
Custom tariff number	39269097
Country of origin	Italy

Technical data

Dimensions

Length (b)	290 mm
Width (a)	3.6 mm
Cable diameter	3 mm ... 80 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (assembly)	-10 °C ... 60 °C
Optimum ambient temperature (storage/transport)	23 °C 50 % Polyamide 6.6 has pronounced hygroscopic properties. It absorbs or releases water in accordance with the level of humidity within its environment. Its properties are ideal when the percentage of water is 2 - 3%. The packaging, which is tailored specifically to the product concerned, contains the optimum level of moisture. To ensure that the ideal

Cable tie - WT-HF 3,6X290 BK-L - 3240754

Technical data

Ambient conditions

	properties are maintained, the following points should be observed during storage: Keep product stored inside sealed original packaging, carry out any product processing soon after breaking open the packaging, avoid direct sunlight, avoid direct heat.
Short-term temperature	110 °C

General

Color	black
Type	Internal teeth
Components	free from silicone and halogen
Flammability rating according to UL 94	V2
Material	PA 6.6

Standards and Regulations

Resistance to UV radiation	no
Connection in acc. with standard	UL
Flammability rating according to UL 94	V2

Approvals

Approvals

Approvals

UL Recognized / LR / GL / BV / DNV / RINA

Ex Approvals





Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm
---------------	---	---

LR		http://www.lr.org/en
----	---	---

Cable tie - WT-HF 3,6X290 BK-L - 3240754

Approvals

GL		http://exchange.dnv.com/tari/
BV		http://www.veristar.com/portal/veristarinfo/generalinfo/approved/approvedProducts/equipmentAndMaterials
DNV		http://exchange.dnv.com/tari/
RINA		http://www.rina.org/en