




CRIMP RINGS & SPADES



✓ Active

↓ **PRODUCT DRAWING**
English

TE CONNECTIVITY (TE)

PIDG SPDFLG 22-16COM22-18MIL 8

[PIDG](#) | [PIDG](#)

32498

TE Internal Number: 32498

Alias ID: 798370-000, AMP-0-0032498-0

[Always EU RoHS/ELV Compliant](#)

Terminal Shape **Spade Tongue**

Stud Diameter **4.17 mm [.164 in]**

Tongue Thickness **.84 mm [.033 in]**

Heavy Duty **No**

Wire Insulation Diameter (Max) **3.56 mm [.14 in]**

Product Drawings

[WIRE TERMINAL, PIDG FLANGED SPADE, WIRE SIZE: 22 16](#)

PDF ([TIFF AVAILABLE](#))

English

[WIRE TERMINAL, PIDG FLANGED SPADE, WIRE SIZE: 22 16](#)

PDF ([TIFF AVAILABLE](#))

English

Product Specifications

Application Specification

[Pre-Insulated Diamond Grip \(PIDG\) Terminals, Splices, And End Caps](#)

PDF

English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Barrel Type

Closed Barrel

Wire/Cable Type

Regular Wire

Insulated

Yes

Insulated Wire Support

Yes

Support Style

Insulation Support

Stud Size

8, M4

Shape Code

SPADE-024

Electrical Characteristics

Voltage (Max) (V)

300

Body Features

Plating Material

Copper, Tin

	Insulation Material	Nylon
	Inspection Slot	No
	Insulation Type	Pre-Insulated
Contact Features	Terminal Shape	Spade Tongue
	Terminal Orientation	Flanged, Straight
Dimensions	Stud Diameter	4.17 mm [.164 in]
	Tongue Thickness	.84 mm [.033 in]
	Wire Insulation Diameter (Max)	3.56 mm [.14 in]
	Wire Insulation Diameter (in)	.105 – .14
	Wire Size (AWG)	22
	Wire Size (mm²)	.3 – 1.42
	Wire Size (CMA)	509 – 3260
	Material Thickness	.79 mm [.031 in]
	Overall Length	21.08 mm [.83 in]
Operation/Application	Heavy Duty	No
Industry Standards	Government Qualified	No
Packaging Features	Packaging Method	Loose Piece
	Packaging Quantity	1000
Other	Barrel Color	Red
Product Compliance	Statement of Compliance PDF	
	VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

THROUGH-HOLE RESISTORS



YR1 0.1% 280K
YR1B280KCC

CRIMP RINGS & SPADES



PIDG RING
130205

THROUGH-HOLE RESISTORS



2W SM M/OX 5% 12K
ROX25J12K

SURFACE MOUNT RESISTORS



CRG0805 1% 120K
CRG0805F120K

>

