

SPECIFICATIONS				
CONTACT CARRIER MATERIAL	TPU			
MOLDED HEAD MATERIAL/COLOR	TPU/BLUE-GRAY			
CONTACT MATERIAL/PLATING	BRASS/GOLD			
COUPLING NUT MATERIAL/PLATING	BRASS/NICKEL			
RATED CURRENT [A]	4.0 A			
RATED VOLTAGE [V]	250 V			
OUTER CABLE JACKET MATERIAL/COLOR	TPE/TEAL			
CONDUCTOR INSULATION MATERIAL	HDPE			
NUMBER OF CONDUCTORS [AWG]	2UTPx24 AWG, STRANDED			
SHIELDING	ALUM. FOIL AND TINNED COPPER BRAIDED			
TEMPERATURE RANGE	-40°C to +80°C (-40°F to +176°F)			
PROTECTION CLASS	IP67			

	* METERS SEE NOTE 1	-
ø15.0 [0.59]  SHIELDED AND ANTI-VIBRATION COUPLING NUT	Ø6.7 [0.26]	7.0 [0.28] 50.0 [1.97]

KMY 11/19/14 47778

ECO NO.

CABLE LENGTH	TOLERANCE *		
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER		
STRIP LENGTH	TOLERANCE *		
0-7mm	±0.5mm		
8-29mm	±1.0mm		
30-49mm	±2.0mm		
50-69mm	±3.0mm		
70-100mm	±4.0mm		
OVER 100mm	±5.0mm		
* UNLESS OTHERWISE SPECIFIED			

## NOTES:

REV DESCRIPTION

H UPDATE CABLE DIAMETER

1. "\*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

	"441" RAW CABLE SPECIFICATIONS					
CADLE	CABLE PROPERTIES: OIL, UV. WELD SLAG, AND ABRASION RESISTANT					
CABLE	PRUPERTIES:	OIL, UV, WELD SLAG, AND ABRASION RESISTANT				
VOLTAGE	E RATINGS (MAX):	600V				
CATEGO	RY:	CAT 5e; (CABLE WILL MEET CAT 5e CHANNEL REQUIREMENTS TO 90M LENGTH)				
POE CO	MPLIANT (802.3af):	UP TO 80M LENGTH WHEN INSTALLED PER RECOMMENDATIONS IN TIA TSB-184				
FLEXLIF	E:	10X CABLE OD MIN: 1 MILLION CYCLES (TICK TOCK)				
		20X CABLE OD MIN: 10 MILLION CYCLES (TICK TOCK)				
		TORSION TEST: 3 MILLION CYCLES (11b LOAD, 360°-71 CYCLES/min)				
APPROV	ALS:	C(UL)US CMX-OUTDOOR-CM LISTED, AWM RECOGNIZED				
		COMPLIANT WITH NEC ARTICLE 800 COMMUNICATIONS CABLES				

## SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS  1. 2. 3. 4.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.	High Technology	Sensors and Automation Controls	3000 CAMPUS MINNEAPOLIS, M 1-800-544- (763) 553- (763) 553- turck.co	IN 55441 -7769 7300 0708 fax
MATERIAL	ALL DIMENSIONS DISPLAYED ON THIS	DRFT RDS	DATE 08/19/05 SCALE 1=1.0	DESCRIPTION RSSD 44	1-*M	
DRAWING ARE FOR REFERENCE ONLY  NISH  CONTACT TURCK FOR MORE		UNIT OF MEASUREMENT  MILLIMETER [ INCH ]		IDENTIFICATION NO.		REV H
	INFORMATION	DO NOT SCALE	THIS DRAWING	FILE: 777011708	SHEE	T 1 OF 1