



SAFETY ISOLATING TRANSFORMER

POWER : 5VA
INPUT VOLTAGE : 230V
FREQUENCY : 50/60Hz
NOMINAL OUTPUT VOLTAGE : 9V

NON SHORT CIRCUIT PROOF TRANSFORMER
IP00
UL94V0

OPERATING TEMPERATURE : -25°C to 50°C
STORAGE TEMPERATURE : -25°C to 85°C
INSULATION CLASS (IEC85) : B
REQUIRED PROTECTION : 630mA FUSE ON SECONDARY

STANDARDS :
UL506 (File E111078)
CSA 22-2 (File E111078)
VDE (File Ref:1398300)
EN60950 (File Ref:1398300)
EN61558-1 (File Ref:1398300)
EN61558-2-6 (File Ref:1398300)
CE



D					
C					
B					
A					
Rev	Date	Modification	Dessiné	Visa	

Finition:		Tolérance générale:	
Finition:		General tolerance:	
Ech: 1:1	Matériau:		
	Matériau:		
Dessiné par	ROUSSEL.Ch	Date:	27/09/2005
		Visa:	J.P.M.
DATA SHEET 44230			
EI 42x14.8			
myrra		22 Allée du Clos des Charmes Z.A. Les Portes de la Forêt 77090 COLLESEN Tel : 01-60-37-55-55 Fax : 01-60-17-12-00	
		DS44230	