


SPECIFICATION CONTROL DRAWING			SCD		44A082X	
Title TWO CONDUCTOR CABLE, UNSHIELDED, UNJACKETED, 600 VOLT			Date 11-3-15		Revision E	
This specification sheet forms a part of the latest issue of Raychem Specification 44.						
COMPONENT WIRES - 44A081X 						
CABLE CONSTRUCTION DETAILS						
PART NUMBER 1/	CONDUCTOR SIZE (AWG)	OUTSIDE DIAMETER (inch)		MAXIMUM WEIGHT (lbs/1000 ft.)		
		NOMINAL	MAXIMUM			
44A082X-26-*	26	.096	.100	3.9		
44A082X-24-*	24	.108	.112	5.5		
44A082X-22-*	22	.124	.130	8.0		
44A082X-20-*	20	.140	.146	11.2		
44A082X-18-*	18	.160	.166	16.3		
44A082X-16-*	16	.178	.186	20.6		
44A082X-14-*	14	.216	.224	31.6		
44A082X-12-*	12	.252	.260	46.9		
44A082X-10-*	10	.310	.320	72.8		
44A082X-8-*	8	.428	.440	128.		
CABLE RATINGS AND ADDITIONAL REQUIREMENTS						
TEMPERATURE RATING: 150°C Maximum continuous conductor temperature			1/ PART NUMBER:			
VOLTAGE RATING: 600 volts (rms) at sea level			The "X" in the part numbers above shall be replaced with a conductor material designator as follows:			
DIELECTRIC WITHSTAND: 2500 volts (rms), 60 Hz, 1 minute			1 tin-coated copper			
INSULATION FLAWS: Spark Test, 5.7 kV (rms) at 3 kHz			2 silver-coated copper (AWG 24-8 only)			
Impulse Dielectric Test, 8.0 kV (peak)			3 nickel-coated copper (AWG 24-12 only)			
			4 silver-coated high-strength copper alloy (AWG 26-20 only)			
			The "*" in the part numbers above shall be replaced by color code designators with a slash separating the component wire colors.			
			Example: AWG 20, tin-coated copper conductors;			
			black and brown component wires:			
			44A0821-20-0/1			
NOTE: Nominal values are for information only. Nominal values are not requirements.						
Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice.						
Tyco Electronics Corporation also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.						
1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "Axxx".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.						
Page 1 of 1	Raychem, TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.			 Raychem Wire & Cable 501 Oakside Avenue Redwood City, CA 94063-3800 Phone: 1-800-227-8816 Fax: 1-650-361-6297		
	DIMENSIONS ARE IN INCHES AND, UNLESS OTHERWISE DESIGNATED, ARE NOMINAL					
	THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.					