

RECTANGULAR POWER CONNECTORS



✓ Active

[PRODUCT DRAWING](#)

English

[3D PDF](#)

TE CONNECTIVITY (TE)

MICRO MNL HDR ASSY S/ROW LF

MATE-N-LOK | Micro MATE-N-LOK

2-1445099-2

TE Internal Number: 2-1445099-2

Always EU RoHS/ELV Compliant

Product Type **Header**

Housing Type **Plug**

Connector System **Wire-to-Board**

Applies To **Printed Circuit Board**

Contact Current Rating (A) **5**

Product Drawings

RIGHT ANGLE SURFACE MNT HEADER ASSY, 0.76 MIC GOLD CONTACTS,
W/THRU HOLE HOLDDOW

PDF

English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP

English

[3D PDF](#)

PDF

3D

[Customer View Model](#)

3D_IGS.ZIP

English

[Customer View Model](#)

3D_STP.ZIP

English

Catalog Pages/Data Sheets

[SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG](#)

PDF

English

[1773458-4_MICRO_MATE_N_LOK_CONNECTOR_SYSTEM_QRG](#)

PDF

English

Product Specifications

Application Specification

[Micro MATE-N-LOK Connectors](#)

PDF

English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	Header
	Housing Type	Plug
	Contact Type	Pin
<hr/>		
Configuration Features	Number of Positions	2
	Centerline	3 mm [.118 in]
	PCB Mounting Orientation	Right Angle
	Number of Rows	1
	Multiple Contact Types	Without
	Contact Layout	Inline
<hr/>		
Electrical Characteristics	Contact Current Rating (A)	5
	Operating Voltage (VAC)	250
	Operating Voltage (VDC)	250
<hr/>		
Contact Features	Contact Retention	Without
	Contact Termination Area Plating Material	Tin
	Contact Termination Area Plating Thickness	2.54 µm [100 µin]
<hr/>		
Termination Features	Wire/Cable Size (AWG)	30 – 20
	Termination Method to Wire/Cable	Solder
	Termination Method to PC Board	Surface Mount
	Termination Post/Tail Length	1.4 mm [.055 in]
<hr/>		
Mechanical Attachment	Mating Alignment	With
	Mating Retention	With
	PCB Mount Retention	With
	PCB Mount Retention Type	Boardlocks
	Mating Alignment Type	Polarization
	PCB Mount Alignment	Without
	Mating Retention Type	Locking Tab
	Panel Mount Retention	Without
	Strain Relief	Without
<hr/>		
Housing Features	UL Flammability Rating	UL 94V-0
	Housing Color	Black
	Housing Material	High Temperature Nylon

Boardlock Material

Phosphor Bronze

Dimensions	PCB Thickness (Recommended)	1.57 mm [.062 in]
	Length (mm)	10
	Insulation Diameter (Max) (mm)	1.52
Usage Conditions	Sealed Condition	Not Sealed
Operation/Application	Connector System	Wire-to-Board
	Applies To	Printed Circuit Board
	Operating Temperature	-40 – 105 °C [-40 – 221 °F]
Industry Standards	VDE Tested	Yes
	CSA Rating	Certified
	Agency/Standard Number	E28476
	UL Rating	Recognized
	CSA File Number	LR7189
	Agency/Standard	CSA, UL
Packaging Features	Packaging Method	Tape
	Packaging Quantity	215
Other	For Use With	Plug Housing
Product Compliance	Statement of Compliance PDF	
		VIEW ALL PRODUCT COMPLIANCE

Products - 1 Results[View All](#)Compare 0/10 Relation Type 

RELATIONSHIP
Mating Products
 Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS





Connectors - Rectangular Power Connectors
MATE-N-LOK | Micro MATE-N-LOK

Always EU RoHS/ELV Compliant

MICRO MNL RECEPT
HSG SINGLE R
- 1445022-2
TE INTERNAL NUMBER: 1445022-2

✓ Active