

RS P/N		A	B	C	D	E	F	G	TYPE
468-0638-0010	CF-BJ15/RT-CLR	29.0	12.7	11.1	6.0	1.5	2.5	0.8	CLEAR
468-0644-0010	CF-BJ15/RT-P011	29.0	12.7	11.1	6.0	1.5	2.5	0.8	0-11/30°
468-0650-0010	CF-BJ15/RT-P112	29.0	12.7	11.1	6.0	1.5	2.5	0.8	1-12/30°
468-0666-0010	CF-BJ15/RT-SPR	29.0	12.7	11.1	6.0	1.5	2.5	0.8	300° SPRIL
	CPBT-BJ15/R1-ARW	29.0	12.7	11.1	6.0	1.5	2.5	0.8	RED/WHITE ARROW
	CPBT-BJ15/R5-ARW	29.0	12.7	11.1	6.0	1.5	2.5	0.8	GREY/BLACK ARROW
	CPBT-BJ15/R6-ARW	29.0	12.7	11.1	6.0	1.5	2.5	0.8	BLACK/WHITE ARROW
468-0672-0010	CPBT-BJ15/R6-ARW	29.0	12.7	11.1	6.0	1.5	2.5	0.8	
468-0694-0010	CF-BJ21/RT-CLR	36.8	18.6	17.0	6.4	1.5	2.5	0.8	CLEAR
468-0701-0010	CF-BJ21/RT-P011	36.8	18.6	17.0	6.4	1.5	2.5	0.8	0-11/30°
468-0717-0010	CF-BJ21/RT-P112	36.8	18.6	17.0	6.4	1.5	2.5	0.8	1-12/30°
468-0723-0010	CF-BJ21/RT-SPR	36.8	18.6	17.0	6.4	1.5	2.5	0.8	300° SPRIL
	CPBT-BJ21/R1-ARW	36.8	18.6	17.0	6.4	1.5	2.5	0.8	RED/WHITE ARROW
	CPBT-BJ21/R5-ARW	36.8	18.6	17.0	6.4	1.5	2.5	0.8	GREY/BLACK ARROW
468-0739-0010	CPBT-BJ21/R6-ARW	36.8	18.6	17.0	6.4	1.5	2.5	0.8	BLACK/WHITE ARROW
468-0751-0010	CF-BJ29/RT-CLR	46.8	26.0	24.0	6.4	1.5	3.0	1.0	CLEAR
468-0767-0010	CF-BJ29/RT-P011	46.8	26.0	24.0	6.4	1.5	3.0	1.0	0-11/30°
468-0773-0010	CF-BJ29/RT-P112	46.8	26.0	24.0	6.4	1.5	3.0	1.0	1-12/30°
468-0789-0010	CF-BJ29/RT-SPR	46.8	26.0	24.0	6.4	1.5	3.0	1.0	300° SPRIL



CLEAR



0-11/30°



1-12/30°



300°SPRIL





CPBT-BJ15/R1-ARW



CPBT-BJ15/R5-ARW



CPST-BJ21-R6/ARW



Material: PLASTIC
Tolerance: +/-0.20
Unit : mm

CF-BJ RING SERIES

Date: 26-Jun-09