

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0444720450

Status:

Active

Overview:

Mini-Fit® Plus HCS

Description:

Mini-Fit® HCS Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-in Plastic Peg  
PCB Lock, 4 Circuits, PA Polyamide Nylon 6/6 94V-2, without Drain Holes

Documents:

3D Model

Drawing (PDF)

Product Specification PS-44476-001 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

CSA

LR19980

UL

E29179

General

Product Family

PCB Headers

Series

44472

Application

Power, Wire-to-Board

Comments

Square Pin|Solder Type

Overview

Mini-Fit® Plus HCS

Product Name

Mini-Fit® HCS

UPC

800754912471

Physical

Breakaway

No

Circuits (Loaded)

4

Circuits (maximum)

4

Color - Resin

Natural

Durability (mating cycles max)

30

Flammability

94V-2

Glow-Wire Compliant

No

Material - Metal

High Performance Alloy (HPA)

Material - Plating Mating

Tin

Material - Plating Termination

Tin

Material - Resin

Nylon

Net Weight

1.029/g

Number of Rows

2

Orientation

Vertical

PCB Locator

Yes

PCB Retention

Yes

PCB Thickness - Recommended

1.80mm

Packaging Type

Tray

Pitch - Mating Interface

4.20mm

Plating min - Mating

2.540µm

Plating min - Termination

2.540µm

Polarized to PCB

Yes

Shrouded

Partial

Stackable

No

Surface Mount Compatible (SMC)

No

Temperature Range - Operating

-40°C to +105°C

Termination Interface: Style

Through Hole

Electrical

Current - Maximum per Contact

11.0A

Voltage - Maximum

600V

Solder Process Data

Duration at Max. Process Temperature (seconds)

005



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

China RoHS

REACH SVHC

Contains SVHC(2014  
December 17): No

Halogen-Free

Status

Low-Halogen

Need more information on product  
environmental compliance?

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
Please visit the [Contact Us](#) section for any  
non-product compliance questions.

China ROHS

ELV

Green Image

Not Relevant

Search Parts in this Series

44472 Series

Mates With

5557 Dual Row

|                                         |                    |                             |
|-----------------------------------------|--------------------|-----------------------------|
| Lead-free                               | Process Capability | WAVE                        |
| Max. Cycles at Max. Process Temperature |                    | 001                         |
| Process Temperature max. C              |                    | 240                         |
| <b>Material Info</b>                    |                    |                             |
| <b>Reference - Drawing Numbers</b>      |                    |                             |
| Product Specification                   |                    | PS-44476-001, RPS-44476-001 |

This document was generated on 06/26/2015

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**