



## **DESCRIPTION:**

Blue Halogen-Free Narrow Slot Betaduct is manufactured in the UK from Noryl NH5110E. It provides a lightweight self-extinguishing cable trunking with excellent rigidity and performance characteristics. Ideal for use with slimmer terminal blocks where more access is required, it improves appearance of panels with cables out in best position.

For use when bundles, cables and wires need supporting in control panels, distribution boards and switchgear. Suitable for I.S circuits. Ideal for use in applications where danger to members of the public is a concern, such petrochemical plants and offshore oil platforms.

Available in 10 sizes. Recommended fixing method; Betaduct rivets or washers. Supplied with lid.

## **SPECIFICATION:**

MATERIAL: Halogen-Free Noryl NH5110E


SLOT PITCH: 10mm • SLOT WIDTH: 4mm • WEBS: 6mm

**COLOUR:** Blue RAL 5015

SERVICE TEMPERATURE RANGE:  $-25^{\circ}$ C to  $+90^{\circ}$ C OXYGEN INDEX: 35.7% BS EN ISO 4589-2: 1999

SMOKE TEST: BS 6853: 1999 Annex D.8.3 (Small Scale Test)

**FLAMMABILITY:** UL94 V-1 Rated Material **STANDARDS:** cULus and UL Approved



## **PART NUMBERS:**

PART NO. BLUE	NOMINAL SIZE INNER (WxH) mm	NOMINAL SIZE OUTER (WxH) mm	PACK QTY (m)
20476033	37.5 x 50	41 x 54	8
20476034	37.5 x 75	41 x 79	8
20476053	50 x 50	54 x 54	8
20476054	50 x 75	55 x 79	8
20476073	75 x 50	78 x 54	8
20476074	75 x 75	80 x 80	8
20476103	100 x 50	107 x 54	4
20476104	100 x 75	107 x 80	4
20476105	100 x 100	107 x 104	4
20476124	125 x 75	131 x 78	4



















Cablecraft House, Circle Business Centre, Blackburn Road, Houghton-Regis, Bedfordshire, LU5 5DD. **Phone:** 01582 606033 • **Fax:** 01582 606063 • **Email:** sales@cablecraft.co.uk • **Web:** www.cablecraft.co.uk