



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

010 HOUSING FFC RCPT 100CL DR

FFC | FFC

487223-1

TE Internal Number: 487223-1

Always EU RoHS/ELV Compliant

Connector Type **Housing**

Connector Style **Receptacle**

Centerline **2.54 mm [.1 in]**

Number of Positions **10**

Number of Rows **2**

Product Drawings

[HOUSING, RECEPTACLE, FFC .100X.100 CENTERLINE, DOUBLE ROW](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Product Specifications

Product Specification

[Connector, Flexible Flat Conductor Cable, .100 Inch Centerline](#)

PDF
English

Application Specification

[Flexible Flat Cable \(FFC\) Housings With Contact Cavities On 2.54-Mm \(.100-In.\) Centerline Spacing](#)

PDF
English

Instruction Sheets

Instruction Sheet (U.S.)

[Extraction Tools](#)

PDF
English

[Extraction Tools](#)

TIF
English


Drawing for all design activity.

Product Type Features	Connector Type	Housing
	Connector Style	Receptacle
	Row-to-Row Spacing	2.54 mm [.1 in]
	Applies To	Cable
	Type of Connector	Standard
	Wire/Cable Type	FFC
	Product Type	Connector
	Connector System	Wire-to-Board
Configuration Features	Number of Positions	10
	Number of Rows	2
Electrical Characteristics	Voltage	300 VAC
	Dielectric Withstanding Voltage (VAC)	720
	Insulation Resistance (MΩ)	5000
Body Features	Color	Black
Contact Features	Contact Type	Socket
Mechanical Attachment	Mating Connector Lock	Without
	Mating Alignment	With
	Panel Mount Retention	Without
	Mating Alignment Type	Polarization
	Mating Retention	Without
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	Black
	Housing Material	Thermoplastic
Usage Conditions	Flame Retardant	Yes
	Operating Temperature Range (°C)	-65 – 105
Industry Standards	UL Flammability Rating	UL 94V-0

Packaging Features	Packaging Method	Package
	Packaging Quantity	1
Other	Comment	Use Extraction Tool No. 91093-1 for round wire contacts.
Product Compliance	Statement of Compliance PDF	
	VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

FFC CONNECTORS



17 ZIF LINE 50 ASSY
487576-9

Save to List

Find Similar Products

FPC CONNECTORS

12POS ZIF 100 CENTERLINE
84501-1

Save to List

Find Similar Products


FFC CONTACTS

FFC, RCPT CONTACT, STD PRESSURE
2-487406-4

Save to List

Find Similar Products

POWER CONTACTS



UMNL PIN 20-14 AU/PHBZ L/P
350547-6

Save to List

Find Similar Products

Products - 58 Results

View All

Compare 0/10


Relation Type

RELATIONSHIP

Mating Products

Used to identify Mating Parts

See All Mating Products



PRODUCT - MATING PRODUCTS

Connectors - Ribbon Cable Connectors
AMP-LATCH | Universal Headers
010 UNIV HDR SP 4S
15DP STD - 102155-1
TE INTERNAL NUMBER: 102155-1

Active

5 of 6 EU RoHS/ELV Compliant

Centerline 2.54 mm

PCB Mount Retention Without

PCB Mount Retention Type Screw Mount

PCB Mounting Orientation Vertical

Termination Method to PC Board Through Hole - Solder

✓

RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - FFC Contacts
FFC | FFC

**FFC RCPT CONTACT
.050CL - 1-487547-2**

TE INTERNAL NUMBER: 1-487547-2

✓ Active

[Always EU RoHS/ELV Compliant](#)

Centerline **1.27 mm**

Wire/Cable Type **FFC**

Contact Type **Socket**

Contact Mating Area Plating

Material **Gold Flash/Palladium**

Nickel or Gold/Nickel

Packaging Method **Reel**




RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - FFC Contacts
FFC | FFC

**RND WIRE RCPT L.P.
- 86571-4**

TE INTERNAL NUMBER: 86571-4

✓ Active

[Always EU RoHS/ELV Compliant](#)

Centerline **2.54 mm**

Wire/Cable Type **Round Wire,
Discrete**

Contact Type **Socket**

Contact Mating Area Plating

Material **Gold Flash/Palladium**

Nickel or Gold/Nickel

Packaging Method **Box**

