


THIS DRAWING IS A CONTROLLED DOCUMENT.
DRAW NO



Left Side
Connector(s): LC-Duplex Secure
Mode: MM
Housing Color: Green
Geom. Spec: N/A

Fiber Path
A - 
B - 


Right Side
Connector(s): ST
Mode: MM
Housing Color: N/A
Geom. Spec: N/A

- Notes:
- 1 Product and Processing must meet requirements of Tyco Electronics Standard 230-702
 - 2 Includes dust caps (not shown on print).
 - 3 IL tested at 1300nm.
 - 4 Label 2 will not be present on any cable assembly less than 5 meters long.

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS, INC. AND ITS AFFILIATES. IT MAY NOT BE DISCLOSED TO ANY OTHER PERSON OR ENTITY WITHOUT THE WRITTEN AUTHORIZATION OF TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA.

LOC
CE
DIST
16

Rev Per	EC#	RELEASE	DATE	DIN	APVD
A			4/17/2008	-	JD
P	LTR	REVISION RECORD	DATE	DIN	APVD



Restricted To:

DIN	Cable Assy Configurator	MATERIAL	HEAT TREAT
CHK	Jeremy Duncan		
APVD	Jeremy Duncan		
NAME	FO C/A - 2 fiber, 50/125, OFNR (Riser) jacket, LC-Duplex Secure to ST		
SCALE	NTS	SIZE	A2
DRAWING NO	C- 1906005	SHEET	1 of 4
REV	A		

AMP Tyco Electronics, Inc.
Harrisburg, PA 17105-3608

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION. IT IS NOT TO BE DISCLOSED TO ANY OTHERS WITHOUT THE WRITTEN AUTHORIZATION OF TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA.

LOC
CE
DIST
16


CAC Customer Layout Rev: D

THIS DRAWING IS A CONTROLLED DOCUMENT.

REV: 40

Part #	L (meters)	L (feet)	LC-Duplex Secure, Green		ST	
			IL (dB)	RL (dB)	IL (dB)	RL (dB)
0-1906005-1	0.950 - 1.050	3.11 - 3.44	0.5	-	0.5	-
0-1906005-2	1.950 - 2.050	6.39 - 6.72	0.5	-	0.5	-
0-1906005-3	2.950 - 3.050	9.67 - 10.00	0.5	-	0.5	-
0-1906005-4	3.920 - 4.080	12.86 - 13.38	0.51	-	0.51	-
0-1906005-5	4.920 - 5.080	16.14 - 16.66	0.51	-	0.51	-
0-1906005-6	5.920 - 6.080	19.42 - 19.94	0.51	-	0.51	-
0-1906005-7	6.920 - 7.080	22.70 - 23.22	0.51	-	0.51	-
0-1906005-8	7.920 - 8.080	25.98 - 26.50	0.51	-	0.51	-
0-1906005-9	8.850 - 9.150	29.03 - 30.01	0.51	-	0.51	-
1-1906005-0	9.850 - 10.150	32.31 - 33.30	0.52	-	0.52	-
1-1906005-1	10.850 - 11.150	35.59 - 36.58	0.52	-	0.52	-
1-1906005-2	11.850 - 12.150	38.87 - 39.86	0.52	-	0.52	-
1-1906005-3	12.850 - 13.150	42.15 - 43.14	0.52	-	0.52	-
1-1906005-4	13.850 - 14.150	45.43 - 46.42	0.52	-	0.52	-
1-1906005-5	14.850 - 15.150	48.72 - 49.70	0.52	-	0.52	-
1-1906005-6	15.840 - 16.160	51.96 - 53.01	0.52	-	0.52	-
1-1906005-7	16.830 - 17.170	55.21 - 56.33	0.53	-	0.53	-
1-1906005-8	17.820 - 18.180	58.46 - 59.64	0.53	-	0.53	-
1-1906005-9	18.810 - 19.190	61.71 - 62.95	0.53	-	0.53	-
2-1906005-0	19.800 - 20.200	64.96 - 66.27	0.53	-	0.53	-
2-1906005-1	20.790 - 21.210	68.20 - 69.58	0.53	-	0.53	-
2-1906005-2	21.780 - 22.220	71.45 - 72.90	0.53	-	0.53	-
2-1906005-3	22.770 - 23.230	74.70 - 76.21	0.53	-	0.53	-
2-1906005-4	23.760 - 24.240	77.95 - 79.52	0.54	-	0.54	-
2-1906005-5	24.750 - 25.250	81.20 - 82.84	0.54	-	0.54	-
2-1906005-6	25.740 - 26.260	84.44 - 86.15	0.54	-	0.54	-
2-1906005-7	26.730 - 27.270	87.69 - 89.46	0.54	-	0.54	-
2-1906005-8	27.720 - 28.280	90.94 - 92.78	0.54	-	0.54	-
2-1906005-9	28.710 - 29.290	94.19 - 96.09	0.54	-	0.54	-
3-1906005-0	29.700 - 30.300	97.44 - 99.40	0.55	-	0.55	-
3-1906005-1	30.690 - 31.310	100.68 - 102.72	0.55	-	0.55	-
3-1906005-2	31.680 - 32.320	103.93 - 106.03	0.55	-	0.55	-
3-1906005-3	32.670 - 33.330	107.18 - 109.35	0.55	-	0.55	-
3-1906005-4	33.660 - 34.340	110.43 - 112.66	0.55	-	0.55	-
3-1906005-5	34.650 - 35.350	113.68 - 115.97	0.55	-	0.55	-
3-1906005-6	35.640 - 36.360	116.92 - 119.29	0.55	-	0.55	-
3-1906005-7	36.630 - 37.370	120.17 - 122.60	0.56	-	0.56	-
3-1906005-8	37.620 - 38.380	123.42 - 125.91	0.56	-	0.56	-
3-1906005-9	38.610 - 39.390	126.67 - 129.23	0.56	-	0.56	-
4-1906005-0	39.600 - 40.400	129.92 - 132.54	0.56	-	0.56	-
4-1906005-1	40.590 - 41.410	133.16 - 135.85	0.56	-	0.56	-
4-1906005-2	41.580 - 42.420	136.41 - 139.17	0.56	-	0.56	-

Qty	U of M	Description	Item No.
2	piece	Trace Label	13
2	piece	Eyelet/Shrink tube assembly - White	12
AR	meter	2 fiber, 50/125, 2.0mm, Twinzip, Orange, OFNR (Riser)	11
2	piece	PVC Build-up tubing	10
2	piece	2.5mm ferrule cover	9
2	piece	ST Connector, Ceramic, Polymer Nut	8
2	piece	ST Short Boot - 1.6 to 2.0mm, Beige	7
2	piece	Crimp Eyelet	6
0.0139	sheet	Leg Label - "B"	5
0.0139	sheet	Leg Label - "A"	4
2	piece	LC Connector Assy, 1.6mm-2.0mm, MM	3
1	piece	LC Duplex clip, black	2
2	piece	LC, SC, FC Straight Boot, Beige	1



DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:	
mm		0 P.L.C.	± .
		1 P.L.C.	± .
		2 P.L.C.	± .
		3 P.L.C.	± .
		4 P.L.C.	± .

Restricted To:

DIN Cable Assy Configurator		MATERIAL -	HEAT TREAT -	
CHK Jeremy Duncan	AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608			
APVD Jeremy Duncan				
NAME FO C/A - 2 fiber, 50/125, OFNR (Riser) jacket, LC-Duplex Secure to ST				
SCALE NTS	SIZE A2	DRAWING NO C- 1906005	SHEET 2 of 4	REV A

THIS DRAWING IS A CONTROLLED DOCUMENT.

LOC
CE
DIST
16

CAC Customer Layout Rev: D

Part #	L (meters)	L (feet)	LC-Duplex Secure, Green		ST	
			IL (dB)	RL (dB)	IL (dB)	RL (dB)
4-1906005-3	42.570 - 43.430	139.66 - 142.48	0.56	-	0.56	-
4-1906005-4	43.560 - 44.440	142.91 - 145.80	0.57	-	0.57	-
4-1906005-5	44.550 - 45.450	146.16 - 149.11	0.57	-	0.57	-
4-1906005-6	45.540 - 46.460	149.40 - 152.42	0.57	-	0.57	-
4-1906005-7	46.530 - 47.470	152.65 - 155.74	0.57	-	0.57	-
4-1906005-8	47.520 - 48.480	155.90 - 159.05	0.57	-	0.57	-
4-1906005-9	48.510 - 49.490	159.15 - 162.36	0.57	-	0.57	-
5-1906005-0	49.500 - 50.500	162.40 - 165.68	0.58	-	0.58	-
5-1906005-1	50.490 - 51.510	165.64 - 168.99	0.58	-	0.58	-
5-1906005-2	51.480 - 52.520	168.89 - 172.30	0.58	-	0.58	-
5-1906005-3	52.470 - 53.530	172.14 - 175.62	0.58	-	0.58	-
5-1906005-4	53.460 - 54.540	175.39 - 178.93	0.58	-	0.58	-
5-1906005-5	54.450 - 55.550	178.64 - 182.25	0.58	-	0.58	-
5-1906005-6	55.440 - 56.560	181.88 - 185.56	0.58	-	0.58	-
5-1906005-7	56.430 - 57.570	185.13 - 188.87	0.59	-	0.59	-
5-1906005-8	57.420 - 58.580	188.38 - 192.19	0.59	-	0.59	-
5-1906005-9	58.410 - 59.590	191.63 - 195.50	0.59	-	0.59	-
6-1906005-0	59.400 - 60.600	194.88 - 198.81	0.59	-	0.59	-
6-1906005-1	60.390 - 61.610	198.12 - 202.13	0.59	-	0.59	-
6-1906005-2	61.380 - 62.620	201.37 - 205.44	0.59	-	0.59	-
6-1906005-3	62.370 - 63.630	204.62 - 208.75	0.59	-	0.59	-
6-1906005-4	63.360 - 64.640	207.87 - 212.07	0.6	-	0.6	-
6-1906005-5	64.350 - 65.650	211.12 - 215.38	0.6	-	0.6	-
6-1906005-6	65.340 - 66.660	214.37 - 218.70	0.6	-	0.6	-
6-1906005-7	66.330 - 67.670	217.61 - 222.01	0.6	-	0.6	-
6-1906005-8	67.320 - 68.680	220.86 - 225.32	0.6	-	0.6	-
6-1906005-9	68.310 - 69.690	224.11 - 228.64	0.6	-	0.6	-
7-1906005-0	69.300 - 70.700	227.36 - 231.95	0.61	-	0.61	-
7-1906005-1	70.290 - 71.710	230.61 - 235.26	0.61	-	0.61	-
7-1906005-2	71.280 - 72.720	233.85 - 238.58	0.61	-	0.61	-
7-1906005-3	72.270 - 73.730	237.10 - 241.89	0.61	-	0.61	-
7-1906005-4	73.260 - 74.740	240.35 - 245.20	0.61	-	0.61	-
7-1906005-5	74.250 - 75.750	243.60 - 248.52	0.61	-	0.61	-
7-1906005-6	75.240 - 76.760	246.85 - 251.83	0.61	-	0.61	-
7-1906005-7	76.230 - 77.770	250.09 - 255.15	0.62	-	0.62	-
7-1906005-8	77.220 - 78.780	253.34 - 258.46	0.62	-	0.62	-
7-1906005-9	78.210 - 79.790	256.59 - 261.77	0.62	-	0.62	-
8-1906005-0	79.200 - 80.800	259.84 - 265.09	0.62	-	0.62	-

	A	Rev Per EC#	RELEASE	4/17/2008	-	JF				
P	LTR		REVISION RECORD	DATE	DIN	AP				

DIMENSIONS;
meters

TOLERANCES UNLESS OTHERWISE SPECIFIED		
0 PLC	$\pm$	-
1 PLC	$\pm$	-
2 PLC	$\pm$	-
3 PLC	$\pm$	-
4 PLC	$\pm$	-

Restricted To:

DBN Cable Assy Configurator		MATERIAL -		HEAT TREAT -	
CHK Jeremy Duncan		 Tyco Electronics, Inc. Harrisburg, PA 17105-3608			
APVD Jeremy Duncan					
NAME FO C/A - 2 fiber, 50/125, OFNR (Riser) jacket, LC-Duplex Secure to ST					
SCALE NTS		SIZE A2		DRAWING NO C- 1906005	
				SHEET 3 of 4	
				REV A	

D

C

B

A

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION. IT MAY NOT BE DISCLOSED TO ANY OTHERS WITHOUT WRITTEN AUTHORIZATION OF TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA.

THIS DRAWING IS A CONTROLLED DOCUMENT.

LOC
CE
DIST
16

CAC Customer Layout Rev: D

8 7 6 5 4 3 2 1

	A	Rev Per EC#	RELEASE	4/17/2008	-	JD	
P	LTR	REVISION RECORD		DATE	DIN	APVD	

DIMENSIONS: meters

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 P.L.C. ± .
1 P.L.C. ± .
2 P.L.C. ± .
3 P.L.C. ± .
4 P.L.C. ± .

Restricted To:

DIN Cable Assy Configurator		MATERIAL -	HEAT TREAT -	
CHK	Jeremy Duncan	AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608		
APVD	Jeremy Duncan			
NAME FO C/A - 2 fiber, 50/125, OFNR (Riser) jacket, LC-Duplex Secure to ST				
SCALE NTS	SIZE A2	DRAWING NO C- 1906005	SHEET 4 of 4	REV A

Label 1

Per specification 107-1645-1

Trace # - Bar Code

XXXXXXXXXXXXXXXXXX

Trace # - Human Readable

Logo

Made in XXXX

X-XXXXXXXX-X

Part Number

Country of Origin

This label is used on all lengths on this drawing.

Label 2

Per specification 107-1645-1

Trace # - Bar Code

XXXXXXXXXXXXXXXXXX

Trace # - Human Readable

Logo

Made in XXXX

X-XXXXXXXX-X

Part Number

Country of Origin

This label is used on all lengths on this drawing.

D
C
B
A