

PRINT DIST

単位:mm DIMENSIONS IN MM. DO NOT SCALE PRINT

NUMBER
C-177900

METRIC

三角度 (3-d ANGLE PROJECTION)

ロックタイプII
LOCK TYPE II

表1 (TABLE 1)

トレードマーク (TRADE MARK)	生産場所 (MANUFACTURING PLACE)
—AMP OR AMP	日本 (JAPAN)
—+AMP OR AMP	中国 (CHINA(PRC))
・AMP OR AMP	韓国 (KOREA)

NOTES,
1. PRODUCT SPEC.:108-5410
2. APPLICABLE CONTACT P/N
REC CONTACT:177915-□(*20-#16AWG)
177914-□(*26-#22AWG)
3. MATING CONN,P/N
CAP HSG:177908-□(PANEL MOUNT)
TAB CONTACT:177917-□(*20-#16AWG)
177916-□(*26-#22AWG)
4.APPLICABLE PLATE P/N:177918-□
5. INSTRUCTION SHEET : 411-5638
△ SEE TABLE 1

本図ロックタイプIを示す
AS SHOWN LOCK TYPE I

ロックタイプII LOCK TYPE II	自然色(NATURAL)	4	3-177900-1
ロックタイプ LOCK TYPE	ハウジング色調 (HOUSING COLOR)	極数 (Pos.)	型番 (P/N)

ロックタイプ LOCK TYPE	ハウジング色調 (HOUSING COLOR)	極数 (Pos.)	型番 (P/N)
ロックタイプI LOCK TYPE I	自然色(NATURAL)	4	5-177900-1
	青 (BLUE)	↑	↑ -6
	黄 (YELLOW)	↑	↑ -4
	赤 (RED)	↓	↓ -2
	自然色(NATURAL)	4	177900-1

材料(MATERIAL)
6/6 ナイロン (UL94V-0)
S/B NYLON (UL94V-0)
9. SEP '93
DR. M. SUZUKI
CHK. M. SHINDO

仕上 (FINISH)
9. SEP '93
DE. M. SUZUKI
APP. Y. KASHIWA

名称 (NAME)
AMP POWER DOUBLE LOCK CONN.
4極 3.96mmピッチ プラグハウジング (2列タイプ)
AMP POWER DOUBLE LOCK CONN. 3.96mm PITCH PLUG HOUSING 4 Pos (DBL ROW)

一般公差
10mm以下: ±0.2
10mm超え 30mm以下: ±0.25
30mm超え 100mm以下: ±0.3
角 度: ±3°

SIZE LOC 番号(No.)
A3 J C-177900

尺度 (SCALE) REV. F3 SHEET 1 OF 1

F3 REVISED PER ECR-14-001994 A.Z D. Z 11FEB 2014
F2 REVISED PER ECR-12-019929 A.Z F.M 16NOV 2012
F1 REVISED PER ECO-11-005140 R.K H.M.R 01APR 11
LTR 変更 (REVISION RECORD) DR CHK DATE

7. ALL PARTS MEET RTI ELECTRICAL RATING OF 105C ACCORDING TO UL 1977
8. PART 5-177900-1 COMPLY WITH GLOW WIRE REQUIREMENT FOR PARTS OF NON-METALLIC MATERIAL SUPPORTING A CURRENT-CARRYING CONNECTION DETAILED IN IEC 60335-1, SECTION 30 (GWT)

CUSTOMER DRAWING

TE Connectivity

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[5-177900-1](#)