



Geom. Spec: N/A


Geom. Spec: N/A

- 1 IL tested at 1300nm.
- 2 Product and Processing must meet requirements of Tyco Electronics Standard 230-702
- 3 A copy of test data will be placed inside or with the unit package.
- 4 Label 2 will not be present on any cable assembly less than 5 meters long.
- 5 The cable meets or exceeds the requirements of GR-409-CORE for both RISER and PLENUM applications.
- 6 The cable meets or exceeds the UL requirements for both RISER and PLENUM applications.

DW1 Cable Assy Configurator		MATERIAL -		HEAT TREAT -	
CHK Dave Fennell		 AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608			
APVD Dave Fennell					
NAME FO C/A - 12 fiber, 62.5/125, OFNR-OFNP, MPO SECURE (No Pins) to MPO SECURE (No Pins)					
SCALE NTS	SIZE A2	DRAWING NO C- 1918751		SHEET 1 of 5	REV A


THIS DRAWING IS A CONTROLLED DOCUMENT.
PAGE NO

USED ON



Pairs Flipped

A-A Fiber Color	Connector Position #	B-B Fiber Color
Blue	1	Orange
Orange	2	Blue
Green	3	Brown
Brown	4	Green
Slate	5	White
White	6	Slate
Red	7	Black
Black	8	Red
Yellow	9	Violet
Violet	10	Yellow
Rose	11	Aqua
Aqua	12	Rose



Lightray Connector Fiber Path


1 - - - - - 1

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION. IT IS NOT TO BE DISCLOSED TO ANY OTHERS WITHOUT THE WRITTEN AUTHORIZATION OF TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA.

LOC
CE
DIST
16

CAC Customer Layout Rev: D

	A	Rev Per EC#	None	12/4/2008	-	DF			
P	LTR	REVISION	RECORD	DATE	DATE	DIN	APVD		



DIMENSIONS:
meters

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 P.L.C. ± .
1 P.L.C. ± .
2 P.L.C. ± .
3 P.L.C. ± .
4 P.L.C. ± .

Restricted To:

DIN	Cable Assy Configurator	MATERIAL	-	HEAT TREAT	-
OK	Dave Fennell				
APVD	Dave Fennell				
NAME	FO C/A - 12 fiber, 62.5/125, OFNR-OFNP, MPO SECURE (No Pins) to MPO SECURE (No Pins)				
SCALE	NTS	SIZE	A2	DRAWING NO	C- 1918751
				SHEET	2 of 5
				REV	A

AMP Tyco Electronics, Inc.
Harrisburg, PA 17105-3608

DING NO.

LOC
CE
DIST
16

CAC Customer Layout Rev: D

Part #	L (meters)	L (feet)	MPO SECURE (No Pins), Orange		MPO SECURE (No Pins), Orange	
			IL (dB)	RL (dB)	IL (dB)	RL (dB)
0-1918751-1	3.048 - 3.353	10.00 - 11.00	0.75	-	0.75	-
0-1918751-2	6.096 - 6.706	20.00 - 22.00	0.76	-	0.76	-
0-1918751-3	9.144 - 9.754	30.00 - 32.00	0.76	-	0.76	-
0-1918751-4	12.192 - 12.802	40.00 - 42.00	0.77	-	0.77	-
0-1918751-5	15.240 - 15.850	50.00 - 52.00	0.77	-	0.77	-
0-1918751-6	18.288 - 18.898	60.00 - 62.00	0.78	-	0.78	-
0-1918751-7	21.336 - 21.946	70.00 - 72.00	0.78	-	0.78	-
0-1918751-8	24.384 - 24.994	80.00 - 82.00	0.79	-	0.79	-
0-1918751-9	27.432 - 28.042	90.00 - 92.00	0.79	-	0.79	-
1-1918751-0	30.480 - 31.394	100.00 - 103.00	0.8	-	0.8	-
1-1918751-1	33.528 - 34.442	110.00 - 113.00	0.8	-	0.8	-
1-1918751-2	36.576 - 37.490	120.00 - 123.00	0.8	-	0.8	-
1-1918751-3	39.624 - 40.538	130.00 - 133.00	0.81	-	0.81	-
1-1918751-4	42.672 - 43.586	140.00 - 143.00	0.81	-	0.81	-
1-1918751-5	45.720 - 46.634	150.00 - 153.00	0.82	-	0.82	-
1-1918751-6	48.768 - 49.682	160.00 - 163.00	0.82	-	0.82	-
1-1918751-7	51.816 - 52.730	170.00 - 173.00	0.83	-	0.83	-
1-1918751-8	54.864 - 55.778	180.00 - 183.00	0.83	-	0.83	-
1-1918751-9	57.912 - 58.826	190.00 - 193.00	0.84	-	0.84	-
2-1918751-0	60.960 - 62.179	200.00 - 204.00	0.84	-	0.84	-
2-1918751-1	64.008 - 65.227	210.00 - 214.00	0.85	-	0.85	-
2-1918751-2	67.056 - 68.275	220.00 - 224.00	0.85	-	0.85	-
2-1918751-3	70.104 - 71.323	230.00 - 234.00	0.86	-	0.86	-
2-1918751-4	73.152 - 74.371	240.00 - 244.00	0.86	-	0.86	-
2-1918751-5	76.200 - 77.419	250.00 - 254.00	0.86	-	0.86	-
2-1918751-6	79.248 - 80.467	260.00 - 264.00	0.87	-	0.87	-
2-1918751-7	82.296 - 83.515	270.00 - 274.00	0.87	-	0.87	-
2-1918751-8	85.344 - 86.563	280.00 - 284.00	0.88	-	0.88	-
2-1918751-9	88.392 - 89.611	290.00 - 294.00	0.88	-	0.88	-
3-1918751-0	91.440 - 93.269	300.00 - 306.00	0.89	-	0.89	-
3-1918751-1	94.488 - 96.378	310.00 - 316.20	0.89	-	0.89	-
3-1918751-2	97.536 - 99.487	320.00 - 326.40	0.9	-	0.9	-
3-1918751-3	100.584 - 102.596	330.00 - 336.60	0.9	-	0.9	-
3-1918751-4	103.632 - 105.705	340.00 - 346.80	0.91	-	0.91	-
3-1918751-5	106.680 - 108.814	350.00 - 357.00	0.91	-	0.91	-
3-1918751-6	109.728 - 111.923	360.00 - 367.20	0.91	-	0.91	-
3-1918751-7	112.776 - 115.032	370.00 - 377.40	0.92	-	0.92	-
3-1918751-8	115.824 - 118.140	380.00 - 387.60	0.92	-	0.92	-
3-1918751-9	118.872 - 121.249	390.00 - 397.80	0.93	-	0.93	-
4-1918751-0	121.920 - 124.358	400.00 - 408.00	0.93	-	0.93	-
4-1918751-1	124.968 - 127.467	410.00 - 418.20	0.94	-	0.94	-
4-1918751-2	128.016 - 130.576	420.00 - 428.40	0.94	-	0.94	-
4-1918751-3	131.064 - 133.685	430.00 - 438.60	0.95	-	0.95	-
4-1918751-4	134.112 - 136.794	440.00 - 448.80	0.95	-	0.95	-

Qty	U of M	Description	Item No.
2	piece	Dust Cover	20
1	piece	Caution Label	19
2	piece	Mini boot, 12 fiber	18
3	piece	Heat Shrink Tubing	17
2	piece	Boot, MPO - Orange	16
2	piece	Crimp Ring	15
2	piece	Pin Holder w/out Pins	14
1	piece	Braided Sleeve	13
2	piece	Spirap 5.5"	12
2	piece	Spring Retainer	11
2	piece	Construction tape	10
1	piece	Pulling Sock	9
3	piece	Trace Label	8
0.378	meters	Oval Tube, Orange	7
2	piece	Protective Tube	6
AR	meter	12 Fiber, 62.5/125, 7.8mm, CLT, Orange, OFNR/OFNP	5
0.2	RL	Electrical Tape	4
2	piece	Connector Housing	3
2	piece	Spring	2
2	piece	Ferrule, MT, MM, 12 Fiber	1

	A	Rev Per EC# None	12/4/2008	-	D		
P	LTR	REVISION RECORD	DATE	DIN	AP		

DIMENSIONS;
meters

TOLERANCES UNLESS OTHERWISE SPECIFIED		
0 PLC	±	—
1 PLC	±	—
2 PLC	±	—
3 PLC	±	—
4 PLC	±	—

Q1 Cable Assy Configurator		MATERIAL -		HEAT TREAT -	
OK Dave Fennell		 AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608			
APVD Dave Fennell					
NAME FO C/A - 12 fiber, 62.5/125, OFNR-OFNP, MPO SECURE (No Pins) to MPO SECURE (No Pins)					
SCALE NTS	SIZE A2	DRAWING NO C-1918751		SHEET 3 of 5	REV A

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION. IT IS NOT TO BE DISCLOSED TO ANY OTHERS WITHOUT THE WRITTEN AUTHORIZATION OF TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA.

THIS DRAWING IS A CONTROLLED DOCUMENT.
REV NO

LOC
CE
DIST
16

CAC Customer Layout Rev: D

Part #	L (meters)	L (feet)	MPO SECURE (No Pins), Orange		MPO SECURE (No Pins), Orange	
			IL (dB)	RL (dB)	IL (dB)	RL (dB)
4-1918751-5	137.160 - 139.903	450.00 - 459.00	0.96	-	0.96	-
4-1918751-6	140.208 - 143.012	460.00 - 469.20	0.96	-	0.96	-
4-1918751-7	143.256 - 146.121	470.00 - 479.40	0.96	-	0.96	-
4-1918751-8	146.304 - 149.230	480.00 - 489.60	0.97	-	0.97	-
4-1918751-9	149.352 - 152.339	490.00 - 499.80	0.97	-	0.97	-
5-1918751-0	152.400 - 155.448	500.00 - 510.00	0.98	-	0.98	-
5-1918751-1	160.020 - 163.220	525.00 - 535.50	0.99	-	0.99	-
5-1918751-2	167.640 - 170.993	550.00 - 561.00	1	-	1	-
5-1918751-3	175.260 - 178.765	575.00 - 586.50	1.01	-	1.01	-
5-1918751-4	182.880 - 186.538	600.00 - 612.00	1.02	-	1.02	-
5-1918751-5	190.500 - 194.310	625.00 - 637.50	1.04	-	1.04	-
5-1918751-6	198.120 - 202.082	650.00 - 663.00	1.05	-	1.05	-
5-1918751-7	205.740 - 209.855	675.00 - 688.50	1.06	-	1.06	-
5-1918751-8	213.360 - 217.627	700.00 - 714.00	1.07	-	1.07	-
5-1918751-9	220.980 - 225.400	725.00 - 739.50	1.08	-	1.08	-
6-1918751-0	228.600 - 233.172	750.00 - 765.00	1.09	-	1.09	-
6-1918751-1	236.220 - 240.944	775.00 - 790.50	1.1	-	1.1	-
6-1918751-2	243.840 - 248.717	800.00 - 816.00	1.12	-	1.12	-
6-1918751-3	251.460 - 256.489	825.00 - 841.50	1.13	-	1.13	-
6-1918751-4	259.080 - 264.262	850.00 - 867.00	1.14	-	1.14	-
6-1918751-5	266.700 - 272.034	875.00 - 892.50	1.15	-	1.15	-
6-1918751-6	274.320 - 279.806	900.00 - 918.00	1.16	-	1.16	-
6-1918751-7	281.940 - 287.579	925.00 - 943.50	1.17	-	1.17	-
6-1918751-8	289.560 - 295.351	950.00 - 969.00	1.18	-	1.18	-
6-1918751-9	297.180 - 303.124	975.00 - 994.50	1.2	-	1.2	-
7-1918751-0	304.800 - 310.896	1000.00 - 1020.00	1.21	-	1.21	-

	A	Rev Per	EC#	None	12/4/2008	-	DF		
P	LTR	REVISION RECORD			DATE	DIN	APVD		

DIMENSIONS:
meters



Restricted To:

TOLERANCES UNLESS OTHERWISE SPECIFIED:	
0 P.L.C.	± .
1 P.L.C.	± .
2 P.L.C.	± .
3 P.L.C.	± .
4 P.L.C.	± .

DIN	Cable Assy Configurator	MATERIAL	HEAT TREAT
CHK	Dave Fennell		
APVD	Dave Fennell	AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608	
NAME	FO C/A - 12 fiber, 62.5/125, OFNR-OFNP, MPO SECURE (No Pins) to MPO SECURE (No Pins)		
SCALE	NTS	SIZE	A2
DRAWING NO	C- 1918751		SHEET
REV	A		4 of 5

8 7 6 5 4 3 2 1

D
C
B
A

THIS DRAWING IS A CONTROLLED DOCUMENT.

Label 1

Per specification 107-1645-1



Trace # - Bar Code
Trace # - Human Readable
Part Number
Country of Origin

This label is used on all lengths on this drawing.


Label 2

Per specification 107-1645-1




Trace # - Bar Code
Trace # - Human Readable
Part Number
Country of Origin

This label is used on all lengths on this drawing.



**Protective Cover
Bottom End**




**Pulling Sock
Top End**

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION. IT IS NOT TO BE DISCLOSED TO ANY OTHERS WITHOUT THE WRITTEN AUTHORIZATION OF TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA.

LOC
CE
DIST
16

CAC Customer Layout Rev: D

Rev	Per	EC#	None	DATE	DIN	APVD
A				12/4/2008	-	DF
P	LTR		REVISION RECORD			



DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
meters	
0 P.L.C.	± .
1 P.L.C.	± .
2 P.L.C.	± .
3 P.L.C.	± .
4 P.L.C.	± .

Restricted To:

DIN	Cable Assy Configurator	MATERIAL	HEAT TREAT
CHK	Dave Fennell		
APVD	Dave Fennell		
NAME	FO C/A - 12 fiber, 62.5/125, OFNR-OFNP, MPO SECURE (No Pins) to MPO SECURE (No Pins)		
SCALE	NTS	SIZE	A2
DRAWING NO	C- 1918751	SHEET	5 of 5
REV	A		

8 7 6 5 4 3 2 1