



## Product Navigation

## Circuit Board Indicators

## Panel Mount Indicators

## Solid State Lighting

## Traffic Signals

## Vehicle Lighting

## Rail

## Obstruction Lighting

## Hazardous Area Lighting

## Heliport Lighting

## how to purchase

[sales contacts](#)
[stock check](#)
[search](#)
[Product Line Search](#)

Please select a Product Line to search.

Circuit Board Indicators

[find](#)
[Part # / Text Search](#)

Part No.:

Text Search:

[search](#)
[quick links](#)

## Dialight Corporate Video

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)

Application Notes  
FAQs

Dialight Ltd (UK)  
Dialight Garufo  
Dialight BLP  
LumiDrives

## Circuit Board Indicators - Through Hole Indicators

P/N# 5522322F

5 mm Lens Single Color

Description  
Package Options  
Product Type  
Sub Product Type  
Configuration  
Lamp Type  
Viewing  
Viewing Angle  
Test Current (mA)  
Forward Current (mA)  
LED Centerline  
Polarity

[onlinecomponents.com](#)

the online distributor of electronic components

5 mm Bi-Level CBI  
50 Pieces Per Bag  
Through Hole Indicators  
with Bi-Level Housing  
5 mm Lens  
Single Color  
24  
20mA  
30mA  
3.2  
Cathode Right

## Absolute Maximum Ratings (Ta = 25 °)

Derating  
Reverse Voltage  
Solder Temp  
Operating Temp  
Storage Temp

from 25Â° @ 1.8 mW/Â°C  
5 V  
260Â° for 5 sec  
-55 to +100° C  
-55 to +100° C


RoHS /pB Free  
view PDF

## Operating Characteristics

LED Position	1,2
Color	Green
Lamp Type	Single Color
LED Type	Super Bright
Intensity Min (mcd)	80
Intensity Typ (mcd)	120.0
Intensity Max (mcd)	
Fwd Voltage Min	
Fwd Voltage Typ	
Fwd Voltage Max	
Dom Wavelength Min (nm)	
Dom Wavelength Typ (nm)	
Dom Wavelength Max (nm)	
Power Dissipation Max (mW)	135
Backlighting	
Pitch Between Vertical	6.35
Pitch Between Horizontal	
Lum Intensity Min	
Lum Intensity Typ	
Lum Intensity Max	

## Distributor Stock Check

Check stock with our distributors now.

5522322F

[check stock](#)