






- Product Navigation
- Circuit Board Indicators
- Panel Mount Indicators
- Solid State Lighting
- Traffic Signals
- Vehicle Lighting
- Rail
- Obstruction Lighting
- Hazardous Area Lighting
- Heliport Lighting

- how to purchase
-  sales contacts
-  stock check

 search


Product Line Search

Please select a Product Line to search.

Part # / Text Search

Part No.:


Text Search:

 quick links

- Dialight Corporate Video
- Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)
- Application Notes
- FAQs
- Dialight Ltd (UK)
- Dialight Garufo
- Dialight BLP
- LumiDrives

Circuit Board Indicators - Through Hole Indicators	
P/N# 5530711110F	3 mm Lens
Description	
Package Options	
Product Type	
Sub Product Type	
Configuration	
Viewing	
Viewing Angle	
Test Current (mA)	

Absolute Maximum Ratings (Ta = 25 °)	
Solder Temp	260Å° for 5 sec
Operating Temp	-55 to +100° C
Storage Temp	-55 to +100° C



Operating Characteristics

LED Position	Found in position(s): 1	Found in position(s): 2
Color	Red	Green
Lamp Type	Bi-Color	Bi-Color
LED Type		
Intensity Min (mcd)	2.5	3.7
Intensity Typ (mcd)	4.7	10.0
Intensity Max (mcd)		
Fwd Voltage Min		
Fwd Voltage Typ		
Fwd Voltage Max		
Dom Wavelength Min (nm)		
Dom Wavelength Typ (nm)		
Dom Wavelength Max (nm)		
Power Dissipation Max (mW)	100	100
Backlighting		
Pitch Between Vertical		
Pitch Between Horizontal		
Lum Intensity Min		
Lum Intensity Typ		
Lum Intensity Max		

Distributor Stock Check

Check stock with our distributors now.