



FEATURES:

- Banana jack is insulated from the panel
- Solder hole at the bottom of the jack allows for 18 to 22 AWG wire attachment
- Offered in six popular colors.
- Recommended maximum panel thickness: .31" (8.0 mm)

MATERIALS:

Banana Jack and Nut: Brass, Nickel Plated

Insulator: Nylon

RATINGS:

Operating Temperature: 500 VRMS

Current: 5 Amperes Max.

ORDERING INFORMATION: Model 5395-*

*= Color Code, Standard colors: -0 Black, -2 Red, -4 Yellow, -5 Green, -6 Blue and -9 White

Sold in packages of 10 per color.

All dimensions are in inches. Tolerances (except noted): .xx = $\pm .02$ " (.51 mm), .xxx = $\pm .005$ " (.127 mm).

All dimensions are in inches. Tolerances (except noted): .xxx = $\pm .02$ (.51 mm); .xxx = $\pm .005$. All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Pomona:

[5935-4](#) [5935-9](#) [5935-5](#) [5935-2](#) [5935-6](#)