




MULTILAYER CERAMIC CHIP CAPACITORS

C Series Commercial Grade High Temperature Application

Type:

C1005 [EIA CC0402]
C1608 [EIA CC0603]
C2012 [EIA CC0805]
C3216 [EIA CC1206]
C3225 [EIA CC1210]
C4532 [EIA CC1812]
C5750 [EIA CC2220]

Issue date:
Jun 2015



REMINDERS

Please read before using this product

SAFETY REMINDERS



REMINDERS

1. If you intend to use a product listed in this catalog for a purpose that may cause loss of life or other damage, you must contact our company's sales window.
2. We may modify products or discontinue production of a product listed in this catalog without prior notification.
3. We provide "Delivery Specification" that explain precautions for the specifications and safety of each product listed in this catalog. We strongly recommend that you exchange these delivery specifications with customers that use one of these products.
4. If you plan to export a product listed in this catalog, keep in mind that it may be a restricted item according to the "Foreign Exchange and Foreign Trade Control Law". In such cases, it is necessary to acquire export permission in harmony with this law.
5. Any reproduction or transferring of the contents of this catalog is prohibited without prior permission from our company.
6. We are not responsible for problems that occur related to the intellectual property rights or other rights of our company or a third party when you use a product listed in this catalog. We do not grant license of these rights.
7. This catalog only applies to products purchased through our company or one of our company's official agencies. This catalog does not apply to products that are purchased through other third parties.

Notice: Effective January 2013, TDK will use a new catalog number which adds product thickness and packaging specification detail. This new catalog number should be referenced on all catalog orders going forward, and is not applicable for OEM part number orders. Please be aware the last five digits of the catalog number will differ from the item description (internal control number) on the product label. Contact your local TDK Sales representative for more information.

(Example)


Catalog Issued date	Catalog Number	Item Description (On Delivery Label)
Prior to January 2013	C1608C0G1E103J	C1608C0G1E103JT000N
January 2013 and Later	C1608C0G1E103J080AA	C1608C0G1E103JT000N



C Series

High Temperature Application

Type: C1005 [EIA CC0402], C1608 [EIA CC0603], C2012 [EIA CC0805], C3216 [EIA CC1206], C3225 [EIA CC1210], C4532 [EIA CC1812], C5750 [EIA CC2220]



Features



- With a maximum temperature of 150°C and a capacitance change within ±15%, the series is suited for devices that operate in high-temperature environments.
- Excellent DC bias properties.


Parameters	Specifications
Temperature	-55 to 150°C
Characteristics	ΔC/C: ±15% or 0 ± 30ppm
Operating Temperature	-55 to +150°C
Dissipation Factor	5% maximum
Insulation Resistance	10 GΩ or 500 MΩ • μF minimum
Voltage Proof	2.5 • Rated Voltage or 3 • Rated Voltage for 1 to 5 seconds Charge/Discharge ≤ 50 mA

Applications



- Automotive applications (engine rooms)
- Measurement instruments used at high temperature environments
- LCD display
- Sensor Module
- Smoothing and decoupling applications for other devices that operate at high temperature

Shape & Dimensions



L	Body Length
W	Body Width
T	Body Height
B	Terminal Width
G	Terminal Spacing



Catalog Number Construction

C • 3225 • X8R • 1C • 106 • K • 250 • A • B

Series Name

Dimensions L x W (mm)

Code	Length	Width	Terminal
C1005	1.00 ± 0.05	0.50 ± 0.05	0.10 min.
C1608	1.60 ± 0.10	0.80 ± 0.10	0.20 min.
C2012	2.00 ± 0.20	1.25 ± 0.20	0.20 min.
C3216	3.20 ± 0.20	1.60 ± 0.20	0.20 min.
C3225	3.20 ± 0.40	2.50 ± 0.30	0.20 min.
C4532	4.50 ± 0.40	3.20 ± 0.40	0.20 min.
C5750	5.70 ± 0.40	5.00 ± 0.40	0.20 min.

*Dimensional tolerances are typical values.

Temperature Characteristics

Temperature Characteristics	Temperature Coefficient or Capacitance Change	Temperature Range
NP0	0 ± 30ppm/°C	-55 to +150°C
X8R	± 15%	-55 to +150°C

Rated Voltage (DC)

Code	Voltage (DC)	Code	Voltage (DC)
1C	16V	2A	100V
1E	25V	2E	250V
1H	50V	2W	450V
		2J	630V

Nominal Capacitance (pF)

The capacitance is expressed in three digit codes and in units of pico Farads (pF). The first and second digits identify the first and second significant figures of the capacitance. The third digit identifies the multiplier. R designates a decimal point.

Ex. 0R2 = 0.2pF; 103 = 10,000pF; 105 = 1,000,000pF = 1,000nF

Capacitance Tolerance

Code	Tolerance
C	± 0.25pF
D	± 0.50pF
J	± 5%
K	± 10%
M	± 20%

Nominal Thickness

Code	Thickness	Code	Thickness
050	0.50 mm	230	2.30 mm
060	0.60 mm	250	2.50 mm
080	0.80 mm	280	2.80 mm
085	0.85 mm	320	3.20 mm
115	1.15 mm		
125	1.25 mm		
160	1.60 mm		
200	2.00 mm		

Packaging Style

Code	Style
A	178 mm Reel, 4 mm Pitch
B	178 mm Reel, 2 mm Pitch
K	178 mm Reel, 8 mm Pitch

Special Reserved Code

Code	Description
A, B	TDK Internal Code





Capacitance Range Chart

EIA CC0402 [C1005]

Capacitance Range Chart

Temperature Characteristics: NP0 ($0 \pm 30\text{ppm}/^\circ\text{C}$), X8R ($\pm 15\%$)

Rated Voltage: 100V (2A), 50V (1H), 25V (1E), 16V (1C)

Capacitance (pF)	Code	Tolerance	NP0		X8R			
			2A (100V)	1H (50V)	2A (100V)	1H (50V)	1E (25V)	1C (16V)
1	010	C: $\pm 0.25\text{pF}$						
1.5	1R5	D: $\pm 0.50\text{pF}$						
2	020	J: $\pm 5\%$						
2.2	2R2	K: $\pm 10\%$						
3	030	M: $\pm 20\%$						
3.3	3R3							
4	040							
4.7	4R7							
5	050							
6	060							
6.8	6R8							
7	070							
8	080							
9	090							
10	100							
12	120							
15	150							
18	180							
22	220							
27	270							
33	330							
39	390							
47	470							
56	560							
68	680							
82	820							
100	101							
120	121							
150	151							
180	181							
220	221							
270	271							
330	331							
390	391							
470	471							
560	561							
680	681							
820	821							
1,000	102							
1,500	152							
2,200	222							
3,300	332							
4,700	472							
6,800	682							
10,000	103							
15,000	153							
22,000	223							
33,000	333							
47,000	473							

Standard Thickness

0.50 mm





Capacitance Range Chart

EIA CC0603 [C1608]

Capacitance Range Chart

Temperature Characteristics: NP0 ($0 \pm 30\text{ppm}/^\circ\text{C}$), X8R ($\pm 15\%$)

Rated Voltage: 250V (2E), 100V (2A), 50V (1H), 25V (1E), 16V (1C)

Capacitance (pF)	Code	Tolerance	NP0		
			2E (250V)	2A (100V)	1H (50V)
1	010	C: $\pm 0.25\text{pF}$ D: $\pm 0.50\text{pF}$ J: $\pm 5\%$			
2	1R5				
2	020				
2	2R2				
3	030				
3	3R3				
4	040				
5	4R7				
5	050				
6	060				
7	6R8				
7	070				
8	080				
9	090				
10	100				
12	120				
15	150				
18	180				
22	220				
27	270				
33	330				
39	390				
47	470				
56	560				
68	680				
82	820				
100	101				
120	121				
150	151				
180	181				
220	221				
270	271				
330	331				
390	391				
470	471				
560	561				
680	681				
820	821				
1,000	102				
1,200	122				
1,500	152				
1,800	182				
2,200	222				
2,700	272				
3,300	332				
3,900	392				
4,700	472				
5,600	562				
6,800	682				
8,200	822				
10,000	103				

Capacitance (pF)	Code	Tolerance	X8R			
			2A (100V)	1H (50V)	1E (25V)	1C (16V)
1,000	102	K: $\pm 10\%$ M: $\pm 20\%$				
1,500	152					
2,200	222					
3,300	332					
4,700	472					
6,800	682					
10,000	103					
15,000	153					
22,000	223					
33,000	333					
47,000	473					
68,000	683					
100,000	104					
150,000	154					
220,000	224					
330,000	334					
470,000	474					

Standard Thickness

 0.80 mm





Capacitance Range Chart

EIA CC0805 [C2012]

Capacitance Range Chart

Temperature Characteristics: NP0 ($0 \pm 30\text{ppm}/^\circ\text{C}$), X8R ($\pm 15\%$)

Rated Voltage: 450V(2W), 250V(2E), 100V(2A), 50V(1H), 25V(1E), 16V(1C)

Capacitance (pF)	Code	Tolerance	NP0				X8R			
			2W (450V)	2E (250V)	2A (100V)	1H (50V)	2A (100V)	1H (50V)	1E (25V)	1C (16V)
100	101	J: $\pm 5\%$ K: $\pm 10\%$ M: $\pm 20\%$								
120	121									
150	151									
180	181									
220	221									
270	271									
330	331									
390	391									
470	471									
560	561									
680	681									
820	821									
1,000	102									
1,200	122									
1,500	152									
1,800	182									
2,200	222									
2,700	272									
3,300	332									
3,900	392									
4,700	472									
5,600	562									
6,800	682									
8,200	822									
10,000	103									
15,000	153									
22,000	223									
33,000	333									
47,000	473									
68,000	683									
100,000	104									
150,000	154									
220,000	224									
330,000	334									
470,000	474									
680,000	684									
1,000,000	105									

Standard Thickness

- 0.60 mm
- 0.85 mm
- 1.25 mm





Capacitance Range Chart

EIA CC1206 [C3216]

Capacitance Range Chart

Temperature Characteristics: NP0 ($0 \pm 30\text{ppm}/^\circ\text{C}$), X8R ($\pm 15\%$)

Rated Voltage: 630V(2J), 450V(2W), 250V(2E), 100V (2A), 50V (1H), 25V (1E), 16V (1C)

Capacitance (pF)	Code	Tolerance	NP0					X8R			
			2J (630V)	2W (450V)	2E (250V)	2A (100V)	1H (50V)	2A (100V)	1H (50V)	1E (25V)	1C (16V)
3,900	392	J: $\pm 5\%$									
4,700	472	K: $\pm 10\%$									
5,600	562	M: $\pm 20\%$									
6,800	682										
8,200	822										
10,000	103										
15,000	153										
22,000	223										
33,000	333										
47,000	473										
68,000	683										
100,000	104										
150,000	154										
220,000	224										
330,000	334										
470,000	474										
680,000	684										
1,000,000	105										
1,500,000	155										
2,200,000	225										
3,300,000	335										
4,700,000	475										

Standard Thickness

- 0.60 mm
- 0.85 mm
- 1.15 mm
- 1.60 mm



Capacitance Range Chart

EIA CC1210 [C3225]

Capacitance Range Chart

Temperature Characteristics: NP0 ($0 \pm 30\text{ppm}/^\circ\text{C}$), X8R ($\pm 15\%$)

Rated Voltage: 630V(2J), 450V(2W), 250V(2E), 100V (2A), 50V (1H), 25V (1E), 16V (1C)

Capacitance (pF)	Code	Tolerance	NP0					X8R		
			2J (630V)	2W (450V)	2E (250V)	2A (100V)	1H (50V)	2A (100V)	1E (25V)	1C (16V)
8,200	822	J: $\pm 5\%$								
10,000	103	K: $\pm 10\%$								
15,000	153	M: $\pm 20\%$								
22,000	223									
33,000	333									
47,000	473									
68,000	683									
100,000	104									
470,000	474									
680,000	684									
1,500,000	155									
2,200,000	225									
3,300,000	335									
4,700,000	475									
6,800,000	685									
10,000,000	106									

Standard Thickness

- 1.25 mm
- 1.60 mm
- 2.00 mm
- 2.30 mm
- 2.50 mm





Capacitance Range Chart

EIA CC1812 [C4532]

Capacitance Range Chart

Temperature Characteristics: NP0 ($0 \pm 30\text{ppm}/^\circ\text{C}$)

Rated Voltage: 630V(2J), 450V(2W), 250V(2E), 100V (2A), 50V (1H)

Capacitance (pF)	Code	Tolerance	NP0				
			2J (630V)	2W (450V)	2E (250V)	2A (100V)	1H (50V)
33,000	333	J: $\pm 5\%$					
47,000	473						
68,000	683						
100,000	104						
150,000	154						
220,000	224						

Standard Thickness

	1.60 mm
	2.00 mm
	2.30 mm
	2.50 mm
	3.20 mm



Capacitance Range Chart

EIA CC2220 [C5750]

Capacitance Range Chart

Temperature Characteristics: NP0 ($0 \pm 30\text{ppm}/^\circ\text{C}$)

Rated Voltage: 450V(2W), 250V(2E), 100V (2A)

Capacitance (pF)	Code	Tolerance	NP0		
			2W (450V)	2E (250V)	2A (100V)
100,000	104	J: $\pm 5\%$			
150,000	154				

Standard Thickness

	2.30 mm
	2.80 mm





Capacitance Range Table

Class 1 (Temperature Compensating)

Temperature Characteristics: NP0 (-55 to +150°C, 0±30 ppm/°C)

Capacitance	Size	Thickness (mm)	Capacitance Tolerance	Catalog Number			
				Rated Voltage Edc: 630V	Rated Voltage Edc: 450V	Rated Voltage Edc: 250V	Rated Voltage Edc: 100V
1 pF	1005	0.50 ± 0.05	± 0.25pF				C1005NP01H010C050BA
	1608	0.80 ± 0.10	± 0.25pF			C1608NP02A010C080AA	C1608NP01H010C080AA
1.5 pF	1005	0.50 ± 0.05	± 0.25pF				C1005NP01H1R5C050BA
	1608	0.80 ± 0.10	± 0.25pF			C1608NP02A1R5C080AA	C1608NP01H1R5C080AA
2 pF	1005	0.50 ± 0.05	± 0.25pF				C1005NP01H020C050BA
	1608	0.80 ± 0.10	± 0.25pF			C1608NP02A020C080AA	C1608NP01H020C080AA
2.2 pF	1005	0.50 ± 0.05	± 0.25pF				C1005NP01H2R2C050BA
	1608	0.80 ± 0.10	± 0.25pF			C1608NP02A2R2C080AA	C1608NP01H2R2C080AA
3 pF	1005	0.50 ± 0.05	± 0.25pF				C1005NP01H030C050BA
	1608	0.80 ± 0.10	± 0.25pF			C1608NP02A030C080AA	C1608NP01H030C080AA
3.3 pF	1005	0.50 ± 0.05	± 0.25pF				C1005NP01H3R3C050BA
	1608	0.80 ± 0.10	± 0.25pF			C1608NP02A3R3C080AA	C1608NP01H3R3C080AA
4 pF	1005	0.50 ± 0.05	± 0.25pF				C1005NP01H040C050BA
	1608	0.80 ± 0.10	± 0.25pF			C1608NP02A040C080AA	C1608NP01H040C080AA
4.7 pF	1005	0.50 ± 0.05	± 0.25pF				C1005NP01H4R7C050BA
	1608	0.80 ± 0.10	± 0.25pF			C1608NP02A4R7C080AA	C1608NP01H4R7C080AA
5 pF	1005	0.50 ± 0.05	± 0.25pF				C1005NP01H050C050BA
	1608	0.80 ± 0.10	± 0.25pF			C1608NP02A050C080AA	C1608NP01H050C080AA
6 pF	1005	0.50 ± 0.05	± 0.50pF				C1005NP01H060D050BA
	1608	0.80 ± 0.10	± 0.50pF			C1608NP02A060D080AA	C1608NP01H060D080AA
6.8 pF	1005	0.50 ± 0.05	± 0.50pF				C1005NP01H6R8D050BA
	1608	0.80 ± 0.10	± 0.50pF			C1608NP02A6R8D080AA	C1608NP01H6R8D080AA
7 pF	1005	0.50 ± 0.05	± 0.50pF				C1005NP01H070D050BA
	1608	0.80 ± 0.10	± 0.50pF			C1608NP02A070D080AA	C1608NP01H070D080AA
8 pF	1005	0.50 ± 0.05	± 0.50pF				C1005NP01H080D050BA
	1608	0.80 ± 0.10	± 0.50pF			C1608NP02A080D080AA	C1608NP01H080D080AA
9 pF	1005	0.50 ± 0.05	± 0.50pF				C1005NP01H090D050BA
	1608	0.80 ± 0.10	± 0.50pF			C1608NP02A090D080AA	C1608NP01H090D080AA
10 pF	1005	0.50 ± 0.05	± 0.50pF				C1005NP01H100D050BA
	1608	0.80 ± 0.10	± 0.50pF			C1608NP02A100D080AA	C1608NP01H100D080AA
12 pF	1005	0.50 ± 0.05	± 5%				C1005NP01H120J050BA
	1608	0.80 ± 0.10	± 5%			C1608NP02A120J080AA	C1608NP01H120J080AA
15 pF	1005	0.50 ± 0.05	± 5%				C1005NP01H150J050BA
	1608	0.80 ± 0.10	± 5%			C1608NP02A150J080AA	C1608NP01H150J080AA
18 pF	1005	0.50 ± 0.05	± 5%				C1005NP01H180J050BA
	1608	0.80 ± 0.10	± 5%			C1608NP02A180J080AA	C1608NP01H180J080AA
22 pF	1005	0.50 ± 0.05	± 5%				C1005NP01H220J050BA
	1608	0.80 ± 0.10	± 5%			C1608NP02A220J080AA	C1608NP01H220J080AA
27 pF	1005	0.50 ± 0.05	± 5%				C1005NP01H270J050BA
	1608	0.80 ± 0.10	± 5%			C1608NP02A270J080AA	C1608NP01H270J080AA
33 pF	1005	0.50 ± 0.05	± 5%				C1005NP01H330J050BA
	1608	0.80 ± 0.10	± 5%			C1608NP02A330J080AA	C1608NP01H330J080AA
39 pF	1005	0.50 ± 0.05	± 5%				C1005NP01H390J050BA
	1608	0.80 ± 0.10	± 5%			C1608NP02A390J080AA	C1608NP01H390J080AA
47 pF	1005	0.50 ± 0.05	± 5%				C1005NP01H470J050BA
	1608	0.80 ± 0.10	± 5%			C1608NP02A470J080AA	C1608NP01H470J080AA
56 pF	1005	0.50 ± 0.05	± 5%				C1005NP01H560J050BA
	1608	0.80 ± 0.10	± 5%			C1608NP02A560J080AA	C1608NP01H560J080AA
68 pF	1005	0.50 ± 0.05	± 5%				C1005NP01H680J050BA
	1608	0.80 ± 0.10	± 5%			C1608NP02A680J080AA	C1608NP01H680J080AA
82 pF	1005	0.50 ± 0.05	± 5%				C1005NP01H820J050BA
	1608	0.80 ± 0.10	± 5%			C1608NP02A820J080AA	C1608NP01H820J080AA
100 pF	1005	0.50 ± 0.05	± 5%				C1005NP02A101J050BA
	1608	0.80 ± 0.10	± 5%				C1608NP02A101J080AA
	2012	0.60 ± 0.15	± 5%		C2012NP02W101J060AA		C1608NP01H101J080AA
120 pF	1005	0.50 ± 0.05	± 5%				C1005NP02A121J050BA
	1608	0.80 ± 0.10	± 5%				C1608NP02A121J080AA
	2012	0.60 ± 0.15	± 5%		C2012NP02W121J060AA		C1608NP01H121J080AA
150 pF	1005	0.50 ± 0.05	± 5%				C1005NP02A151J050BA
	1608	0.80 ± 0.10	± 5%				C1608NP02A151J080AA
	2012	0.60 ± 0.15	± 5%		C2012NP02W151J060AA		C1608NP01H151J080AA
180 pF	1005	0.50 ± 0.05	± 5%				C1005NP02A181J050BA
	1608	0.80 ± 0.10	± 5%				C1608NP02A181J080AA
	2012	0.60 ± 0.15	± 5%		C2012NP02W181J060AA		C1608NP01H181J080AA





Capacitance Range Table

Class 1 (Temperature Compensating)

Temperature Characteristics: NP0 (-55 to +150°C, 0±30 ppm/°C)

Capacitance	Size	Thickness (mm)	Capacitance Tolerance	Catalog Number				
				Rated Voltage Edc: 630V	Rated Voltage Edc: 450V	Rated Voltage Edc: 250V	Rated Voltage Edc: 100V	Rated Voltage Edc: 50V
220 pF	1005	0.50 ± 0.05	± 5%				C1005NP02A221J050BA	C1005NP01H221J050BA
	1608	0.80 ± 0.10	± 5%				C1608NP02A221J080AA	C1608NP01H221J080AA
	2012	0.60 ± 0.15	± 5%	C2012NP02W221J060AA				
270 pF	1005	0.50 ± 0.05	± 5%				C1005NP02A271J050BA	C1005NP01H271J050BA
	1608	0.80 ± 0.10	± 5%				C1608NP02A271J080AA	C1608NP01H271J080AA
	2012	0.60 ± 0.15	± 5%	C2012NP02W271J060AA				
330 pF	1005	0.50 ± 0.05	± 5%				C1005NP02A331J050BA	C1005NP01H331J050BA
	1608	0.80 ± 0.10	± 5%				C1608NP02A331J080AA	C1608NP01H331J080AA
	2012	0.60 ± 0.15	± 5%	C2012NP02W331J060AA				
390 pF	1005	0.50 ± 0.05	± 5%				C1005NP02A391J050BA	C1005NP01H391J050BA
	1608	0.80 ± 0.10	± 5%				C1608NP02A391J080AA	C1608NP01H391J080AA
	2012	0.60 ± 0.15	± 5%	C2012NP02W391J060AA				
470 pF	1005	0.50 ± 0.05	± 5%				C1005NP02A471J050BA	C1005NP01H471J050BA
	1608	0.80 ± 0.10	± 5%				C1608NP02A471J080AA	C1608NP01H471J080AA
	2012	0.60 ± 0.15	± 5%	C2012NP02W471J060AA				
560 pF	1005	0.50 ± 0.05	± 5%					C1005NP01H561J050BA
	1608	0.80 ± 0.10	± 5%				C1608NP02A561J080AA	C1608NP01H561J080AA
	2012	0.60 ± 0.15	± 5%	C2012NP02W561J060AA				
680 pF	1005	0.50 ± 0.05	± 5%					C1005NP01H681J050BA
	1608	0.80 ± 0.10	± 5%				C1608NP02A681J080AA	C1608NP01H681J080AA
	2012	0.60 ± 0.15	± 5%	C2012NP02W681J060AA				
820 pF	1005	0.50 ± 0.05	± 5%					C1005NP01H821J050BA
	1608	0.80 ± 0.10	± 5%		C1608NP02E821J080AA	C1608NP02A821J080AA	C1608NP01H821J080AA	
	2012	0.60 ± 0.15	± 5%	C2012NP02W821J060AA				
1 nF	1005	0.50 ± 0.05	± 5%					C1005NP01H102J050BA
	1608	0.80 ± 0.10	± 5%		C1608NP02E102J080AA	C1608NP02A102J080AA	C1608NP01H102J080AA	
	2012	0.60 ± 0.15	± 5%	C2012NP02W102J060AA		C2012NP02A102J060AA		
1.2 nF	1608	0.80 ± 0.10	± 5%		C1608NP02E122J080AA	C1608NP02A122J080AA	C1608NP01H122J080AA	
	2012	0.60 ± 0.15	± 5%	C2012NP02W122J060AA		C2012NP02A122J060AA		
	1608	0.80 ± 0.10	± 5%		C1608NP02E152J080AA	C1608NP02A152J080AA	C1608NP01H152J080AA	
1.5 nF	2012	0.60 ± 0.15	± 5%			C2012NP02A152J060AA		
		0.85 ± 0.15	± 5%	C2012NP02W152J085AA				
	1608	0.80 ± 0.10	± 5%		C1608NP02E182J080AA	C1608NP02A182J080AA	C1608NP01H182J080AA	
1.8 nF	2012	0.85 ± 0.15	± 5%	C2012NP02W182J085AA		C2012NP02A182J085AA		
	1608	0.80 ± 0.10	± 5%		C1608NP02E222J080AA	C1608NP02A222J080AA	C1608NP01H222J080AA	
	2012	0.85 ± 0.15	± 5%	C2012NP02W222J085AA		C2012NP02A222J085AA		
2.7 nF	1608	0.80 ± 0.10	± 5%				C1608NP01H272J080AA	
		0.80±0.15/-0.1	± 5%			C1608NP02A272J080AA		
	2012	0.60 ± 0.15	± 5%				C2012NP01H272J060AA	
3.3 nF		1.25 ± 0.20	± 5%	C2012NP02W272J125AA		C2012NP02A272J125AA		
	1608	0.80 ± 0.10	± 5%				C1608NP01H332J080AA	
		0.80 + 0.15/-0.1	± 5%			C1608NP02A332J080AA		
3.9 nF		0.60 ± 0.15	± 5%				C2012NP01H332J060AA	
	2012	0.85 ± 0.15	± 5%		C2012NP02E332J085AA			
		1.25 ± 0.20	± 5%	C2012NP02W332J125AA		C2012NP02A332J125AA		
3.9 nF	1608	0.80 ± 0.10	± 5%				C1608NP01H392J080AA	
		0.60 ± 0.15	± 5%				C2012NP01H392J060AA	
	2012	1.25 ± 0.20	± 5%	C2012NP02W392J125AA	C2012NP02E392J125AA	C2012NP02A392J125AA		
4.7 nF	3216	0.60 ± 0.15	± 5%				C3216NP02A392J060AA	
		0.85 ± 0.15	± 5%	C3216NP02J392J085AA				
	1608	0.80 ± 0.10	± 5%				C1608NP01H472J080AA	
4.7 nF		0.60 ± 0.15	± 5%				C2012NP01H472J060AA	
	2012	1.25 ± 0.20	± 5%	C2012NP02W472J125AA	C2012NP02E472J125AA	C2012NP02A472J125AA		
	3216	0.60 ± 0.15	± 5%				C3216NP01H472J060AA	
5.6 nF		0.85 ± 0.15	± 5%	C3216NP02J472J085AA		C3216NP02A472J085AA		
	1608	0.80 ± 0.10	± 5%				C1608NP01H562J080AA	
		0.60 ± 0.15	± 5%				C2012NP01H562J060AA	
5.6 nF	2012	1.25 ± 0.20	± 5%	C2012NP02W562J125AA	C2012NP02E562J125AA	C2012NP02A562J125AA		
		0.60 ± 0.15	± 5%				C3216NP01H562J060AA	
	3216	0.85 ± 0.15	± 5%			C3216NP02A562J085AA		
5.6 nF		1.15 ± 0.15	± 5%	C3216NP02J562J115AA				





Capacitance Range Table

Class 1 (Temperature Compensating)

Temperature Characteristics: NP0 (-55 to +150°C, 0±30 ppm/°C)

Capacitance	Size	Thickness (mm)	Capacitance Tolerance	Catalog Number				
				Rated Voltage Edc: 630V	Rated Voltage Edc: 450V	Rated Voltage Edc: 250V	Rated Voltage Edc: 100V	Rated Voltage Edc: 50V
6.8 nF	1608	0.80 ± 0.10	± 5%					C1608NP01H682J080AA
	2012	0.60 ± 0.15	± 5%					C2012NP01H682J060AA
		1.25 ± 0.20	± 5%			C2012NP02E682J125AA	C2012NP02A682J125AA	
	3216	0.60 ± 0.15	± 5%					C3216NP01H682J060AA
		1.15 ± 0.15	± 5%	C3216NP02J682J115AA	C3216NP02W682J115AA		C3216NP02A682J115AA	
8.2 nF	1608	0.80 ± 0.10	± 5%					C1608NP01H822J080AA
	2012	0.60 ± 0.15	± 5%					C2012NP01H822J060AA
		1.25 ± 0.20	± 5%			C2012NP02E822J125AA	C2012NP02A822J125AA	
	3216	0.60 ± 0.15	± 5%					C3216NP01H822J060AA
		1.15 ± 0.15	± 5%		C3216NP02W822J115AA		C3216NP02A822J115AA	
	3225	1.60 ± 0.20	± 5%	C3216NP02J822J160AA				
		1.25 ± 0.20	± 5%	C3225NP02J822J125AA				
10 nF	1608	0.80 ± 0.10	± 5%					C1608NP01H103J080AA
	2012	0.60 ± 0.15	± 5%					C2012NP01H103J060AA
		1.25 ± 0.20	± 5%			C2012NP02E103J125AA	C2012NP02A103J125AA	
	3216	0.60 ± 0.15	± 5%					C3216NP01H103J060AA
		1.15 ± 0.15	± 5%			C3216NP02E103J115AA	C3216NP02A103J115AA	
	3225	1.60 ± 0.20	± 5%	C3216NP02J103J160AA	C3216NP02W103J160AA			
		1.25 ± 0.20	± 5%	C3225NP02J103J125AA				
15 nF	2012	0.85 ± 0.15	± 5%					C2012NP01H153J085AA
		0.60 ± 0.15	± 5%					C3216NP01H153J060AA
	3216	1.15 ± 0.15	± 5%				C3216NP02A153J115AA	
		1.60 ± 0.20	± 5%		C3216NP02W153J160AA	C3216NP02E153J160AA		
	3225	1.25 ± 0.20	± 5%				C3225NP02A153J125AA	
		1.60 ± 0.20	± 5%	C3225NP02J153J160AA				
	22 nF	2012	1.25 ± 0.20	± 5%				
3216		0.60 ± 0.15	± 5%					C3216NP01H223J060AA
		1.60 ± 0.20	± 5%			C3216NP02E223J160AA	C3216NP02A223J160AA	
3225		1.25 ± 0.20	± 5%					C3225NP01H223J125AA
		1.60 ± 0.20	± 5%			C3225NP02E223J160AA	C3225NP02A223J160AA	
3225		2.30 ± 0.20	± 5%	C3225NP02J223J230AA	C3225NP02W223J230AA			
		1.25 ± 0.20	± 5%					
33 nF	2012	1.25 ± 0.20	± 5%					C2012NP01H333J125AA
		0.85 ± 0.15	± 5%					C3216NP01H333J085AA
	3216	1.60 + 0.3/-0.1	± 5%				C3216NP02A333J160AA	
		1.60 ± 0.20	± 5%					C3225NP01H333J160AA
	3225	2.00 ± 0.20	± 5%				C3225NP02A333J200AA	
		2.30 ± 0.20	± 5%			C3225NP02E333J230AA		
	3225	2.50 ± 0.30	± 5%	C3225NP02J333J250AA	C3225NP02W333J250AA			
4532		2.00 ± 0.20	± 5%	C4532NP02J333J200KA				
47 nF	3216	1.15 ± 0.15	± 5%					C3216NP01H473J115AA
	3225	2.00 ± 0.20	± 5%					C3225NP01H473J200AA
		2.30 ± 0.20	± 5%				C3225NP02A473J230AA	
	3225	2.50 ± 0.30	± 5%			C3225NP02E473J250AA		
		1.60 ± 0.20	± 5%					C4532NP01H473J160KA
	4532	2.00 ± 0.20	± 5%				C4532NP02A473J200KA	
		2.30 ± 0.20	± 5%		C4532NP02W473J230KA			
4532	3.20 ± 0.30	± 5%	C4532NP02J473J320KA					
	68 nF	3216	1.60 ± 0.20	± 5%				
3225		2.00 ± 0.20	± 5%					C3225NP01H683J200AA
		2.30 ± 0.20	± 5%				C3225NP02A683J230AA	
4532		1.60 ± 0.20	± 5%					C4532NP01H683J160KA
		2.30 ± 0.20	± 5%			C4532NP02E683J230KN		
4532		2.50 ± 0.30	± 5%				C4532NP02A683J250KA	
		3.20 ± 0.30	± 5%		C4532NP02W683J320KA			
100 nF	3216	1.60 ± 0.20	± 5%					C3216NP01H104J160AA
	3225	2.50 ± 0.30	± 5%					C3225NP01H104J250AA
	4532	2.00 ± 0.20	± 5%					C4532NP01H104J200KA
		3.20 ± 0.30	± 5%			C4532NP02E104J320KN	C4532NP02A104J320KA	
150 nF	5750	2.80 ± 0.30	± 5%		C5750NP02W104J280KA			
	4532	2.50 ± 0.30	± 5%					C4532NP01H154J250KA
		2.30 ± 0.20	± 5%			C5750NP02E154J230KN	C5750NP02A154J230KA	
220 nF	4532	3.20 ± 0.30	± 5%					C4532NP01H224J320KA





Capacitance Range Table

Class 2 (Temperature Stable)

Temperature Characteristics: X8R (-55 to +150°C, ±15%)

Capacitance	Size	Thickness (mm)	Capacitance Tolerance	Catalog Number			
				Rated Voltage Edc: 100V	Rated Voltage Edc: 50V	Rated Voltage Edc: 25V	Rated Voltage Edc: 16V
150 pF	1005	0.50 ± 0.05	± 10%	C1005X8R2A151K050BA	C1005X8R1H151K050BA		
			± 20%	C1005X8R2A151M050BA	C1005X8R1H151M050BA		
220 pF	1005	0.50 ± 0.05	± 10%	C1005X8R2A221K050BA	C1005X8R1H221K050BA		
			± 20%	C1005X8R2A221M050BA	C1005X8R1H221M050BA		
330 pF	1005	0.50 ± 0.05	± 10%	C1005X8R2A331K050BA	C1005X8R1H331K050BA		
			± 20%	C1005X8R2A331M050BA	C1005X8R1H331M050BA		
470 pF	1005	0.50 ± 0.05	± 10%	C1005X8R2A471K050BA	C1005X8R1H471K050BA		
			± 20%	C1005X8R2A471M050BA	C1005X8R1H471M050BA		
680 pF	1005	0.50 ± 0.05	± 10%	C1005X8R2A681K050BA	C1005X8R1H681K050BA		
			± 20%	C1005X8R2A681M050BA	C1005X8R1H681M050BA		
1 nF	1005	0.50 ± 0.05	± 10%	C1005X8R2A102K050BA	C1005X8R1H102K050BA		
			± 20%	C1005X8R2A102M050BA	C1005X8R1H102M050BA		
	1608	0.80 ± 0.10	± 10%	C1608X8R2A102K080AA	C1608X8R1H102K080AA		
			± 20%	C1608X8R2A102M080AA	C1608X8R1H102M080AA		
1.5 nF	1005	0.50 ± 0.05	± 10%	C1005X8R2A152K050BA	C1005X8R1H152K050BA		
			± 20%	C1005X8R2A152M050BA	C1005X8R1H152M050BA		
	1608	0.80 ± 0.10	± 10%	C1608X8R2A152K080AA	C1608X8R1H152K080AA		
			± 20%	C1608X8R2A152M080AA	C1608X8R1H152M080AA		
2.2 nF	1005	0.50 ± 0.05	± 10%	C1005X8R2A222K050BA	C1005X8R1H222K050BA		
			± 20%	C1005X8R2A222M050BA	C1005X8R1H222M050BA		
	1608	0.80 ± 0.10	± 10%	C1608X8R2A222K080AA	C1608X8R1H222K080AA		
			± 20%	C1608X8R2A222M080AA	C1608X8R1H222M080AA		
3.3 nF	1005	0.50 ± 0.05	± 10%	C1005X8R2A332K050BB	C1005X8R1H332K050BA		
			± 20%	C1005X8R2A332M050BB	C1005X8R1H332M050BA		
	1608	0.80 ± 0.10	± 10%	C1608X8R2A332K080AA	C1608X8R1H332K080AA		
			± 20%	C1608X8R2A332M080AA	C1608X8R1H332M080AA		
4.7 nF	1005	0.50 ± 0.05	± 10%		C1005X8R1H472K050BA		
			± 20%		C1005X8R1H472M050BA		
	1608	0.80 ± 0.10	± 10%	C1608X8R2A472K080AA	C1608X8R1H472K080AA		
			± 20%	C1608X8R2A472M080AA	C1608X8R1H472M080AA		
6.8 nF	1005	0.50 ± 0.05	± 10%		C1005X8R1H682K050BB	C1005X8R1E682K050BA	
			± 20%		C1005X8R1H682M050BB	C1005X8R1E682M050BA	
	1608	0.80 ± 0.10	± 10%	C1608X8R2A682K080AA	C1608X8R1H682K080AA		
			± 20%	C1608X8R2A682M080AA	C1608X8R1H682M080AA		
10 nF	1005	0.50 ± 0.05	± 10%		C1005X8R1H103K050BB	C1005X8R1E103K050BA	
			± 20%		C1005X8R1H103M050BB	C1005X8R1E103M050BA	
	1608	0.80 ± 0.10	± 10%	C1608X8R2A103K080AA	C1608X8R1H103K080AA		
			± 20%	C1608X8R2A103M080AA	C1608X8R1H103M080AA		
15 nF	1005	0.50 ± 0.05	± 10%			C1005X8R1E153K050BB	
			± 20%			C1005X8R1E153M050BB	
	1608	0.80 ± 0.10	± 10%	C1608X8R2A153K080AA	C1608X8R1H153K080AA		
			± 20%	C1608X8R2A153M080AA	C1608X8R1H153M080AA		
22 nF	1005	0.50 ± 0.05	± 10%			C1005X8R1E223K050BB	
			± 20%			C1005X8R1E223M050BB	
	1608	0.80 ± 0.10	± 10%	C1608X8R2A223K080AB	C1608X8R1H223K080AA		
			± 20%	C1608X8R2A223M080AB	C1608X8R1H223M080AA		
33 nF	2012	1.25 ± 0.20	± 10%	C2012X8R2A223K125AA			
			± 20%	C2012X8R2A223M125AA			
	1005	0.50 ± 0.05	± 10%				C1005X8R1C333K050BB
			± 20%				C1005X8R1C333M050BB
33 nF	1608	0.80 ± 0.10	± 10%	C1608X8R2A333K080AB	C1608X8R1H333K080AA		
			± 20%	C1608X8R2A333M080AB	C1608X8R1H333M080AA		
	2012	1.25 ± 0.20	± 10%	C2012X8R2A333K125AB			
			± 20%	C2012X8R2A333M125AB			
33 nF	3216	0.85 ± 0.15	± 10%	C3216X8R2A333K085AA			
			± 20%	C3216X8R2A333M085AA			





Capacitance Range Table

Class 2 (Temperature Stable)

Temperature Characteristics: X8R (-55 to +150°C, ±15%)

Capacitance	Size	Thickness (mm)	Capacitance Tolerance	Catalog Number			
				Rated Voltage Edc: 100V	Rated Voltage Edc: 50V	Rated Voltage Edc: 25V	Rated Voltage Edc: 16V
47 nF	1005	0.50 ± 0.05	± 10%				C1005X8R1C473K050BB
			± 20%				C1005X8R1C473M050BB
	1608	0.80 ± 0.10	± 10%		C1608X8R1H473K080AA		
			± 20%		C1608X8R1H473M080AA		
	2012	1.25 ± 0.20	± 10%	C2012X8R2A473K125AB			
			± 20%	C2012X8R2A473M125AB			
68 nF	3216	0.85 ± 0.15	± 10%	C3216X8R2A473K085AA			
			± 20%	C3216X8R2A473M085AA			
	1608	0.80 ± 0.10	± 10%		C1608X8R1H683K080AB	C1608X8R1E683K080AA	
			± 20%		C1608X8R1H683M080AB	C1608X8R1E683M080AA	
	2012	1.25 ± 0.20	± 10%	C2012X8R2A683K125AB	C2012X8R1H683K125AA		
			± 20%	C2012X8R2A683M125AB	C2012X8R1H683M125AA		
100 nF	3216	1.15 ± 0.15	± 10%	C3216X8R2A683K115AA			
			± 20%	C3216X8R2A683M115AA			
	1608	0.80 ± 0.10	± 10%		C1608X8R1H104K080AB	C1608X8R1E104K080AA	
			± 20%		C1608X8R1H104M080AB	C1608X8R1E104M080AA	
	2012	1.25 ± 0.20	± 10%		C2012X8R1H104K125AA		
			± 20%		C2012X8R1H104M125AA		
150 nF	3216	1.15 ± 0.15	± 10%	C3216X8R2A104K115AA			
			± 20%	C3216X8R2A104M115AA			
	1608	0.80 ± 0.10	± 10%			C1608X8R1E154K080AB	
			± 20%			C1608X8R1E154M080AB	
	2012	0.85 ± 0.15	± 10%			C2012X8R1E154K085AA	
			± 20%			C2012X8R1E154M085AA	
220 nF	3216	1.25 ± 0.20	± 10%		C2012X8R1H154K125AB		
			± 20%		C2012X8R1H154M125AB		
	1608	0.85 ± 0.15	± 10%		C3216X8R1H154K085AA		
			± 20%		C3216X8R1H154M085AA		
	3216	0.85 ± 0.15	± 10%		C3216X8R1H154M085AA		
			± 20%				
330 nF	1608	1.60 ± 0.20	± 10%	C3216X8R2A154K160AA			
			± 20%	C3216X8R2A154M160AA			
	1608	0.80 ± 0.10	± 10%			C1608X8R1E224K080AB	
			± 20%			C1608X8R1E224M080AB	
	2012	1.25 ± 0.20	± 10%		C2012X8R1H224K125AB	C2012X8R1E224K125AA	
			± 20%		C2012X8R1H224M125AB	C2012X8R1E224M125AA	
470 nF	3216	1.15 ± 0.15	± 10%		C3216X8R1H224K115AA		
			± 20%		C3216X8R1H224M115AA		
	1608	1.60 ± 0.20	± 10%	C3216X8R2A224K160AB			
			± 20%	C3216X8R2A224M160AB			
	1608	0.80 ± 0.10	± 10%				C1608X8R1C334K080AB
			± 20%				C1608X8R1C334M080AB
1000 nF	2012	1.25 ± 0.20	± 10%			C2012X8R1E334K125AA	
			± 20%			C2012X8R1E334M125AA	
	3216	0.85 ± 0.15	± 10%			C3216X8R1E334K085AA	
			± 20%			C3216X8R1E334M085AA	
	1608	1.60 ± 0.20	± 10%	C3216X8R2A334K160AB	C3216X8R1H334K160AA		
			± 20%	C3216X8R2A334M160AB	C3216X8R1H334M160AA		
1500 nF	1608	0.80 ± 0.10	± 10%				C1608X8R1C474K080AB
			± 20%				C1608X8R1C474M080AB
	2012	1.25 ± 0.20	± 10%			C2012X8R1E474K125AB	
			± 20%			C2012X8R1E474M125AB	
	3216	0.85 ± 0.15	± 10%			C3216X8R1E474K085AA	
			± 20%			C3216X8R1E474M085AA	
2200 nF	1608	1.60 ± 0.20	± 10%		C3216X8R1H474K160AA		
			± 20%		C3216X8R1H474M160AA		
	3225	2.00 ± 0.20	± 10%	C3225X8R2A474K200AB			
			± 20%	C3225X8R2A474M200AB			
	1608	0.80 ± 0.10	± 10%				C1608X8R1C474K080AB
			± 20%				C1608X8R1C474M080AB
3300 nF	2012	1.25 ± 0.20	± 10%				C2012X8R1E474K125AB
			± 20%				C2012X8R1E474M125AB
	3216	0.85 ± 0.15	± 10%				C3216X8R1E474K085AA
			± 20%				C3216X8R1E474M085AA
	1608	1.60 ± 0.20	± 10%		C3216X8R1H474K160AA		
			± 20%		C3216X8R1H474M160AA		
4700 nF	3225	2.00 ± 0.20	± 10%	C3225X8R2A474K200AB			
			± 20%	C3225X8R2A474M200AB			
	1608	0.80 ± 0.10	± 10%				C1608X8R1C474K080AB
			± 20%				C1608X8R1C474M080AB
	2012	1.25 ± 0.20	± 10%				C2012X8R1E474K125AB
			± 20%				C2012X8R1E474M125AB
10000 nF	3216	0.85 ± 0.15	± 10%				C3216X8R1E474K085AA
			± 20%				C3216X8R1E474M085AA
	1608	0.80 ± 0.10	± 10%				C1608X8R1C474K080AB
			± 20%				C1608X8R1C474M080AB
	2012	1.25 ± 0.20	± 10%				C2012X8R1E474K125AB
			± 20%				C2012X8R1E474M125AB
15000 nF	3216	0.85 ± 0.15	± 10%				C3216X8R1E474K085AA
			± 20%				C3216X8R1E474M085AA
	1608	0.80 ± 0.10	± 10%				C1608X8R1C474K080AB
			± 20%				C1608X8R1C474M080AB
	2012	1.25 ± 0.20	± 10%				C2012X8R1E474K125AB
			± 20%				C2012X8R1E474M125AB
22000 nF	3216	0.85 ± 0.15	± 10%				C3216X8R1E474K085AA
			± 20%				C3216X8R1E474M085AA
	1608	0.80 ± 0.10	± 10%				C1608X8R1C474K080AB
			± 20%				C1608X8R1C474M080AB
	2012	1.25 ± 0.20	± 10%				C2012X8R1E474K125AB
			± 20%				C2012X8R1E474M125AB
33000 nF	3216	0.85 ± 0.15	± 10%				C3216X8R1E474K085AA
			± 20%				C3216X8R1E474M085AA
	1608	0.80 ± 0.10	± 10%				C1608X8R1C474K080AB
			± 20%				C1608X8R1C474M080AB
	2012	1.25 ± 0.20	± 10%				C2012X8R1E474K125AB
			± 20%				C2012X8R1E474M125AB
47000 nF	3216	0.85 ± 0.15	± 10%				C3216X8R1E474K085AA
			± 20%				C3216X8R1E474M085AA
	1608	0.80 ± 0.10	± 10%				C1608X8R1C474K080AB
			± 20%				C1608X8R1C474M080AB
	2012	1.25 ± 0.20	± 10%				C2012X8R1E474K125AB
			± 20%				C2012X8R1E474M125AB
100000 nF	3216	0.85 ± 0.15	± 10%				C3216X8R1E474K085AA
			± 20%				C3216X8R1E474M085AA
	1608	0.80 ± 0.10	± 10%				C1608X8R1C474K080AB
			± 20%				C1608X8R1C474M080AB
	2012	1.25 ± 0.20	± 10%				C2012X8R1E474K125AB
			± 20%				C2012X8R1E474M125AB
150000 nF	3216	0.85 ± 0.15	± 10%				C3216X8R1E474K085AA
			± 20%				C3216X8R1E474M085AA
	1608	0.80 ± 0.10	± 10%				C1608X8R1C474K080AB
			± 20%				C1608X8R1C474M080AB
	2012	1.25 ± 0.20	± 10%				C2012X8R1E474K125AB
			± 20%				C2012X8R1E474M125AB
220000 nF	3216	0.85 ± 0.15	± 10%				C3216X8R1E474K085AA
			± 20%				C3216X8R1E474M085AA
	1608	0.80 ± 0.10	± 10%				C1608X8R1C474K080AB
			± 20%				C1608X8R1C474M080AB
	2012	1.25 ± 0.20	± 10%				C2012X8R1E474K125AB
			± 20%				C2012X8R1E474M125AB
330000 nF	3216	0.85 ± 0.15	± 10%				C3216X8R1E474K085AA
			± 20%				C3216X8R1E474M085AA
	1608	0.80 ± 0.10	± 10%				C1608X8R1C474K080AB
			± 20%				C1608X8R1C474M080AB
	2012	1.25 ± 0.20	± 10%				C2012X8R1E474K125AB
			± 20%				C2012X8R1E474M125AB
470000 nF	3216	0.85 ± 0.15	± 10%				C3216X8R1E474K085AA
			± 20%				C3216X8R1E474M085AA
	1608	0.80 ± 0.10	± 10%				C1608X8R1C474K080AB
			± 20%				C1608X8R1C474M080AB
	2012	1.25 ± 0.20	± 10%				C2012X8R1E474K125AB
			± 20%				C2012X8R1E474M125AB
1000000 nF	3216	0.85 ± 0.15	± 10%				C3216X8R1E474K085AA
			± 20%				C3216X8R1E474M085AA
	1608	0.80 ± 0.10	± 10%				C1608X8R1C474K080AB
			± 20%				C1608X8R1C474M080AB
	2012	1.25 ± 0.20	± 10%				C2012X8R1E474K125AB
			± 20%				C2012X8R1E474M125AB
1500000 nF	3216	0.85 ± 0.15	± 10%				C3216X8R1E474K085AA
			± 20%				C3216X8R1E474M085AA
	1608	0.80 ± 0.10	± 10%				C1608X8R1C474K080AB
			± 20%				C1608X8R1C474M080AB
	2012	1.25 ± 0.20	± 10%				C2012X8R1E474K125AB
			± 20%				C2012X8R1E474M125AB
2200000 nF	3216	0.85 ± 0.15	± 10%				C3216X8R1E474K085AA
			± 20%				C3216X8R1E474M085AA
	1608	0.80 ± 0.10	± 10%				C1608X8R1C474K080AB
			± 20%				C1608X8R1C474M080AB
	2012	1.25 ± 0.20	± 10%				C2012X8R1E474K125AB
			± 20%				C2012X8R1E474M125AB
3300000 nF	3216	0.85 ± 0.15	± 10%				C3216X8R1E474K085AA
			± 20%				C3216X8R1E474M085AA
	1608	0.80 ± 0.10	± 10%				C1608X8R1C474K080AB
			± 20%				C1608X8R1C474M080AB
	2012	1.25 ± 0.20	± 10%				C2012X8R1E474K125AB
			± 20%				C2012X8R1E474M125AB
4700000 nF	3216	0.85 ± 0.15	± 10%				C3216X8R1E474K085AA
			± 20%				C3216X8R1E474M085AA
	1608	0.80 ± 0.10	± 10%				C1608X8R1C474K080AB
			± 20%				C1608X8R1C474M080AB
	2012	1.25 ± 0.20	± 10%				C2012X8R1E474K125AB
			± 20%				C2012X8R1E474M125AB
10000000 nF	3216	0.85 ± 0.15	± 10%				C3216X8R1E474K085AA
			± 20%				C3216X8R1E474M085AA
	1608	0.80 ± 0.10	± 10%				C1608X8R1C474K080AB
			± 20%				C1608X8R1C474M080AB
	2012	1.25 ± 0.20	± 10%				C2012X8R1E474K125AB
			± 20%				C2012X8R1E474M125AB
15000000 nF	3216	0.85 ± 0.15	± 10%				C3216X8R1E474K085AA
			± 20%				C3216X8R1E474M085AA
	1608	0.80 ± 0.10	± 10%				C1608X8R1C474



Capacitance Range Table

Class 2 (Temperature Stable)

Temperature Characteristics: X8R (-55 to +150°C, ±15%)

Capacitance	Size	Thickness (mm)	Capacitance Tolerance	Catalog Number			
				Rated Voltage Edc: 100V	Rated Voltage Edc: 50V	Rated Voltage Edc: 25V	Rated Voltage Edc: 16V
680 nF	2012	1.25 ± 0.20	± 10%				C2012X8R1C684K125AB
			± 20%				C2012X8R1C684M125AB
	3216	1.15 ± 0.15	± 10%			C3216X8R1E684K115AA	
			± 20%			C3216X8R1E684M115AA	
		1.60 ± 0.20	± 10%		C3216X8R1H684K160AB		
			± 20%		C3216X8R1H684M160AB		
1 µF	3225	2.50 ± 0.30	± 10%	C3225X8R2A684K250AB			
			± 20%	C3225X8R2A684M250AB			
	2012	1.25 ± 0.20	± 10%				C2012X8R1C105K125AB
			± 20%				C2012X8R1C105M125AB
1.5 µF	3216	1.60 ± 0.20	± 10%		C3216X8R1H105K160AB	C3216X8R1E105K160AA	
			± 20%		C3216X8R1H105M160AB	C3216X8R1E105M160AA	
	3225	1.60 ± 0.20	± 10%			C3216X8R1E155K160AB	
			± 20%			C3216X8R1E155M160AB	
			± 10%			C3225X8R1E155K160AA	
			± 20%			C3225X8R1E155M160AA	
2.2 µF	3216	1.60 ± 0.20	± 10%			C3216X8R1E225K160AB	
			± 20%			C3216X8R1E225M160AB	
	3225	2.00 ± 0.20	± 10%			C3225X8R1E225K200AA	
			± 20%			C3225X8R1E225M200AA	
3.3 µF	3216	1.60 ± 0.20	± 10%				C3216X8R1C335K160AB
			± 20%				C3216X8R1C335M160AB
	3225	2.50 ± 0.30	± 10%			C3225X8R1E335K250AA	
			± 20%			C3225X8R1E335M250AA	
4.7 µF	3216	1.60 ± 0.20	± 10%				C3216X8R1C475K160AB
			± 20%				C3216X8R1C475M160AB
	3225	2.50 ± 0.30	± 10%			C3225X8R1E475K250AB	
			± 20%			C3225X8R1E475M250AB	
6.8 µF	3225	2.00 ± 0.20	± 10%				C3225X8R1C685K200AB
			± 20%				C3225X8R1C685M200AB
10 µF	3225	2.50 ± 0.30	± 10%				C3225X8R1C106K250AB
			± 20%				C3225X8R1C106M250AB



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TDK:

C1608X8R2A153K	C2012X8R1E224K	C1005X8R1E103K	C2012X8R2A223K	C1608X8R2A103K
C1608X8R2A102K	C1608X8R1H102K	C1608X8R1H103K	C1608X8R1H222K	C1608X8R1H223K
C3216X8R1H474K	C2012X8R1H104K	C1608X8R2A472K	C3216X8R2A154K	C3225X8R1E335K
C2012X8R1E334K	C3216X8R1E105K	C1608X8R1E104K	C1005X8R1H471K	C1005X8R1H472K
C1005X8R1H222K	C1005X8R1H221K	C1608X8R1H472K	C1608X8R1H473K	C3225X8R1E225K
C3216X8R1E474K	C3216X8R2A473K	C1005X8R1H102K	C1608X8R2A222K	C3216X8R2A104K
C3216X8R1H224K	C1005X8R1E682K	C1005X8R1H151K	C1005X8R1H331K	C1005X8R1H681K
C1005X8R1H152K	C1005X8R1H332K	C1608X8R1E683K	C1608X8R1H152K	C1608X8R1H332K
C1608X8R1H682K	C1608X8R1H153K	C1608X8R1H333K	C1608X8R2A152K	C1608X8R2A332K
C1608X8R2A682K	C2012X8R1E154K	C2012X8R1H683K	C3216X8R1E334K	C3216X8R1E684K
C3216X8R1H154K	C3216X8R1H334K	C3216X8R2A333K	C3216X8R2A683K	C3225X8R1E155K
C1005X8R1H103K	C1608X8R1H104K	C1608X8R1E224K	C1608X8R1C334K	C1608X8R1C474K
C2012X8R1H154K	C2012X8R1E474K	C3216X8R1H684K	C3216X8R1E155K	C3216X8R1C335K
C3216X8R1C475K	C3225X8R1C685K	C1005X8R1H682K	C1608X8R1H683K	C3216X8R1H105K
C2012X8R1H224K	C2012X8R1C105K	C3225X8R1C106K	C1005X8R1E153K	C1005X8R1C473K
C1608X8R1E154K	C1005X8R1E223K	C2012X8R1C684K	C3216X8R1E225K	C5750NP02A154J230KA
C2012NP02A562J125AA	C2012NP02A682J125AA	C1608NP02A332J080AA	C3216NP02A333J160AA	
C3216NP02A223J160AA	C3225NP02A683J250AA	C1608NP02A182J080AA	C2012NP02A822J125AA	
C1608NP02A222J080AA	C2012NP02A103J125AA	C1608NP02A272J080AA	C1608NP02A152J080AA	
C3216NP02A153J115AA	C3216X8R2A333K085AA	C1005X8R1H151K050BA	C1005X8R1H222K050BA	
C1005X8R1H471K050BA	C1608X8R2A102K080AA	C1608X8R2A103K080AA	C2012X8R1H104K125AA	