+

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

+

CJ88XXXY	PANDUIT PART NO.
8 POSITION, 8 WIRE TERMINATION CAP IS COLOR CODED FOR EIA/TIA 568A AND/OR 568B WIRING.	DESCRIPTION
1.62 LB/100 PCS (738 g/100 PCS)	WEIGHT

TERMINATION CAP

SELECTIVE TIN-LEAD POST-PLATING ON IDC TERMINATIONS WITH CONTINUOUS NICKEL UNDERPLATING.

[34.8] SEE JACK HOUSING NOTE 2 (JACK HOUSING)

- \$ = 1 . 72

50 MICRO INCH GOLD PLATING AT MATING JACK SIDE WITH CONTINUOUS NICKEL UNDERPLATING.

NOTE:

- 1. SEE CURRENT CATALOG FOR ADDITIONAL PART
 NUMBER SUFFIXES TO INDICATE COLOR AND OR
 PACKAGE QUANTITY.

 2. MATERIAL:
 JACK HOUSING ABS NOMINAL WALL THICKNESS .078(2.0).
 TERMINATION CAP POLYCARBONATE
 ALL MINI-JACK 8 POSITION, 8 WIRE CONNECTOR
 MODULES ARE UNIVERSAL IN DESIGN.
 THEY WILL ACCEPT TWO, THREE, OR FOUR PAIR
 MODULAR PLUGS WITHOUT DAMAGE.
- THIS PART IS DESIGNED FOR USE WITH MINI-COM PLATES & BOXES.
 MEETS ALL CATEGORY 3 PERFORMANCE REQUIREMENTS AS DEFINED BY EIA/TIA.
- DIMENSIONS IN PARENTHESIS ARE IN METRIC.

<u></u>თ ហ 4

CAD FILENAME/LAYERS M02479MV_DC335_00A.PRT

CORP. TINLEY PARK, ILLINOIS

MINI-JACK CATEGORY 3 TWISTED PAIR CONNECTOR MODULE CUSTOMER DRAWING

ž	-335			
Ę				
CHK CUST SUP				
SUP				
CHECKED BY	03-24-06	DRAWN BY NER	(.xx) ± .03	DIMENSION
	AS NOTED	MAT'L:	(.X) ± .03 (.XXX) ± .005 (.XX) ± .01 ANGLES ± 1°	UNLESS OTHERWISE SPECIFIED,
024/9-335	DRAWING NO.	NONE	IN INCHES, THIRD ANGLE PROJECTION.	UNLESS OTHERWISE SPECIFIED,
SIZE	Dw _G		OTION.	
1				

+

J

NER N ВЧ E S

RELEASED

PRODUCTION

02479-ECZ

DESCRIPTION TO

DATE 3-24-06

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

CJ88BLY CJ88EIY