



Micro Commercial Components

Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

CXT5401

Features

- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Switching and amplification in high voltage Applications such as telephony
- Epoxy meets UL 94 V-0 flammability rating
- Moisure Sensitivity Level 1

PNP Plastic-Encapsulate Transistors


Maximum Ratings

Symbol	Rating	Value	Unit
V_{CEO}	Collector-Emitter Voltage	150	V
V_{CBO}	Collector-Base Voltage	160	V
V_{EBO}	Emitter-Base Voltage	5.0	V
I _C	Collector Current DC	0.5	Α
Pc	Collector Power Dissipation	0.5	W
TJ	Junction Temperature	150	°С
T _{STG}	Storage Temperature	-65 to +150	°C

Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Тур	Max	Units
OFF CHARA	CTERISTICS				
V _{CBO}	Collector-Base Voltage (I _C =100uAdc, I _E =0)	160			Vdc
V _{CEO}	Collector-Emitter Voltage (I _C =1mAdc, I _B =0)	150			Vdc
V _{EBO}	Emitter-Base Voltage (I _E =10uAdc, I _C =0)	5.0			Vdc
I _{CBO}	Collector Cutoff Current (V _{CB} =120Vdc, I _E =0)			50	nAdc
I _{EBO}	Emitter Cutoff Current (V _{EB} =3.0Vdc, I _C =0)			50	nAdc
h _{FE(1)}	DC Current Gain (V _{CE} =5.0Vdc, I _C =1mAdc)	50			
h _{FE(2)}	DC Current Gain (V _{CE} =5.0Vdc, I _C =10mAdc)	60		300	
h _{FE(3)}	DC Current Gain (V _{CE} =5.0Vdc, I _C =50mAdc)	50			
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage (I _C =10mAdc,I _B =1mAdc)			0.2	Vdc
V _{CE(sat)}	Collector-Emitter Saturation Voltage (I _C =50mAdc,I _B =5mAdc)			0.5	Vdc
V _{BE(sat)}	Base-Emitter Voltage (I _C =10mAdc,I _B =1mAdc)			1	Vdc
V _{BE(sat)}	Base-Emitter Voltage (I _C =50mAdc,I _B =5mAdc)			1	Vdc
f⊤	Transition Frequency (V _{CE} =10Vdc, I _C =10mAdc, f=100MHz)	100		300	MHz
Соь	Collector output capacitance (V _{CB} =10Vdc, I _E =0, f=1MHz)			6	pF
NF	Noise figure (V _{CE} =5Vdc, I _C =0.2mAdc, f=10MHz-15.7KHZ,Rs=10ohm)			8	dB

SOT-89




DIMENSINS						
DIM	INCHES		MM		NOTES	
	MIN	MAX	MIN	MAX		
Α	.173	.181	4.39	4.60		
В	.061		1.55		REF.	
С	.154	.165	3.91	4.25		
D	.031	.039	0.80	1.00		
Е	.092	.100	2.34	2.54		
F	.118		3.00		TYP	
G	.013	.019	0.33	0.48		
Н	.015	.021	0.38	0.53		
J	.015	.016	0.38	0.41		
K	.055	.063	1.40	1.60		




Micro Commercial Components


Typical Characteristics



DC Current Gain



Collector Saturation Region





Micro Commercial Components

Ordering Information:

Device	Packing
Part Number-TP	Tape&Reel1Kpcs/Reel

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.