


[→ Honeywell.com](#) [→ Automation & Control Solutions](#)
[HOME](#)
[ABOUT US](#)
[KEY INDUSTRIES SERVED](#)
[PRODUCTS & INFORMATION](#)
[NEWS & EVENTS](#)
[SALES & SUPPORT](#)
[LOGIN](#)

Honeywell Sensing and Control

Search



GLBA02A

(Home : Products : Switches » MICRO SWITCH™ Limit Switches » MICRO SWITCH™ Global Limit Switches » GLS DIN)

narrow your search

Products

- Controls Monitoring and Lighting (286)
- Machine Safety (1727)
- Sensors (6158)
- Switches (9781)
- Wireless (45)

Technology

- Control and Instrumentation (890)
- Electromechanical (9303)
- Magnetic (538)
- Platinum thin film (56)
- Thick Film (1372)
- More...



Actual product appearance may vary.

Global Limit Switches Series GLS: Side Rotary With -- No Lever --, 1NC 1NO SPDT Snap Action, 0.5 in - 14NPT conduit

[Sales & Service](#)
[Distributor Inventory](#)

new products

New Wireless Products

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



[Wireless Web Site](#)
[WGLA and WPMM](#)
[XYR6000™](#)

[find out more](#)

white papers

Wireless Switches Offer Unlimited Benefit
 Basic Switches Are Not Created Equal
 Applying Precision Switches
 Sensors for Medical Devices
 New Ways to Measure Torque
 Choosing Safety Switches
 Specifying Hour Meters

Need help?

[Click here to contact us](#)
[Overview](#) [Specs](#) [Documentation](#) [Application Notes](#)

Product Specifications

Availability	Global
Operating Force (OF)	0,330 N m [2.90 in lb]
Pretravel (PT)	26°
Overtravel (OT)	59°
Differential Travel (DT)	12° max.
Product Type	EN50041/47 Global Limit Switch
Actuator	Side Rotary
Lever Type	-- No Lever --
Circuitry	1NC 1NO SPDT Snap Action
Ampere Rating	10 A (Thermal)
Supply Voltage	600 Vac and 250 Vdc max.
Housing Material	Zinc Die-Cast
Termination Type	0.5 in - 14NPT Conduit
Housing Type	EN 50041+ Plug-in
Series Name	GLS DIN
Shock	50 g per IEC 68-2-27c (w/o Actuator)
Vibration	10 g per IEC 68-2-6 (w/o Actuator)
Sealing	IP67; NEMA 1, 4, 12, 13
UL File #	E37138 & E157416
Expected Mechanical Life	15 Million
Operating Temperature	-25 °C to 85 °C [-13 °F to 185 °F]
Agency Approvals and Standards	UL, CE, CSA, IEC 947-5-1, EN60947-5-1, UL508
UNSPSC Code	302119
UNSPSC Commodity	302119 Switches and controls and relays
Sealed	Industrial
Operating Position (OP)	26°

contacts

Customer Service
 Technical Support
 Global Sales & Service
 View Site Demo
 Site Comments?

meet dr. larry

VIDEO - Dr. Larry Goldstein explains our newest and best technologies.

Meet Dr. Larry



my links

[Login to iCOM](#)
[Login to Rep/AD Portal](#)
[Login to Digital University](#)

News Center

HONEYWELL INTRODUCES TRUSTABILITY® NSC SERIES, UNCOMPENSATED / UNAMPLIFIED BOARD MOUNT PRESSURE SENSORS

HONEYWELL EXPANDS ITS LIMITLESS™ PLATFORM WITH THE LAUNCH OF ITS GLOBALLY AVAILABLE INDUSTRIAL WIRELESS RECEIVER

HONEYWELL EXTENDS ITS TRUSTABILITY® PRESSURE SENSOR PRODUCT LINE WITH A SINGLE SIDE LIQUID MEDIA OPTION

MICRO SWITCH
Anniversary site

[Terms & Conditions](#) | [Privacy Statement](#) | [Site Map](#)