



[> PN Search](#)

Millipacs™
HM2P08PDN151N9

[> Communications Data & Consumer division](#)
FCI brings you more
[✉ Contact our sales/technical support](#)
[✉ Sample request](#)
[€ Price request](#)
[📊 Check distributor stock](#)
[Home page](#)
[Product quick search](#)

P/N Search

FCI Competitor

GO

RoHS/LF P/N
Search

Product type search

Alphabetical list

Connection type

Markets / Applications

[Product finder](#)
[Literature](#)
[Services](#)
[Contact us](#)
[Registered users](#)
[Forgot password ?](#)
[Register now](#)
[Download](#)
[> Customer Drawing](#)
[> Product Specification](#)
[> 3D Model](#)
[Mating half](#)

Not Available

[Alternative parts](#)

Not Available

[Application tooling](#)
[www.foehrenbach.be](#)
[Americas](#)
[Asia Pacific](#)

Features Selected

Product Type Header

Contact Finish Level 2 (0.8 microns Au)

Series Module type B

Gender Header

Orientation Straight

#ofRows 5

of Positions 125

Tail Lengths Short Tails (3,7mm)

PCB Mounting Press-fit

Shielded? yes

Other Properties

Housing Material High Temperature Thermoplastic (UL94 V-0)

Contact Base Material Phosphor Bronze

Operating Temperature -55°C to +125°C

Signal Contact Current Rating 1.5 A @ 20°C, 1.0 A @ 70°C

Signal Contact Test Voltage (Fully Loaded) 750 Vrms

Signal Contact, Contact Resistance 20 milli ohms max

Signal Contact Insulation Resistance 10000 mega ohms min

Signal Contact Mating Force 0.75 N max per contact pair

Signal Contact Withdrawal Force 0.15 N min per contact pair

Signal Contact Hertz Stress 200 Kpsi min

Contact Levels Refer to Customer Drawing

Signal Contact Normal Force 0.75 N min (EOL)

Approvals and Certification UL and CSA Certified