

Silicon Power Rectifier Assemblies Plate Heatsink

- Complete bridge with heatsinks – no assembly required
- Available in single or three phase bridge assemblies
- Available with bracket or bolt mounting
- Can be supplied with either DO-4 or DO-5 rectifiers
- Blocking voltages to 1600V

Silicon Power Rectifier Plate Heatsink Assembly Coding System

K 34 20 B I E B I S								
Size of Heat Sink	Type of Diode	Peak Reverse Voltage	Type of Circuit	Number of Diodes in Series	Type of Finish	Type of Mounting	Number of Diodes in Parallel	Special Feature
E-2"x2"	20	20-200	Single Phase	Per leg	E-Commercial T-High Humidity salt spray F-Fungicide	B-Stud with brackets or insulating board with mounting bracket N-Stud with no bracket C-Bolt BC-Bolt mounting with one bracket	Per leg	Surge Suppressor
K-3"x3"	21		H-Half Wave					
G-5"x5"			C-Center Tap Positive					
N-7"x7"			N-Center Tap Negative					
	34	30-300	D-Doubler					
	37		B-Bridge					
	42		M-Open Bridge					
	43	40-400						
	504	50-500						
		60-600						
		80-800	Three Phase					
			Z-Bridge					
			X-Center Tap					
			Y-Half Wave DC Positive					
			Q-Half Wave DC Negative					
			W-Double Wave					
			V-Open Bridge					

Microsemi Corp.
Colorado