



SIRIUS SOFT STARTER, VALUES WITH 400 V, 40 DEG., STANDARD: 162A, 90KW, INSIDE-DELTA
CIRCUIT 3: 281A, 160KW, 200-460 V AC, 230 V AC,
CAGE CLAMP TERMINALS

| General technical data | | |
|--|--|--------------|
| product brandname | | SIRIUS |
| <ul style="list-style-type: none">Product equipment Integrated bypass contact system | | Yes |
| <ul style="list-style-type: none">Product feature Thyristors | | Yes |
| Product function | | |
| <ul style="list-style-type: none">Intrinsic device protection | | Yes |
| <ul style="list-style-type: none">motor overload protection | | Yes |
| <ul style="list-style-type: none">Evaluation of thermistor motor protection | | Yes |
| <ul style="list-style-type: none">External reset | | Yes |
| <ul style="list-style-type: none">Adjustable current limitation | | Yes |
| <ul style="list-style-type: none">Inside-delta circuit | | Yes |
| Product component Motor brake output | | Yes |
| Equipment marking acc. to DIN EN 61346-2 | | Q |
| Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750 | | G |
| Power Electronics | | |
| Product designation | | Soft starter |

| | | |
|---|----|-------------|
| Operating current | | |
| • at 40 °C rated value | A | 162 |
| • at 50 °C rated value | A | 145 |
| • at 60 °C rated value | A | 125 |
| Operating current for three-phase motors at inside-delta circuit | | |
| • at 40 °C rated value | A | 281 |
| • at 50 °C rated value | A | 251 |
| • at 60 °C rated value | A | 217 |
| Mechanical power output for three-phase motors | | |
| • at 230 V | | |
| — at standard circuit at 40 °C rated value | W | 45 000 |
| — at inside-delta circuit at 40 °C rated value | W | 90 000 |
| • at 400 V | | |
| — at standard circuit at 40 °C rated value | W | 90 000 |
| — at inside-delta circuit at 40 °C rated value | W | 160 000 |
| Yielded mechanical performance [hp] for three-phase AC motor at 200/208 V at standard circuit at 50 °C rated value | hp | 40 |
| Operating frequency rated value | Hz | 50 ... 60 |
| Relative negative tolerance of the operating frequency | % | -10 |
| Relative positive tolerance of the operating frequency | % | 10 |
| Operating voltage at standard circuit rated value | V | 200 ... 460 |
| Relative negative tolerance of the operating voltage at standard circuit | % | -15 |
| Relative positive tolerance of the operating voltage at standard circuit | % | 10 |
| Operating voltage at inside-delta circuit rated value | V | 200 ... 460 |
| Relative negative tolerance of the operating voltage at inside-delta circuit | % | -15 |
| Relative positive tolerance of the operating voltage at inside-delta circuit | % | 10 |
| Minimum load [% of IM] | % | 8 |
| Adjustable motor current for motor overload protection minimum rated value | A | 32 |
| Continuous operating current [% of I_e] at 40 °C | % | 115 |
| Power loss [W] at operating current at 40 °C during operation typical | W | 95 |
| Control electronics | | |
| Type of voltage of the control supply voltage | | AC |
| Control supply voltage frequency 1 rated value | Hz | 50 |
| Control supply voltage frequency 2 rated value | Hz | 60 |

| | | |
|--|---|---------|
| Relative negative tolerance of the control supply voltage frequency | % | -10 |
| Relative positive tolerance of the control supply voltage frequency | % | 10 |
| Control supply voltage 1 at AC | | |
| • at 50 Hz rated value | V | 230 |
| • at 60 Hz rated value | V | 230 |
| Relative negative tolerance of the control supply voltage at AC at 60 Hz | % | -15 |
| Relative positive tolerance of the control supply voltage at AC at 60 Hz | % | 10 |
| Display version for fault signal | | Display |

Mechanical data

| | | |
|---|----|--|
| Width | mm | 170 |
| Height | mm | 200 |
| Depth | mm | 270 |
| Mounting type | | screw fixing |
| Mounting position | | with vertical mounting surface +/-90° rotatable, with vertical mounting surface +/- 22.5° tiltable to the front and back |
| Required spacing with side-by-side mounting | | |
| • upwards | mm | 100 |
| • at the side | mm | 5 |
| • downwards | mm | 75 |
| Installation altitude at height above sea level | m | 5 000 |
| Wire length maximum | m | 500 |
| Number of poles for main current circuit | | 3 |

Connections/Terminals

| | | |
|--|--|---------------------------|
| Type of electrical connection | | |
| • for main current circuit | | busbar connection |
| • for auxiliary and control current circuit | | spring-loaded terminals |
| Number of NC contacts for auxiliary contacts | | 0 |
| Number of NO contacts for auxiliary contacts | | 3 |
| Number of CO contacts for auxiliary contacts | | 1 |
| Type of connectable conductor cross-sections for main contacts for box terminal using the front clamping point | | |
| • finely stranded with core end processing | | 16 ... 70 mm ² |
| • finely stranded without core end processing | | 16 ... 70 mm ² |
| • stranded | | 16 ... 70 mm ² |
| Type of connectable conductor cross-sections for main contacts for box terminal using the back clamping point | | |

| | | |
|--|--|--|
| <ul style="list-style-type: none"> • finely stranded with core end processing • finely stranded without core end processing • stranded | | 16 ... 70 mm ² 16 ... 70 mm ² 16 ... 70 mm ² |
| Type of connectable conductor cross-sections for main contacts for box terminal using both clamping points <ul style="list-style-type: none"> • finely stranded with core end processing • finely stranded without core end processing • stranded | | max. 1x 50 mm ² , 1x 70 mm ² max. 1x 50 mm ² , 1x 70 mm ² max. 2x 70 mm ² |
| Type of connectable conductor cross-sections at AWG conductors for main contacts for box terminal <ul style="list-style-type: none"> • using the back clamping point • using the front clamping point • using both clamping points | | 6 ... 2/0 6 ... 2/0 max. 2x 1/0 |
| Type of connectable conductor cross-sections for DIN cable lug for main contacts <ul style="list-style-type: none"> • finely stranded • stranded | | 16 ... 95 mm ² 25 ... 120 mm ² |
| Type of connectable conductor cross-sections for auxiliary contacts <ul style="list-style-type: none"> • solid • finely stranded with core end processing | | 2x (0.25 ... 1.5 mm ²) 2x (0.25 ... 1.5 mm ²) |
| Type of connectable conductor cross-sections at AWG conductors <ul style="list-style-type: none"> • for main contacts • for auxiliary contacts | | 4 ... 250 kcmil 2x (24 ... 16) |

Ambient conditions

| | | |
|--|----|-------------|
| Ambient temperature | | |
| <ul style="list-style-type: none"> • during operation • during storage | °C | 60 |
| | °C | -25 ... +80 |
| Derating temperature | °C | 40 |
| Protection class IP | | IP00 |

Certificates/approvals

| | | |
|--------------------------|-----|---------------------------|
| General Product Approval | EMC | Declaration of Conformity |
|--------------------------|-----|---------------------------|



| | |
|-------------------|-------------------|
| Test Certificates | Shipping Approval |
|-------------------|-------------------|

[Typprüfbescheinigung/Werkszeugnis](#)

[spezielle Prüfbescheinigungen](#)



| | |
|-------------------|-------|
| Shipping Approval | other |
|-------------------|-------|



[Umweltbestätigung](#)

[Bestätigungen](#)

UL/CSA ratings

Yielded mechanical performance [hp] for three-phase AC motor

- at 200/208 V

— at inside-delta circuit at 50 °C rated value

hp

75

- at 220/230 V

— at standard circuit at 50 °C rated value

hp

50

— at inside-delta circuit at 50 °C rated value

hp

100

- at 460/480 V

— at standard circuit at 50 °C rated value

hp

100

— at inside-delta circuit at 50 °C rated value

hp

200

Contact rating of auxiliary contacts according to UL

B300 / R300

Further information

Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW4436-2BC44>

Cax online generator




<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW4436-2BC44>


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW4436-2BC44>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW4436-2BC44&lang=en





last modified:

02/27/2017