

SUMMARY

Wires

Low	0
High	0
Coax	0
Triax	0
Quad	0
Fiber	0
Fluidic	1



Download

[Request a quote](#)

[Catalog](#)

Series	C
Termination type	
IP rating	50
Cable Ø	0.00 - 0.00 mm
Matching parts	xxx

TECHNICAL DETAILS

Mechanics

Shell Style/Model	CA*: Straight plug with cable collet
Keying	
Housing Material	PSU (Polysulfone), black
Cable Fixing	∅ 0 - 0 mm
Variant	

Performance

Configuration	CAB.015 : 1 Fluidic, 10 Low V.
Insulator	
Rated Current	5 Amps

Specifications


Test voltage (kV rms) Contact-contact:	1.15
Air clearance min. (mm) or Creepage distance min. (mm):	0.9

Others

IP Rating:	50
------------	----

DRAWINGS

Draws



Dimensions

	A	L
mm.	18	53
in.	0,71	2,09

RECOMMENDED BY LEMO

Tools

- Crimp Tool: DPC.91.701.V
- Crimp settings: AWG/Selector = 22-24-26/6-5-5
- Positionner: DCE.91.072.BVC
- Extractor: DCF.91.070.2LT
- Replacement contact: FGG.2B.555.ZZC

Cables