



RECTANGULAR POWER CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**



TE CONNECTIVITY (TE)

HONHUS UMNL V0 9-P

MATE-N-LOK | Universal MATE-N-LOK

927231-3

TE Internal Number: 927231-3

Always EU RoHS/ELV Compliant

Product Type **Housing**

Housing Type **Receptacle**

Connector System **Wire-to-Panel, Wire-to-Wire**

Applies To **Panel, Wire/Cable**

Number of Positions **9**

Product Drawings

UMNL 9 WAY CAP HOUSING

PDF
English

CAD Files

3D PDF

PDF
3D

Customer View Model

2D_DXF.ZIP
English

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Product Specifications

Product Specification

Universal MATE-N-LOK Connector

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Product Type

Housing

Housing Type

Receptacle

Contact Type

Pin or Socket

Configuration Features

Number of Positions

9

| | | |
|----------------------------|------------------------------|--------------------------------|
| | Centerline | 6.35 mm [.25 in] |
| | Number of Rows | 3 |
| | Row-to-Row Spacing | 6.35 mm [.25 in] |
| | Contact Layout | Matrix |
| | Multiple Contact Types | Without |
| Electrical Characteristics | Operating Voltage (VAC) | 600 |
| | Operating Voltage (VDC) | 600 |
| Contact Features | Contact Retention | Without |
| Mechanical Attachment | Panel Mount Retention Type | Patch & Tabs |
| | Panel Mount Retention | With |
| | Assembly Integration Feature | Without |
| Housing Features | UL Flammability Rating | UL 94V-0 |
| | Housing Color | Natural |
| | Housing Material | PA 66 |
| Dimensions | Panel Thickness | .76 – 2.29 mm [.03 – .09 in] |
| Usage Conditions | Sealed Condition | Not Sealed |
| Operation/Application | Connector System | Wire-to-Panel, Wire-to-Wire |
| | Applies To | Panel, Wire/Cable |
| | Operating Temperature | -55 – 125 °C [-67 – 257 °F] |
| Industry Standards | Glow Wire Rating | Standard Part - Not Glow Wire |
| | UL Rating | Recognized |
| | VDE Tested | Yes |
| | CSA Rating | Certified |
| | CSA File Number | LR7189 |
| | Agency/Standard Number | E28476 |
| | Agency/Standard | CSA, UL |
| Packaging Features | Packaging Method | Bag/Box |
| | Packaging Quantity | 1000 |

Other













For Use With

Universal MATE-N-LOK Plug or Socket Housing

Product Compliance

[Statement of Compliance](#)
PDF[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

| POWER CONTACTS | PCB CONNECTOR SHROUDS | RECTANGULAR POWER CONNECTORS | PCB D-SUB CONNECTORS |
|--|--|--|--|
|  |  |  |  |
| UNIVERSAL M-N-L SOCKET 926895-1 | 096 EURO SHROUD 533236-4 | 12P UNIV.CAP HSG. 926681-3 | 25P.HDP20 REC.ASSY 5-106507-2 |
|  Save to List  Find Similar Products |  Save to List  Find Similar Products |  Save to List  Find Similar Products |  Save to List  Find Similar Products |