


Slot-type Photomicrosensor with Cable EE-SPX-W

Photomicrosensor with built-in amplifier and attached cable reduces external light interference.

- Light modulation effectively reduces external light interference.
- Wide operation voltage range: 5 to 24 VDC
- Easy operation monitoring with bright light indicator.



Refer to *Precautions* on page 49.



Ordering Information

 Infrared light




Appearance	Sensing method	Sensing distance (slot width)	Output type	Output configuration	Cable length	Model
	Through-beam type	 3.6 mm	NPN output	Dark-ON	1 m	EE-SPX302-W2A
		 3.6 mm		Light-ON		EE-SPX402-W2A
		 3.6 mm		Dark-ON		EE-SPX304-W2A
		 3.6 mm		Light-ON		EE-SPX404-W2A
		 5.0 mm		Dark-ON		EE-SPX306-W2A
		 5.0 mm		Light-ON		EE-SPX406-W2A
		 5.0 mm		Dark-ON		EE-SPX305-W2A (See note.)
		 5.0 mm		Light-ON		EE-SPX405-W2A (See note.)

Note: The EE-SPX305-W2A/SPX405-W2A are not CE certified due to their internal structures. All other Photomicrosensors are CE certified.

Ratings/Characteristics

Item	Models	EE-SPX302-W2A, EE-SPX402-W2A EE-SPX304-W2A, EE-SPX404-W2A EE-SPX306-W2A, EE-SPX406-W2A	EE-SPX305-W2A EE-SPX405-W2A
Sensing distance	3.6 mm (slot width)	5 mm (slot width)	
Sensing object	Opaque: 1 × 0.5 mm min.	Opaque: 2 × 0.8 mm min.	
Differential distance	0.05 mm max.		
Light source	GaAs infrared LED (pulse lighting) with a peak wavelength of 940 nm		
Indicator *1	Light indicator (red)		
Supply voltage	5 to 24 VDC ±10%, ripple (p-p): 5% max.		
Current consumption	Average: 15 mA max.; Peak: 50 mA max.		
Control output	NPN voltage output: Load power supply voltage: 5 to 24 VDC Load current: 80 mA max. 80 mA load current with a residual voltage of 1.0 V max. 10 mA load current with a residual voltage of 0.4 V max.		
Response frequency *2	500 Hz min.		
Ambient illumination	3,000 lx max. with incandescent light or sunlight on the surface of the receiver		
Ambient temperature	Operating: -10 to +55°C Storage: -25 to +65°C		
Ambient humidity	Operating: 5% to 85% Storage: 5% to 95%		
Vibration resistance	Destruction: 10 to 55 Hz, 1.5-mm double amplitude for 2 h each in X, Y, and Z directions		
Shock resistance	Destruction: 500 m/s ² for 3 times each in X, Y, and Z directions		
Enclosure rating	IEC IP50		
Connecting method	Pre-wired (standard cable length: 1 m)		
Weight	18.5 g		
Material	Case Holder	Polycarbonate	

- 1. The indicator is a GaP red LED (peak emission wavelength: 700 nm).
- 2. The response frequency was measured by detecting the following rotating disk.



I/O Circuits

NPN Output



Model	Output configuration	Timing charts	Output circuit
EE-SPX402-W2A EE-SPX404-W2A EE-SPX405-W2A EE-SPX406-W2A	Light-ON	<p>Incident Interrupted</p> <p>Light indicator (red) ON OFF</p> <p>Output transistor ON OFF</p> <p>Load 1 (relay) Operates Releases</p> <p>Load 2 H L</p>	<p>* Voltage output (when the sensor is connected to a transistor circuit)</p>
EE-SPX302-W2A EE-SPX304-W2A EE-SPX305-W2A EE-SPX306-W2A	Dark-ON	<p>Incident Interrupted</p> <p>Light indicator (red) ON OFF</p> <p>Output transistor ON OFF</p> <p>Load 1 (relay) Operates Releases</p> <p>Load 2 H L</p>	<p>* Voltage output (when the sensor is connected to a transistor circuit)</p>

Engineering Data

Sensing Position Characteristics (Typical)



EE-SPX302-W2A
EE-SPX304-W2A
EE-SPX306-W2A

EE-SPX302-W2A
EE-SPX304-W2A
EE-SPX306-W2A



EE-SPX305-W2A

EE-SPX305-W2A



Precautions

Refer to *General Precautions* on page 23 to 28 for general precautions.

Warning

Do not use this product in sensing devices designed to provide human safety.




Precautions for Correct Use


Make sure that this product is used within the rated ambient environment conditions.

● Wiring

- When extending the cable, use an extension cable with conductors having a total cross-section area of 0.3 mm². The total cable length must be 2 m maximum.
- To use a cable length longer than 2 m, attach a capacitor with a capacitance of approximately 10 μ F to the wires as shown below. The distance between the terminal and the capacitor must be within 2 m. (Use a capacitor with a dielectric strength that is at least twice the Sensor's power supply voltage.)




Dimensions (Unit: mm)

EE-SPX302-W2A
EE-SPX402-W2A


* Vinyl-insulated round cable of 3.5 dia., 3 cores,
(0.14 mm² with 1.0-dia. insulator); Standard length: 1 m

Note: The lug is used to prevent turning and to indicate the optical axis.
When installing, make a fixed hole of 2.1 to 2.3 mm dia.



EE-SPX304-W2A
EE-SPX404-W2A

* Vinyl-insulated round cable of 3.5 dia., 3 cores,
(0.14 mm² with 1.0-dia. insulator); Standard length: 1 m

Note: The lug is used to prevent turning and to indicate the optical axis.
When installing, make a fixed hole of 2.1 to 2.3 mm dia.

EE-SPX306-W2A
EE-SPX406-W2A

* Vinyl-insulated round cable of 3.5 dia., 3 cores,
(0.14 mm² with 1.0-dia. insulator); Standard length: 1 m

EE-SPX305-W2A
EE-SPX405-W2A

* Vinyl-insulated round cable of 3.5 dia., 3 cores,
(0.14 mm² with 1.0-dia. insulator); Standard length: 1 m

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com