

Standard Multilayer Ceramic Capacitors (Temperature compensating type)

EMK042CG080DD-W



■ Features

- Item Summary
8pF $\pm$ 0.5pF, 16V,
C0G/CG, 01005/0402 (EIA/JIS)
- Lifecycle Stage
Mass Production
- Standard packaging quantity (minimum)
Taping Embossed 40000pcs

■ Products characteristics table

Capacitance	8 pF $\pm$ 0.5pF
Case Size (EIA/JIS)	01005/0402
Rated Voltage	16 V
Q (min)	560 at 1MHz
Temperature Characteristic (EIA)	C0G
Operating Temp. Range (EIA)	-55 to +125 °C
Temperature Characteristic (JIS)	CG
Operating Temp. Range (JIS)	-55 to +125 °C
Temperature Characteristic	0 $\pm$ 30 ppm/°C
High Temperature Loading (% Rated Voltage)	200 %
Insulation Resistance (min)	10 G Ω
RoHS2 Compliance (10 subst.)	Yes
REACH Compliance (168 subst.)	Yes
Soldering	Reflow





■ External Dimensions

Dimension L	0.4 $\pm$ 0.02 mm
Dimension W	0.2 $\pm$ 0.02 mm
Dimension T	0.2 $\pm$ 0.02 mm
Dimension e	0.10 $\pm$ 0.03 mm

2016.10.01

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.
 Before making final selection, please check product specification.

○EMK042CG080DD

16V 0402 CG/C0G 8pF +/- 0.5pF t=0.22mmMAX16V 01005 CG/C0G 8pF +/- 0.5pF t=0.009inchMAX

部品特性は設置環境、測定条件等により変化する場合があります。本データをご使用される際は実際の製品特性に対する参考データとしてご利用ください。また、本データは予告無く追加・削除及び変更を行う場合があります。ご注文の際は、納入仕様書のご確認をお願いします。

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.

TAIYO YUDEN reserves the right to make change to the data at any time without notice.

Before making final selection, please check product specification.