



Distributed by:

**JAMECO**<sup>®</sup>  
ELECTRONICS

**www.Jameco.com ♦ 1-800-831-4242**

The content and copyrights of the attached  
material are the property of its owner.

Jameco Part Number 947261

**75A, 80V, 0.010 Ohm, N-Channel,  
 UltraFET® Power MOSFET**
**Packaging**

**Symbol**

**Features**

- Ultra Low On-Resistance
  - $r_{DS(ON)} = 0.010\Omega$ ,  $V_{GS} = 10V$
- Simulation Models
  - Temperature Compensated PSPICE® and SABER™ Electrical Models
  - Spice and SABER Thermal Impedance Models
  - [www.fairchildsemi.com](http://www.fairchildsemi.com)
- Peak Current vs Pulse Width Curve
- UIS Rating Curve

**Ordering Information**

| PART NUMBER | PACKAGE  | BRAND  |
|-------------|----------|--------|
| HUF75545P3  | TO-220AB | 75545P |
| HUF75545S3  | TO-262AA | 75545S |
| HUF75545S3S | TO-263AB | 75545S |

NOTE: When ordering, use the entire part number. Add the suffix T to obtain the TO-263AB variant in tape and reel, e.g., HUF75545S3ST.

**Absolute Maximum Ratings**  $T_C = 25^\circ\text{C}$ , Unless Otherwise Specified

|                                                                                | HUF75545P3, HUF75545S3,<br>HUF75545S3S | UNITS              |
|--------------------------------------------------------------------------------|----------------------------------------|--------------------|
| Drain to Source Voltage (Note 1) . . . . .                                     | $V_{DSS}$                              | V                  |
| Drain to Gate Voltage ( $R_{GS} = 20k\Omega$ ) (Note 1) . . . . .              | $V_{DGR}$                              | V                  |
| Gate to Source Voltage . . . . .                                               | $V_{GS}$                               | V                  |
| Drain Current                                                                  |                                        |                    |
| Continuous ( $T_C = 25^\circ\text{C}$ , $V_{GS} = 10V$ ) (Figure 2) . . . . .  | $I_D$                                  | A                  |
| Continuous ( $T_C = 100^\circ\text{C}$ , $V_{GS} = 10V$ ) (Figure 2) . . . . . | $I_D$                                  | A                  |
| Pulsed Drain Current . . . . .                                                 | $I_{DM}$                               | Figure 4           |
| Pulsed Avalanche Rating . . . . .                                              | UIS                                    | Figure 6           |
| Power Dissipation . . . . .                                                    | $P_D$                                  | W                  |
| Derate Above $25^\circ\text{C}$ . . . . .                                      |                                        | $W/^\circ\text{C}$ |
| Operating and Storage Temperature . . . . .                                    | $T_J, T_{STG}$                         | $^\circ\text{C}$   |
| Maximum Temperature for Soldering                                              |                                        |                    |
| Leads at 0.063in (1.6mm) from Case for 10s. . . . .                            | $T_L$                                  | $^\circ\text{C}$   |
| Package Body for 10s, See Techbrief TB334. . . . .                             | $T_{pkg}$                              | $^\circ\text{C}$   |

**NOTES:**

1.  $T_J = 25^\circ\text{C}$  to  $150^\circ\text{C}$ .

**CAUTION:** Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied.

Product reliability information can be found at <http://www.fairchildsemi.com/products/discrete/reliability/index.html>

For severe environments, see our Automotive HUFA series.

All Fairchild semiconductor products are manufactured, assembled and tested under ISO9000 and QS9000 quality systems certification.

# HUF75545P3, HUF75545S3, HUF75545S3S

## Electrical Specifications $T_C = 25^\circ\text{C}$ , Unless Otherwise Specified

| PARAMETER                                        | SYMBOL              | TEST CONDITIONS                                                                                 | MIN                                                                                           | TYP    | MAX   | UNITS |    |
|--------------------------------------------------|---------------------|-------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|--------|-------|-------|----|
| OFF STATE SPECIFICATIONS                         |                     |                                                                                                 |                                                                                               |        |       |       |    |
| Drain to Source Breakdown Voltage                | BV <sub>DSS</sub>   | I <sub>D</sub> = 250μA, V <sub>GS</sub> = 0V (Figure 11)                                        | 80                                                                                            | -      | -     | V     |    |
| Zero Gate Voltage Drain Current                  | I <sub>DSS</sub>    | V <sub>DS</sub> = 75V, V <sub>GS</sub> = 0V                                                     | -                                                                                             | -      | 1     | μA    |    |
|                                                  |                     | V <sub>DS</sub> = 70V, V <sub>GS</sub> = 0V, T <sub>C</sub> = 150°C                             | -                                                                                             | -      | 250   | μA    |    |
| Gate to Source Leakage Current                   | I <sub>GSS</sub>    | V <sub>GS</sub> = ±20V                                                                          | -                                                                                             | -      | ±100  | nA    |    |
| ON STATE SPECIFICATIONS                          |                     |                                                                                                 |                                                                                               |        |       |       |    |
| Gate to Source Threshold Voltage                 | V <sub>GS(TH)</sub> | V <sub>GS</sub> = V <sub>DS</sub> , I <sub>D</sub> = 250μA (Figure 10)                          | 2                                                                                             | -      | 4     | V     |    |
| Drain to Source On Resistance                    | r <sub>DS(ON)</sub> | I <sub>D</sub> = 75A, V <sub>GS</sub> = 10V (Figure 9)                                          | -                                                                                             | 0.0082 | 0.010 | Ω     |    |
| THERMAL SPECIFICATIONS                           |                     |                                                                                                 |                                                                                               |        |       |       |    |
| Thermal Resistance Junction to Case              | R <sub>θJC</sub>    | TO-220 and TO-263                                                                               | -                                                                                             | -      | 0.55  | °C/W  |    |
| Thermal Resistance Junction to Ambient           | R <sub>θJA</sub>    |                                                                                                 | -                                                                                             | -      | 62    | °C/W  |    |
| SWITCHING SPECIFICATIONS (V <sub>GS</sub> = 10V) |                     |                                                                                                 |                                                                                               |        |       |       |    |
| Turn-On Time                                     | t <sub>ON</sub>     | V <sub>DD</sub> = 40V, I <sub>D</sub> = 75A<br>V <sub>GS</sub> = 10V,<br>R <sub>GS</sub> = 2.5Ω | -                                                                                             | -      | 210   | ns    |    |
| Turn-On Delay Time                               | t <sub>d(ON)</sub>  |                                                                                                 | -                                                                                             | 14     | -     | ns    |    |
| Rise Time                                        | t <sub>r</sub>      |                                                                                                 | -                                                                                             | 125    | -     | ns    |    |
| Turn-Off Delay Time                              | t <sub>d(OFF)</sub> |                                                                                                 | -                                                                                             | 40     | -     | ns    |    |
| Fall Time                                        | t <sub>f</sub>      |                                                                                                 | -                                                                                             | 90     | -     | ns    |    |
| Turn-Off Time                                    | t <sub>OFF</sub>    |                                                                                                 | -                                                                                             | -      | 195   | ns    |    |
| GATE CHARGE SPECIFICATIONS                       |                     |                                                                                                 |                                                                                               |        |       |       |    |
| Total Gate Charge                                | Q <sub>g(TOT)</sub> | V <sub>GS</sub> = 0V to 20V                                                                     | V <sub>DD</sub> = 40V,<br>I <sub>D</sub> = 75A,<br>I <sub>g(REF)</sub> = 1.0mA<br>(Figure 13) | -      | 195   | 235   | nC |
| Gate Charge at 10V                               | Q <sub>g(10)</sub>  | V <sub>GS</sub> = 0V to 10V                                                                     |                                                                                               | -      | 105   | 125   | nC |
| Threshold Gate Charge                            | Q <sub>g(TH)</sub>  | V <sub>GS</sub> = 0V to 2V                                                                      |                                                                                               | -      | 6.8   | 8.2   | nC |
| Gate to Source Gate Charge                       | Q <sub>gs</sub>     |                                                                                                 |                                                                                               | -      | 15    | -     | nC |
| Gate to Drain “Miller” Charge                    | Q <sub>gd</sub>     |                                                                                                 |                                                                                               | -      | 43    | -     | nC |
| CAPACITANCE SPECIFICATIONS                       |                     |                                                                                                 |                                                                                               |        |       |       |    |
| Input Capacitance                                | C <sub>ISS</sub>    | V <sub>DS</sub> = 25V, V <sub>GS</sub> = 0V,<br>f = 1MHz<br>(Figure 12)                         | -                                                                                             | 3750   | -     | pF    |    |
| Output Capacitance                               | C <sub>OSS</sub>    |                                                                                                 | -                                                                                             | 1100   | -     | pF    |    |
| Reverse Transfer Capacitance                     | C <sub>RSS</sub>    |                                                                                                 | -                                                                                             | 350    | -     | pF    |    |

## Source to Drain Diode Specifications

| PARAMETER                     | SYMBOL   | TEST CONDITIONS                                                | MIN | TYP | MAX  | UNITS |
|-------------------------------|----------|----------------------------------------------------------------|-----|-----|------|-------|
| Source to Drain Diode Voltage | $V_{SD}$ | $I_{SD} = 75\text{A}$                                          | -   | -   | 1.25 | V     |
|                               |          | $I_{SD} = 35\text{A}$                                          | -   | -   | 1.00 | V     |
| Reverse Recovery Time         | $t_{rr}$ | $I_{SD} = 75\text{A}$ , $dI_{SD}/dt = 100\text{A}/\mu\text{s}$ | -   | -   | 100  | ns    |
| Reverse Recovered Charge      | $Q_{RR}$ | $I_{SD} = 75\text{A}$ , $dI_{SD}/dt = 100\text{A}/\mu\text{s}$ | -   | -   | 300  | nC    |

# Typical Performance Curves




FIGURE 1. NORMALIZED POWER DISSIPATION vs CASE TEMPERATURE




FIGURE 2. MAXIMUM CONTINUOUS DRAIN CURRENT vs CASE TEMPERATURE




FIGURE 3. NORMALIZED MAXIMUM TRANSIENT THERMAL IMPEDANCE




FIGURE 4. PEAK CURRENT CAPABILITY

# Typical Performance Curves (Continued)





FIGURE 5. FORWARD BIAS SAFE OPERATING AREA



NOTE: Refer to Fairchild Application Notes AN9321 and AN9322.

FIGURE 6. UNCLAMPED INDUCTIVE SWITCHING CAPABILITY




FIGURE 7. TRANSFER CHARACTERISTICS




FIGURE 8. SATURATION CHARACTERISTICS




FIGURE 9. NORMALIZED DRAIN TO SOURCE ON RESISTANCE vs JUNCTION TEMPERATURE




FIGURE 10. NORMALIZED GATE THRESHOLD VOLTAGE vs JUNCTION TEMPERATURE

Typical Performance Curves (Continued)




FIGURE 11. NORMALIZED DRAIN TO SOURCE BREAKDOWN VOLTAGE vs JUNCTION TEMPERATURE





FIGURE 12. CAPACITANCE vs DRAIN TO SOURCE VOLTAGE



NOTE: Refer to Fairchild Application Notes AN7254 and AN7260.

FIGURE 13. GATE CHARGE WAVEFORMS FOR CONSTANT GATE CURRENT

## Test Circuits and Waveforms




FIGURE 14. UNCLAMPED ENERGY TEST CIRCUIT




FIGURE 15. UNCLAMPED ENERGY WAVEFORMS




FIGURE 16. GATE CHARGE TEST CIRCUIT




FIGURE 17. GATE CHARGE WAVEFORMS




FIGURE 18. SWITCHING TIME TEST CIRCUIT




FIGURE 19. SWITCHING TIME WAVEFORM

## PSPICE Electrical Model

.SUBCKT HUF75545 2 1 3 ; rev 21 May 1999

CA 12 8 5.4e-9  
CB 15 14 5.3e-9  
CIN 6 8 3.4e-9

DBODY 7 5 DBODYMOD  
DBREAK 5 11 DBREAKMOD  
DPLCAP 10 5 DPLCAPMOD

EBREAK 11 7 17 18 87.4  
EDS 14 8 5 8 1  
EGS 13 8 6 8 1  
ESG 6 10 6 8 1  
EVTHRES 6 21 19 8 1  
EVTEMP 20 6 18 22 1

IT 8 17 1

LDRAIN 2 5 1.0e-9  
LGATE 1 9 5.1e-9  
LSOURCE 3 7 4.4e-9

MMED 16 6 8 8 MMEDMOD  
MSTRO 16 6 8 8 MSTROMOD  
MWEAK 16 21 8 8 MWEAKMOD

RBREAK 17 18 RBREAKMOD 1  
RDRAIN 50 16 RDRAINMOD 4.80e-3  
RGATE 9 20 0.87  
RLDRAIN 2 5 10  
RLGATE 1 9 51  
RLSOURCE 3 7 44  
RSLC1 5 51 RSLCMOD 1e-6  
RSLC2 5 50 1e3  
RSOURCE 8 7 RSOURCEMOD 1.6e-3  
RVTHRES 22 8 RVTHRESMOD 1  
RVTEMP 18 19 RVTEMPMOD 1

S1A 6 12 13 8 S1AMOD  
S1B 13 12 13 8 S1BMOD  
S2A 6 15 14 13 S2AMOD  
S2B 13 15 14 13 S2BMOD

VBAT 22 19 DC 1


ESLC 51 50 VALUE={(V(5,51)/ABS(V(5,51)))\*(PWR(V(5,51)/(1e-6\*320),3))}

.MODEL DBODYMOD D (IS = 3.6e-12 RS = 2.1e-3 TRS1 = 1.5e-3 TRS2 = 5.1e-6 CJO = 4.6e-9 TT = 3.3e-8 M = 0.55)  
.MODEL DBREAKMOD D (RS = 2.3e-1 TRS1 = 0 TRS2 = -1.8e-5)  
.MODEL DPLCAPMOD D (CJO = 4.8e-9 IS = 1e-30 N = 10 VJ = 1 M = 0.8)  
.MODEL MMEDMOD NMOS (VTO = 3.04 KP = 6 IS = 1e-30 N = 10 TOX = 1 L = 1u W = 1u RG = 0.87)  
.MODEL MSTROMOD NMOS (VTO = 3.5 KP = 105 IS = 1e-30 N = 10 TOX = 1 L = 1u W = 1u)  
.MODEL MWEAKMOD NMOS (VTO = 2.65 KP = 0.12 IS = 1e-30 N = 10 TOX = 1 L = 1u W = 1u RG = 8.7 )  
.MODEL RBREAKMOD RES (TC1 = 1.3e-3 TC2 = -1e-6)  
.MODEL RDRAINMOD RES (TC1 = 9e-3 TC2 = 2.8e-5)  
.MODEL RSLCMOD RES (TC1 = 1.53e-3 TC2 = 2e-5)  
.MODEL RSOURCEMOD RES (TC1 = 1e-3 TC2 = 1e-6)  
.MODEL RVTHRESMOD RES (TC1 = -2.3e-3 TC2 = -1.2e-5)  
.MODEL RVTEMPMOD RES (TC1 = -2.9e-3 TC2 = 5e-7)

.MODEL S1AMOD VSWITCH (RON = 1e-5 ROFF = 0.1 VON = -5 VOFF = -3)  
.MODEL S1BMOD VSWITCH (RON = 1e-5 ROFF = 0.1 VON = -3 VOFF = -5)  
.MODEL S2AMOD VSWITCH (RON = 1e-5 ROFF = 0.1 VON = -1.5 VOFF = 0.5)  
.MODEL S2BMOD VSWITCH (RON = 1e-5 ROFF = 0.1 VON = 0.5 VOFF = -1.5)

.ENDS

NOTE: For further discussion of the PSPICE model, consult **A New PSPICE Sub-Circuit for the Power MOSFET Featuring Global Temperature Options**; IEEE Power Electronics Specialist Conference Records, 1991, written by William J. Hepp and C. Frank Wheatley.







## SPICE Thermal Model

REV 21 May 1999

HUF75545T

CTHERM1 th 6 6.4e-3  
CTHERM2 6 5 3.0e-2  
CTHERM3 5 4 1.4e-2  
CTHERM4 4 3 1.6e-2  
CTHERM5 3 2 5.5e-2  
CTHERM6 2 tl 1.5

RTHERM1 th 6 3.2e-3  
RTHERM2 6 5 8.1e-3  
RTHERM3 5 4 2.3e-2  
RTHERM4 4 3 1.3e-1  
RTHERM5 3 2 1.8e-1  
RTHERM6 2 tl 3.8e-2

## SABER Thermal Model


SABER thermal model HUF75545T

template thermal\_model th tl  
thermal\_c th, tl

```
{
ctherm.ctherm1 th 6 = 6.4e-3
ctherm.ctherm2 6 5 = 3.0e-2
ctherm.ctherm3 5 4 = 1.4e-2
ctherm.ctherm4 4 3 = 1.6e-2
ctherm.ctherm5 3 2 = 5.5e-2
ctherm.ctherm6 2 tl = 1.5

```

```
rtherm.rtherm1 th 6 = 3.2e-3
rtherm.rtherm2 6 5 = 8.1e-3
rtherm.rtherm3 5 4 = 2.3e-2
rtherm.rtherm4 4 3 = 1.3e-1
rtherm.rtherm5 3 2 = 1.8e-1
rtherm.rtherm6 2 tl = 3.8e-2
}
```



## TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

|                                      |                     |                    |                     |                 |
|--------------------------------------|---------------------|--------------------|---------------------|-----------------|
| ACE <sup>x</sup> ™                   | FACT™               | ImpliedDisconnect™ | PACMAN™             | SPM™            |
| ActiveArray™                         | FACT Quiet Series™  | ISOPLANAR™         | POP™                | Stealth™        |
| Bottomless™                          | FAST®               | LittleFET™         | Power247™           | SuperSOT™-3     |
| CoolFET™                             | FAST <sub>r</sub> ™ | MicroFET™          | PowerTrench®        | SuperSOT™-6     |
| CROSSVOLT™                           | FRFET™              | MicroPak™          | QFET™               | SuperSOT™-8     |
| DOVE™                                | GlobalOptoisolator™ | MICROWIRE™         | QS™                 | SyncFET™        |
| EcoSPARK™                            | GTO™                | MSX™               | QT Optoelectronics™ | TinyLogic™      |
| E <sup>2</sup> CMOS™                 | HiSeC™              | MSXPro™            | Quiet Series™       | TruTranslation™ |
| EnSigna™                             | I <sup>2</sup> C™   | OCX™               | RapidConfigure™     | UHC™            |
| Across the board. Around the world.™ |                     | OCXPro™            | RapidConnect™       | UltraFET®       |
| The Power Franchise™                 |                     | OPTOLOGIC®         | SILENT SWITCHER®    | VCX™            |
| Programmable Active Droop™           |                     | OPTOPLANAR™        | SMART START™        |                 |

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

| Datasheet Identification | Product Status         | Definition                                                                                                                                                                                                            |
|--------------------------|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advance Information      | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.                                                                                    |
| Preliminary              | First Production       | This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| No Identification Needed | Full Production        | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.                                                       |
| Obsolete                 | Not In Production      | This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.                                                   |