


SPECIFICATION CONTROL DRAWING			55/0322
TITLE	TWO CONDUCTOR CABLE, UNSHIELDED, UNJACKETED, OUTER SPACE, 600 VOLT	Date 11-3-08	Revision C
This specification sheet forms a part of the latest issue of Raychem Specification 55/.			

COMPONENT WIRES - 55/0312



CABLE CONSTRUCTION DETAILS				
PART NUMBER <u>1/</u>	CONDUCTOR SIZE (AWG)	OUTSIDE DIAMETER (in.)		MAXIMUM WEIGHT (lbs/1000 ft.)
		NOMINAL	MAXIMUM	
55/0322-28-*	28	.047	.050	1.62
55/0322-26-*	26	.055	.058	2.39
55/0322-24-*	24	.064	.067	3.58
55/0322-22-*	22	.078	.081	5.40
55/0322-20-*	20	.099	.102	8.57
55/0322-18-*	18	.118	.121	13.14
55/0322-16-*	16	.133	.136	16.71
55/0322-14-*	14	.162	.166	25.73
55/0322-12-*	12	.200	.204	39.67

CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 200°C
Maximum continuous conductor temperature
VOLTAGE RATING: 600 volts (rms) at sea level
INSULATION FLAWS:
Spark Test, 1.5 kV (rms) (28 - 24 AWG)
3.0 kV (rms) (22 AWG and larger)
Impulse Dielectric Test, 6.0 kV (peak)

PART NUMBER:
The "*" in the part numbers above shall be replaced by color code designators with a slash separating the component wire colors.
1/ Example: AWG 22, black and brown component wires:
55/0322-22-0/1

NOTE: Nominal values are for information only.
Nominal values are not requirements.

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.			
1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "Axxx".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.			
Page 1 of 1	The TE logo, Tyco Electronics, and Raychem are trademarks.		 Raychem Wire & Cable 501 Oakside Avenue Redwood City, CA 94063-3800 Phone: 1-800-227-8816 Fax: 1-650-361-6297
	DIMENSIONS ARE IN INCHES, AND UNLESS OTHERWISE DESIGNATED ARE NOMINAL		
	THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity:

[55/0322-22-6/9CS2725](#) [55/0322-22-6/9CS2794](#) [55/0322-20-6/9CS2725](#) [55/0322-20-6/9CS2794](#) [55/0322-22-0/9](#)
[55/0322-20-6/9CS3329](#) [55/0322-22-9/96](#) [55/0322-14-6/9CS3329](#) [55/0322-12-6/9CS2725](#) [55/0322-24-0/9](#) [55/0322-](#)
[18-6/9CS2725](#) [55/0322-20-2/9](#) [55/0322-22-9/92](#) [55/0322-22-9/96CS2787](#) [55/0322-14-6/9CS2725](#) [55/0322-16-](#)
[6/9CS3329](#) [55/0322-12-6/9CS3329](#) [55/0322-16-6/9CS2725](#) [55/0322-22-9/90](#) [55/0322-24-9/96](#) [55/0322-26-9/96](#)
[55/0322-12-6/9CS2794](#) [55/0322-22-6/9CS3329](#)