

Filter Inductors High Current, Radial Leaded



ELECTRICAL SPECIFICATIONS

Inductance: Measured at 1.0 V with no DC current

Dielectric: 2500 V_{RMS} between winding and 0.250" [6.35 mm] of insulating covering edge (with optional insulating covering)

Current Rating: Maximum continuous operating current based on a + 50 °C temperature rise

Operating Temperature: - 55 °C to + 130 °C (no load)
- 55 °C to + 80 °C (at full rated current)

FEATURES

- Printed circuit mounting
- Wide range of inductance and current ratings
- Pre-tinned leads
- Optional polyolefin tubing and printing available at additional cost
- Compliant to RoHS directive 2002/95/EC





RoHS
COMPLIANT

MECHANICAL SPECIFICATIONS

Terminals: Extensions of winding wire, solder coated to within 0.063" [1.60 mm] of body

Mounting: Center hole for mechanical mounting. Insulated bushings recommended for center hole mounting

DIMENSIONS in inches [millimeters]

							
MODEL	A (Max.)	B (Max.)	D (Min.)				
IHB-1	0.660 [16.76]	0.840 [21.34]	0.115 [2.92]				
IHB-2	0.825 [20.96]	0.840 [21.34]	0.115 [2.92]				
IHB-3	1.100 [27.94]	0.840 [21.34]	0.115 [2.92]				
IHB-4	1.600 [40.64]	1.030 [26.16]	0.175 [4.45]				
IHB-5	1.600 [40.64]	1.450 [36.83]	0.175 [4.45]				
IHB-6	2.000 [50.80]	1.500 [38.10]	0.240 [6.10]				

*E varies between components. See individual model specifications for details. Tolerance of ± 0.035.

**F varies between components. See individual model specifications for details.

STANDARD ELECTRICAL SPECIFICATIONS

IND. at 1 kHz (μH)	TOL.	DCR MAX. (Ω)	RATED CURRENT (A)	APPROX. LEAD "E" SPACING	MAXIMUM LEAD "F" DIAMETER	IND. at 1 kHz (μH)	TOL.	DCR MAX. (Ω)	RATED CURRENT (A)	APPROX. LEAD "E" SPACING	MAXIMUM LEAD "F" DIAMETER
MODEL IHB-1											
1.0	± 20 %	0.003	9.0	0.550 [13.97]	0.045 [1.15]	27.0	± 10 %	0.030	4.5	0.500 [12.70]	0.032 [0.812]
1.2	± 20 %	0.003	9.0	0.550 [13.97]	0.045 [1.15]	33.0	± 10 %	0.040	4.0	0.475 [12.07]	0.028 [0.723]
1.5	± 20 %	0.004	9.0	0.550 [13.97]	0.045 [1.15]	39.0	± 10 %	0.046	4.0	0.475 [12.07]	0.028 [0.723]
1.8	± 20 %	0.004	9.0	0.550 [13.97]	0.045 [1.15]	47.0	± 10 %	0.062	2.8	0.470 [11.94]	0.025 [0.644]
2.2	± 20 %	0.005	9.0	0.550 [13.97]	0.045 [1.15]	56.0	± 10 %	0.069	2.8	0.470 [11.94]	0.025 [0.644]
2.7	± 20 %	0.005	9.0	0.550 [13.97]	0.045 [1.15]	68.0	± 10 %	0.077	2.8	0.500 [12.70]	0.025 [0.644]
3.3	± 20 %	0.005	9.0	0.550 [13.97]	0.045 [1.15]	82.0	± 10 %	0.083	2.8	0.500 [12.70]	0.025 [0.644]
3.9	± 20 %	0.006	9.0	0.550 [13.97]	0.045 [1.15]	100.0	± 10 %	0.095	2.8	0.500 [12.70]	0.025 [0.644]
4.7	± 20 %	0.007	9.0	0.550 [13.97]	0.045 [1.15]	120.0	± 10 %	0.127	2.0	0.500 [12.70]	0.023 [0.573]
5.6	± 20 %	0.007	9.0	0.550 [13.97]	0.045 [1.15]	150.0	± 10 %	0.181	1.6	0.500 [12.70]	0.020 [0.510]
6.8	± 20 %	0.008	9.0	0.550 [13.97]	0.045 [1.15]	180.0	± 10 %	0.217	1.6	0.500 [12.70]	0.020 [0.510]
8.2	± 20 %	0.009	9.0	0.550 [13.97]	0.045 [1.15]	220.0	± 10 %	0.240	1.6	0.500 [12.70]	0.020 [0.510]
10.0	± 10 %	0.010	9.0	0.550 [13.97]	0.045 [1.15]	270.0	± 10 %	0.300	1.6	0.480 [12.19]	0.018 [0.455]
12.0	± 10 %	0.011	9.0	0.550 [13.97]	0.045 [1.15]	330.0	± 10 %	0.336	1.3	0.480 [12.19]	0.018 [0.455]
15.0	± 10 %	0.015	7.2	0.500 [12.70]	0.040 [1.02]	390.0	± 10 %	0.460	1.0	0.480 [12.19]	0.016 [0.405]
18.0	± 10 %	0.016	7.2	0.500 [12.70]	0.040 [1.02]	470.0	± 10 %	0.636	0.8	0.475 [12.07]	0.014 [0.361]
22.0	± 10 %	0.020	5.5	0.500 [12.70]	0.040 [1.02]	560.0	± 10 %	0.696	0.8	0.475 [12.07]	0.014 [0.361]

STANDARD ELECTRICAL SPECIFICATIONS

IND. at 1 kHz (μ H)	TOL.	DCR MAX. (Ω)	RATED CURRENT (A)	APPROX. LEAD "E" SPACING	MAXIMUM LEAD "F" DIAMETER	IND. at 1 kHz (μ H)	TOL.	DCR MAX. (Ω)	RATED CURRENT (A)	APPROX. LEAD "E" SPACING	MAXIMUM LEAD "F" DIAMETER
MODEL IHB-2											
1.0	$\pm 20\%$	0.003	11.4	0.620 [15.75]	0.051 [1.29]	56.0	$\pm 10\%$	0.039	5.5	0.600 [15.24]	0.036 [0.912]
1.2	$\pm 20\%$	0.003	11.4	0.620 [15.75]	0.051 [1.29]	68.0	$\pm 10\%$	0.053	4.8	0.600 [15.24]	0.032 [0.812]
1.5	$\pm 20\%$	0.003	11.4	0.620 [15.75]	0.051 [1.29]	82.0	$\pm 10\%$	0.060	4.8	0.600 [15.24]	0.032 [0.812]
1.8	$\pm 20\%$	0.003	11.4	0.620 [15.75]	0.051 [1.29]	100.0	$\pm 10\%$	0.080	4.0	0.600 [15.24]	0.028 [0.723]
2.2	$\pm 20\%$	0.004	11.4	0.620 [15.75]	0.051 [1.29]	120.0	$\pm 10\%$	0.090	4.0	0.600 [15.24]	0.028 [0.723]
2.7	$\pm 20\%$	0.005	11.4	0.620 [15.75]	0.051 [1.29]	150.0	$\pm 10\%$	0.098	4.0	0.600 [15.24]	0.028 [0.723]
3.3	$\pm 20\%$	0.005	11.4	0.620 [15.75]	0.051 [1.29]	180.0	$\pm 10\%$	0.110	4.0	0.600 [15.24]	0.028 [0.723]
3.9	$\pm 20\%$	0.005	11.4	0.620 [15.75]	0.051 [1.29]	220.0	$\pm 10\%$	0.150	2.8	0.600 [15.24]	0.025 [0.644]
4.7	$\pm 20\%$	0.005	11.4	0.620 [15.75]	0.051 [1.29]	270.0	$\pm 10\%$	0.213	2.0	0.600 [15.24]	0.023 [0.573]
5.6	$\pm 20\%$	0.006	11.4	0.620 [15.75]	0.051 [1.29]	330.0	$\pm 10\%$	0.305	1.6	0.600 [15.24]	0.020 [0.510]
6.8	$\pm 20\%$	0.007	11.4	0.620 [15.75]	0.051 [1.29]	390.0	$\pm 10\%$	0.320	1.6	0.600 [15.24]	0.020 [0.510]
8.2	$\pm 20\%$	0.007	11.4	0.620 [15.75]	0.051 [1.29]	470.0	$\pm 10\%$	0.355	1.6	0.590 [14.99]	0.020 [0.510]
10.0	$\pm 10\%$	0.009	11.4	0.620 [15.75]	0.051 [1.29]	560.0	$\pm 10\%$	0.388	1.6	0.590 [14.99]	0.020 [0.510]
12.0	$\pm 10\%$	0.009	11.4	0.620 [15.75]	0.051 [1.29]	680.0	$\pm 10\%$	0.430	1.6	0.590 [14.99]	0.020 [0.510]
15.0	$\pm 10\%$	0.013	9.0	0.620 [15.75]	0.045 [1.15]	820.0	$\pm 10\%$	0.590	1.3	0.590 [14.99]	0.018 [0.455]
18.0	$\pm 10\%$	0.018	7.2	0.615 [15.62]	0.040 [1.02]	1000.0	$\pm 10\%$	0.818	1.0	0.590 [14.99]	0.016 [0.405]
22.0	$\pm 10\%$	0.019	7.2	0.615 [15.62]	0.040 [1.02]	1200.0	$\pm 10\%$	1.140	0.8	0.590 [14.99]	0.014 [0.361]
27.0	$\pm 10\%$	0.026	5.5	0.575 [14.61]	0.036 [0.912]	1500.0	$\pm 10\%$	1.260	0.8	0.590 [14.99]	0.014 [0.361]
33.0	$\pm 10\%$	0.029	5.5	0.575 [14.61]	0.036 [0.912]	1800.0	$\pm 10\%$	1.390	0.8	0.590 [14.99]	0.014 [0.361]
39.0	$\pm 10\%$	0.030	5.5	0.600 [15.24]	0.036 [0.912]	2200.0	$\pm 10\%$	1.540	0.8	0.590 [14.99]	0.014 [0.361]
47.0	$\pm 10\%$	0.035	5.5	0.600 [15.24]	0.036 [0.912]						
MODEL IHB-3											
1.0	$\pm 20\%$	0.003	21.0	0.790 [20.07]	0.072 [1.83]	82.0	$\pm 10\%$	0.032	9.0	0.760 [19.30]	0.045 [1.150]
1.2	$\pm 20\%$	0.003	21.0	0.790 [20.07]	0.072 [1.83]	100.0	$\pm 10\%$	0.034	9.0	0.760 [19.30]	0.045 [1.150]
1.5	$\pm 20\%$	0.003	21.0	0.790 [20.07]	0.072 [1.83]	120.0	$\pm 10\%$	0.046	7.2	0.740 [18.80]	0.040 [1.020]
1.8	$\pm 20\%$	0.003	21.0	0.790 [20.07]	0.072 [1.83]	150.0	$\pm 10\%$	0.064	5.5	0.720 [18.29]	0.036 [0.912]
2.2	$\pm 20\%$	0.003	21.0	0.790 [20.07]	0.072 [1.83]	180.0	$\pm 10\%$	0.072	5.5	0.720 [18.29]	0.036 [0.912]
2.7	$\pm 20\%$	0.003	21.0	0.790 [20.07]	0.072 [1.83]	220.0	$\pm 10\%$	0.080	5.5	0.790 [20.07]	0.036 [0.912]
3.3	$\pm 20\%$	0.003	21.0	0.790 [20.07]	0.072 [1.83]	270.0	$\pm 10\%$	0.110	4.5	0.770 [19.56]	0.032 [0.812]
3.9	$\pm 20\%$	0.003	21.0	0.790 [20.07]	0.072 [1.83]	330.0	$\pm 10\%$	0.122	4.5	0.770 [19.56]	0.032 [0.812]
4.7	$\pm 20\%$	0.003	21.0	0.790 [20.07]	0.072 [1.83]	390.0	$\pm 10\%$	0.169	4.0	0.740 [18.80]	0.028 [0.723]
5.6	$\pm 20\%$	0.003	21.0	0.790 [20.07]	0.072 [1.83]	470.0	$\pm 10\%$	0.187	4.0	0.740 [18.80]	0.028 [0.723]
6.8	$\pm 20\%$	0.004	21.0	0.790 [20.07]	0.072 [1.83]	560.0	$\pm 10\%$	0.205	4.0	0.740 [18.80]	0.028 [0.723]
8.2	$\pm 20\%$	0.004	21.0	0.790 [20.07]	0.072 [1.83]	680.0	$\pm 10\%$	0.256	2.8	0.725 [18.42]	0.025 [0.644]
10.0	$\pm 10\%$	0.006	17.0	0.770 [19.56]	0.064 [1.63]	820.0	$\pm 10\%$	0.288	2.8	0.725 [18.42]	0.025 [0.644]
12.0	$\pm 10\%$	0.008	13.5	0.750 [19.05]	0.057 [1.45]	1000.0	$\pm 10\%$	0.426	2.0	0.715 [18.16]	0.023 [0.573]
15.0	$\pm 10\%$	0.009	13.5	0.750 [19.05]	0.057 [1.45]	1200.0	$\pm 10\%$	0.462	2.0	0.760 [19.30]	0.023 [0.573]
18.0	$\pm 10\%$	0.010	13.5	0.750 [19.05]	0.057 [1.45]	1500.0	$\pm 10\%$	0.518	2.0	0.760 [19.30]	0.023 [0.573]
22.0	$\pm 10\%$	0.011	13.5	0.750 [19.05]	0.057 [1.45]	1800.0	$\pm 10\%$	0.705	1.6	0.740 [18.80]	0.020 [0.510]
27.0	$\pm 10\%$	0.012	13.5	0.800 [20.32]	0.057 [1.45]	2200.0	$\pm 10\%$	1.020	1.3	0.720 [18.29]	0.018 [0.455]
33.0	$\pm 10\%$	0.017	13.5	0.780 [19.81]	0.051 [1.29]	2700.0	$\pm 10\%$	1.140	1.3	0.720 [18.29]	0.018 [0.455]
39.0	$\pm 10\%$	0.022	11.4	0.780 [19.81]	0.051 [1.29]	3300.0	$\pm 10\%$	1.270	1.3	0.720 [18.29]	0.018 [0.455]
47.0	$\pm 10\%$	0.024	9.0	0.760 [19.30]	0.045 [1.15]	3900.0	$\pm 10\%$	1.670	1.0	0.700 [17.78]	0.016 [0.405]
56.0	$\pm 10\%$	0.026	9.0	0.760 [19.30]	0.045 [1.15]	4700.0	$\pm 10\%$	1.860	1.0	0.730 [18.54]	0.016 [0.405]
68.0	$\pm 10\%$	0.029	9.0	0.760 [19.30]	0.045 [1.15]						

**STANDARD ELECTRICAL SPECIFICATIONS**

IND. at 1 kHz (μ H)	TOL.	DCR MAX. (Ω)	RATED CURRENT (A)	APPROX. LEAD "E" SPACING	MAXIMUM LEAD "F" DIAMETER	IND. at 1 kHz (μ H)	TOL.	DCR MAX. (Ω)	RATED CURRENT (A)	APPROX. LEAD "E" SPACING	MAXIMUM LEAD "F" DIAMETER
MODEL IHB-4											
1.8	$\pm 20\%$	0.002	27.0	1.10 [27.94]	0.072 [1.83]	180.0	$\pm 10\%$	0.045	11.4	1.10 [27.94]	0.051 [1.29]
2.2	$\pm 20\%$	0.002	27.0	1.10 [27.94]	0.072 [1.83]	220.0	$\pm 10\%$	0.050	11.4	1.10 [27.94]	0.051 [1.29]
2.7	$\pm 20\%$	0.003	27.0	1.10 [27.94]	0.072 [1.83]	270.0	$\pm 10\%$	0.056	11.4	1.10 [27.94]	0.051 [1.29]
3.3	$\pm 20\%$	0.003	27.0	1.10 [27.94]	0.072 [1.83]	330.0	$\pm 10\%$	0.074	11.4	1.16 [29.46]	0.045 [1.15]
3.9	$\pm 20\%$	0.003	27.0	1.10 [27.94]	0.072 [1.83]	390.0	$\pm 10\%$	0.082	9.0	1.13 [28.70]	0.045 [1.15]
4.7	$\pm 20\%$	0.003	27.0	1.10 [27.94]	0.072 [1.83]	470.0	$\pm 10\%$	0.114	7.2	1.13 [28.70]	0.040 [1.02]
5.6	$\pm 20\%$	0.004	27.0	1.10 [27.94]	0.072 [1.83]	560.0	$\pm 10\%$	0.125	7.2	1.13 [28.70]	0.040 [1.02]
6.8	$\pm 20\%$	0.004	27.0	1.10 [27.94]	0.072 [1.83]	680.0	$\pm 10\%$	0.139	7.2	1.13 [28.70]	0.040 [1.02]
8.2	$\pm 20\%$	0.004	27.0	1.10 [27.94]	0.072 [1.83]	820.0	$\pm 10\%$	0.154	7.2	1.13 [28.70]	0.040 [1.02]
10.0	$\pm 10\%$	0.005	27.0	1.10 [27.94]	0.072 [1.83]	1000.0	$\pm 10\%$	0.216	5.5	1.10 [27.94]	0.036 [0.912]
12.0	$\pm 10\%$	0.005	27.0	1.10 [27.94]	0.072 [1.83]	1200.0	$\pm 10\%$	0.232	5.5	1.10 [27.94]	0.036 [0.912]
15.0	$\pm 10\%$	0.006	27.0	1.10 [27.94]	0.072 [1.83]	1500.0	$\pm 10\%$	0.324	4.5	1.14 [28.96]	0.032 [0.812]
18.0	$\pm 10\%$	0.008	27.0	1.10 [27.94]	0.064 [1.63]	1800.0	$\pm 10\%$	0.360	4.5	1.14 [28.96]	0.032 [0.812]
22.0	$\pm 10\%$	0.009	21.0	1.10 [27.94]	0.064 [1.63]	2200.0	$\pm 10\%$	0.494	4.0	1.11 [28.19]	0.028 [0.723]
27.0	$\pm 10\%$	0.010	21.0	1.10 [27.94]	0.064 [1.63]	2700.0	$\pm 10\%$	0.555	4.0	1.11 [28.19]	0.028 [0.723]
33.0	$\pm 10\%$	0.011	21.0	1.10 [27.94]	0.064 [1.63]	3300.0	$\pm 10\%$	0.773	2.8	1.09 [27.69]	0.025 [0.644]
39.0	$\pm 10\%$	0.012	21.0	1.10 [27.94]	0.064 [1.63]	3900.0	$\pm 10\%$	0.845	2.8	1.09 [27.69]	0.025 [0.644]
47.0	$\pm 10\%$	0.018	14.4	1.10 [27.94]	0.057 [1.45]	4700.0	$\pm 10\%$	1.140	2.0	1.07 [27.18]	0.023 [0.573]
56.0	$\pm 10\%$	0.019	14.4	1.11 [28.19]	0.057 [1.45]	5600.0	$\pm 10\%$	1.600	2.0	1.05 [26.67]	0.020 [0.510]
68.0	$\pm 10\%$	0.021	14.4	1.11 [28.19]	0.057 [1.45]	6800.0	$\pm 10\%$	1.760	1.6	1.05 [26.67]	0.020 [0.510]
82.0	$\pm 10\%$	0.023	14.4	1.11 [28.19]	0.057 [1.45]	8200.0	$\pm 10\%$	1.950	1.6	1.09 [27.69]	0.020 [0.510]
100.0	$\pm 10\%$	0.025	14.4	1.11 [28.19]	0.057 [1.45]	10000.0	$\pm 10\%$	2.760	1.3	1.07 [27.18]	0.018 [0.455]
120.0	$\pm 10\%$	0.028	14.4	1.11 [28.19]	0.057 [1.45]	12000.0	$\pm 10\%$	3.040	1.3	1.07 [27.18]	0.018 [0.455]
150.0	$\pm 10\%$	0.040	11.4	1.10 [27.94]	0.051 [1.29]	15000.0	$\pm 10\%$	3.390	1.3	1.07 [27.18]	0.018 [0.455]
MODEL IHB-5											
1.8	$\pm 20\%$	0.002	35.0	1.13 [28.70]	0.081 [2.05]	180.0	$\pm 10\%$	0.035	13.5	1.12 [28.45]	0.057 [1.45]
2.2	$\pm 20\%$	0.002	35.0	1.13 [28.70]	0.081 [2.05]	220.0	$\pm 10\%$	0.040	13.5	1.12 [28.45]	0.057 [1.45]
2.7	$\pm 20\%$	0.002	35.0	1.13 [28.70]	0.081 [2.05]	270.0	$\pm 10\%$	0.044	13.5	1.12 [28.45]	0.057 [1.45]
3.3	$\pm 20\%$	0.002	35.0	1.13 [28.70]	0.081 [2.05]	330.0	$\pm 10\%$	0.049	13.5	1.12 [28.45]	0.057 [1.45]
3.9	$\pm 20\%$	0.003	35.0	1.13 [28.70]	0.081 [2.05]	390.0	$\pm 10\%$	0.070	11.4	1.09 [27.69]	0.051 [1.29]
4.7	$\pm 20\%$	0.003	35.0	1.13 [28.70]	0.081 [2.05]	470.0	$\pm 10\%$	0.078	11.4	1.09 [27.69]	0.051 [1.29]
5.6	$\pm 20\%$	0.003	35.0	1.13 [28.70]	0.081 [2.05]	560.0	$\pm 10\%$	0.105	9.0	1.07 [27.18]	0.045 [1.15]
6.8	$\pm 20\%$	0.003	35.0	1.13 [28.70]	0.081 [2.05]	680.0	$\pm 10\%$	0.115	9.0	1.07 [27.18]	0.045 [1.15]
8.2	$\pm 20\%$	0.003	35.0	1.13 [28.70]	0.081 [2.05]	820.0	$\pm 10\%$	0.127	9.0	1.07 [27.18]	0.045 [1.15]
10.0	$\pm 10\%$	0.004	35.0	1.13 [28.70]	0.081 [2.05]	1000.0	$\pm 10\%$	0.176	7.2	1.05 [26.67]	0.040 [1.02]
12.0	$\pm 10\%$	0.004	35.0	1.13 [28.70]	0.081 [2.05]	1200.0	$\pm 10\%$	0.195	7.2	1.05 [26.67]	0.040 [1.02]
15.0	$\pm 10\%$	0.005	35.0	1.13 [28.70]	0.081 [2.05]	1500.0	$\pm 10\%$	0.274	5.5	1.03 [26.16]	0.036 [0.912]
18.0	$\pm 10\%$	0.007	27.0	1.10 [27.94]	0.072 [1.83]	1800.0	$\pm 10\%$	0.302	5.5	1.10 [27.94]	0.036 [0.912]
22.0	$\pm 10\%$	0.007	27.0	1.10 [27.94]	0.072 [1.83]	2200.0	$\pm 10\%$	0.338	5.5	1.10 [27.94]	0.036 [0.912]
27.0	$\pm 10\%$	0.008	27.0	1.10 [27.94]	0.072 [1.83]	2700.0	$\pm 10\%$	0.459	4.5	1.08 [27.43]	0.032 [0.812]
33.0	$\pm 10\%$	0.009	27.0	1.10 [27.94]	0.072 [1.83]	3300.0	$\pm 10\%$	0.642	4.0	1.06 [26.92]	0.028 [0.723]
39.0	$\pm 10\%$	0.010	27.0	1.10 [27.94]	0.072 [1.83]	3900.0	$\pm 10\%$	0.699	4.0	1.06 [26.92]	0.028 [0.723]
47.0	$\pm 10\%$	0.011	27.0	1.10 [27.94]	0.072 [1.83]	4700.0	$\pm 10\%$	0.775	4.0	1.06 [26.92]	0.028 [0.723]
56.0	$\pm 10\%$	0.013	21.0	1.10 [27.94]	0.072 [1.83]	5600.0	$\pm 10\%$	0.843	4.0	1.06 [26.92]	0.028 [0.723]
68.0	$\pm 10\%$	0.015	21.0	1.10 [27.94]	0.072 [1.83]	6800.0	$\pm 10\%$	1.150	2.8	1.04 [26.42]	0.025 [0.644]
82.0	$\pm 10\%$	0.017	21.0	1.10 [27.94]	0.072 [1.83]	8200.0	$\pm 10\%$	1.260	2.8	1.09 [27.69]	0.025 [0.644]
100.0	$\pm 10\%$	0.018	21.0	1.10 [27.94]	0.072 [1.83]	10000.0	$\pm 10\%$	1.740	2.0	1.07 [27.18]	0.023 [0.573]
120.0	$\pm 10\%$	0.022	17.0	1.08 [27.43]	0.064 [1.63]	12000.0	$\pm 10\%$	1.920	2.0	1.07 [27.18]	0.023 [0.573]
150.0	$\pm 10\%$	0.025	17.0	1.08 [27.43]	0.064 [1.63]	15000.0	$\pm 10\%$	2.170	2.0	1.07 [27.18]	0.023 [0.573]

STANDARD ELECTRICAL SPECIFICATIONS

IND. at 1 kHz (μ H)	TOL.	DCR MAX. (Ω)	RATED CURRENT (A)	APPROX. LEAD "E" SPACING	MAXIMUM LEAD "F" DIAMETER	IND. at 1 kHz (μ H)	TOL.	DCR MAX. (Ω)	RATED CURRENT (A)	APPROX. LEAD "E" SPACING	MAXIMUM LEAD "F" DIAMETER
MODEL IHB-6											
4.7	$\pm 20\%$	0.002	35.0	1.43 [36.32]	0.102 [2.59]	560.0	$\pm 10\%$	0.068	13.5	1.35 [34.29]	0.057 [1.45]
5.6	$\pm 20\%$	0.002	35.0	1.43 [36.32]	0.102 [2.59]	680.0	$\pm 10\%$	0.094	11.4	1.33 [33.78]	0.051 [1.29]
6.8	$\pm 20\%$	0.003	35.0	1.43 [36.32]	0.102 [2.59]	820.0	$\pm 10\%$	0.104	11.4	1.33 [33.78]	0.051 [1.29]
8.2	$\pm 20\%$	0.003	35.0	1.43 [36.32]	0.102 [2.59]	1000.0	$\pm 10\%$	0.143	9.0	1.31 [33.27]	0.045 [1.15]
10.0	$\pm 10\%$	0.003	35.0	1.43 [36.32]	0.102 [2.59]	1200.0	$\pm 10\%$	0.156	9.0	1.40 [35.56]	0.045 [1.15]
12.0	$\pm 10\%$	0.004	35.0	1.43 [36.32]	0.102 [2.59]	1500.0	$\pm 10\%$	0.219	7.2	1.37 [34.80]	0.040 [1.02]
15.0	$\pm 10\%$	0.004	35.0	1.43 [36.32]	0.102 [2.59]	1800.0	$\pm 10\%$	0.241	7.2	1.37 [34.80]	0.040 [1.02]
18.0	$\pm 10\%$	0.005	35.0	1.43 [36.32]	0.102 [2.59]	2200.0	$\pm 10\%$	0.270	7.2	1.37 [34.80]	0.040 [1.02]
22.0	$\pm 10\%$	0.005	35.0	1.43 [36.32]	0.102 [2.59]	2700.0	$\pm 10\%$	0.364	5.5	1.34 [34.04]	0.036 [0.912]
27.0	$\pm 10\%$	0.006	35.0	1.43 [36.32]	0.102 [2.59]	3300.0	$\pm 10\%$	0.498	4.5	1.32 [33.53]	0.032 [0.812]
33.0	$\pm 10\%$	0.006	35.0	1.43 [36.32]	0.102 [2.59]	3900.0	$\pm 10\%$	0.548	4.5	1.32 [33.53]	0.032 [0.812]
39.0	$\pm 10\%$	0.006	35.0	1.43 [36.32]	0.102 [2.59]	4700.0	$\pm 10\%$	0.608	4.5	1.32 [33.53]	0.032 [0.812]
47.0	$\pm 10\%$	0.008	35.0	1.53 [38.86]	0.102 [2.59]	5600.0	$\pm 10\%$	0.671	4.5	1.38 [35.05]	0.032 [0.812]
56.0	$\pm 10\%$	0.009	35.0	1.53 [38.86]	0.102 [2.59]	6800.0	$\pm 10\%$	0.750	4.5	1.38 [35.05]	0.032 [0.812]
68.0	$\pm 10\%$	0.009	35.0	1.53 [38.86]	0.102 [2.59]	8200.0	$\pm 10\%$	1.030	4.0	1.35 [34.29]	0.028 [0.723]
82.0	$\pm 10\%$	0.010	35.0	1.53 [38.86]	0.102 [2.59]	10000.0	$\pm 10\%$	1.160	4.0	1.35 [34.29]	0.028 [0.723]
100.0	$\pm 10\%$	0.014	27.0	1.45 [36.83]	0.081 [2.05]	12000.0	$\pm 10\%$	1.540	2.8	1.33 [33.78]	0.025 [0.644]
120.0	$\pm 10\%$	0.015	27.0	1.45 [36.83]	0.081 [2.05]	15000.0	$\pm 10\%$	1.750	2.8	1.33 [33.78]	0.025 [0.644]
150.0	$\pm 10\%$	0.023	21.0	1.41 [35.81]	0.072 [1.83]	18000.0	$\pm 10\%$	1.940	2.8	1.38 [35.05]	0.025 [0.644]
180.0	$\pm 10\%$	0.025	21.0	1.41 [35.81]	0.072 [1.83]	22000.0	$\pm 10\%$	2.740	2.0	1.36 [34.54]	0.023 [0.573]
220.0	$\pm 10\%$	0.028	21.0	1.41 [35.81]	0.072 [1.83]	27000.0	$\pm 10\%$	3.710	1.7	1.33 [33.78]	0.020 [0.510]
270.0	$\pm 10\%$	0.030	21.0	1.41 [35.81]	0.072 [1.83]	33000.0	$\pm 10\%$	4.160	1.7	1.33 [33.78]	0.020 [0.510]
330.0	$\pm 10\%$	0.040	17.0	1.38 [35.05]	0.064 [1.63]	39000.0	$\pm 10\%$	5.550	1.4	1.31 [33.27]	0.018 [0.455]
390.0	$\pm 10\%$	0.055	13.5	1.35 [34.29]	0.057 [1.45]	47000.0	$\pm 10\%$	6.190	1.4	1.34 [34.04]	0.018 [0.455]
470.0	$\pm 10\%$	0.061	13.5	1.35 [34.29]	0.057 [1.45]						

MARKING

- Model
- Value
- Date code

ORDERING INFORMATION

IHB-1	10 μ H	$\pm 10\%$	EB	e2
MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	PACKAGE CODE	JEDEC LEAD (Pb)-FREE STANDARD

GLOBAL PART NUMBER

I H B 1	E B	1 0 0	K
MODEL	PACKING CODE	INDUCTANCE VALUE	TOL.



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.