



CRIMP RINGS & SPADES



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

TERMINAL, PG R 16-14 8

PLASTI-GRIP | PLASTI-GRIP

328527

TE Internal Number: 328527

Always EU RoHS/ELV Compliant

Terminal Shape **Ring Tongue**

Stud Diameter **4.34 mm [.171 in]**

Tongue Thickness **.79 mm [.031 in]**

Sealed **No**

Heavy Duty **No**

Product Drawings

[TERMINAL, RING TONGUE, PLASTI-GRIP WIRE SIZE: 16-14 AWG](#)

PDF (TIFF AVAILABLE)
English

[TERMINAL, RING TONGUE, PLASTI-GRIP WIRE SIZE: 16-14 AWG](#)

PDF (TIFF AVAILABLE)
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Catalog Pages/Data Sheets

[PLASTI GRIP_QRG](#)

PDF
English

Product Specifications

Application Specification

[PLASTI-GRIP Terminals And Splices](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_328527_04142014734_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Sealed	No
	Barrel Type	Closed Barrel
	Wire/Cable Type	Regular Wire
	Insulated	Yes
	Insulated Wire Support	Yes
	Support Style	Insulation Support
	Stud Size	8, M4
	Shape Code	RING-043
Wire/Cable Composition	Solid or Stranded	

Configuration Features	Terminal Angle	Straight
	Number of Holes	1

Electrical Characteristics	Voltage (Max) (V)	600
----------------------------	-------------------	------------

Body Features	Plating Material	Copper, Tin
	Insulation Sleeve Material	PVC
	Insulation Sleeve Color	Blue
	Insulation Material	PVC
	Inspection Slot	No
	Weight per Piece (g)	.796

Contact Features	Terminal Shape	Ring Tongue
	Terminal Orientation	Straight

Dimensions	Stud Diameter	4.34 mm [.171 in]
	Tongue Thickness	.79 mm [.031 in]
	Wire Insulation Diameter	3 – 4.9 mm [.118 – .193 in]
	Wire Size (AWG)	16 – 14
	Wire Size (mm ²)	1.04 – 2.62
	Wire Size (CMA)	2050 – 5180
	Overall Length	20.96 mm [.8252 in]

Usage Conditions	Operating Temperature Range (°C)	105
------------------	----------------------------------	------------





Operation/Application	Heavy Duty	No
Industry Standards	Government Qualified	No
Packaging Features	Packaging Method	Loose Piece
	Packaging Quantity	1000
Other	Barrel Color	Blue

Product Compliance

[Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

WIRE-TO-BOARD CONNECTOR CONTACTS	CRIMP RINGS & SPADES	SURFACE MOUNT RESISTORS	COMBO JACKS
 <p>SL 156 CONTACT LP 640706-1</p>	 <p>TERMINAL, PIDG SPD 16-14 8 325199</p>	 <p>CPF 0805 33R 0.1% 25PPM 5K RL CPF0805B33RE</p>	 <p>RJ45 OVER USB W/ LED OG/OG 4-1775855-1</p>
<p>Save to List</p> <p>Find Similar Products</p>	<p>Save to List</p> <p>Find Similar Products</p>	<p>Save to List</p> <p>Find Similar Products</p>	<p>Save to List</p> <p>Find Similar Products</p>