



## Datasheet for part number KJA0T17F6SN

|                                      |                            |                                           |            |
|--------------------------------------|----------------------------|-------------------------------------------|------------|
| Our Catalog Part Number: KJA0T17F6SN |                            |                                           |            |
| Brand: Cannon                        | Product Category: Circular | Product Line: 38999 Series I, II, and III | Series: KJ |

| Product Datasheet                 |                                                                               |
|-----------------------------------|-------------------------------------------------------------------------------|
| SERIES                            | MIL - DTL - 38999 Series III                                                  |
| STYLE                             | Wall mounting receptacle                                                      |
| CLASS                             | Environment resistant (without rear accessory)                                |
| SHELL SIZE                        | 17                                                                            |
| SHELL MATERIAL                    | Corrosion resistant shells of aluminum alloy                                  |
| INSULATOR MATERIAL                | High grade plastic                                                            |
| GROMMET AND SEAL MATERIAL         | Silicone base elastomer                                                       |
| PLATING                           | Electroless nickel                                                            |
| ARRANGEMENT                       | 17-6                                                                          |
| NUMBER OF CONTACTS                | 6 contacts size 12                                                            |
| GENDER                            | Socket                                                                        |
| CONTACT TYPE                      | Rear release crimp snap-in contacts                                           |
| CONTACT MATERIAL                  | Copper Alloy, gold plate                                                      |
| POLARIZATION                      | AR° or AP° BSC=80°<br>BR° or BP° BSC=142°<br>CR° or CP° BSC=196°              |
| LOW PROFILE / LIGHT WEIGHT        | no                                                                            |
| SCOOP PROOF                       | yes                                                                           |
| COUPLING SYSTEM                   | Threaded coupling                                                             |
| ELECTROLYTIC EROSION              | yes                                                                           |
| DURABILITY (CYCLES)               | 500                                                                           |
| HIGH IMPACT SHOCK                 | yes                                                                           |
| EXTERNAL BENDING MOMENT (Size 25) | 1000 in/lbs                                                                   |
| RANDOM VIBRATION "J"              | 492 F                                                                         |
| SINE VIBRATION                    | 60 G, 85 to +392 F                                                            |
| SAND, DUST, ICE                   | yes                                                                           |
| TEMPERATURE RANGE                 | 65°C (85°F) to + 200°C (+392°F)                                               |
| CORROSION RESISTANT               | 48 hours                                                                      |
| TEST SERVICE RATING (MATED)       | Sea Level = 1800<br>50000 ft. = 1000<br>70000 ft. = 1000<br>100000 ft. = 1000 |
| TEST SERVICE RATING (UNMATED)     | Sea Level = 1800<br>50000 ft. = 600<br>70000 ft. = 400<br>100000 ft. = 200    |
| OPERATING VOLTAGE                 | Vrms = 600<br>Vdc = 850                                                       |