



## Datasheet for part number KJL6T17B35PNL

|                                                                                               |
|-----------------------------------------------------------------------------------------------|
| Our Catalog Part Number: KJL6T17B35PNL                                                        |
| Our Global Manufacturing Part Number: 111079-0013                                             |
| Brand: Cannon Product Category: Circular Product Line: 38999 Series I, II, and III Series: KJ |

| Product Datasheet                 |                                                                            |
|-----------------------------------|----------------------------------------------------------------------------|
| SERIES                            | MIL - DTL - 38999 Series I                                                 |
| STYLE                             | Straight plug                                                              |
| CLASS                             | Environment resistant (without rear accessory)                             |
| SHELL SIZE                        | 17                                                                         |
| SHELL MATERIAL                    | Corrosion resistant shells of aluminum alloy                               |
| INSULATOR MATERIAL                | High grade plastic                                                         |
| GROMMET AND SEAL MATERIAL         | Silicone base elastomer                                                    |
| PLATING                           | Olive drab cadmium over electroless nickel plate                           |
| ARRANGEMENT                       | 17-35                                                                      |
| NUMBER OF CONTACTS                | 55 contacts size 22D                                                       |
| GENDER                            | Pin                                                                        |
| CONTACT TYPE                      | Rear release crimp snap-in contacts                                        |
| CONTACT MATERIAL                  | Copper Alloy, gold plate                                                   |
| POLARIZATION                      | 95°                                                                        |
| MOD. CONTACT                      | less contacts                                                              |
| LOW PROFILE / LIGHT WEIGHT        | no                                                                         |
| SCOOP PROOF                       | yes                                                                        |
| COUPLING SYSTEM                   | Bayonet                                                                    |
| ELECTROLYTIC EROSION              | no                                                                         |
| DURABILITY (CYCLES)               | 500                                                                        |
| HIGH IMPACT SHOCK                 | yes                                                                        |
| EXTERNAL BENDING MOMENT (Size 25) | 650 in/lbs                                                                 |
| RANDOM VIBRATION "J"              | Ambient                                                                    |
| SINE VIBRATION                    | 30 G, Ambient                                                              |
| SAND, DUST, ICE                   | yes                                                                        |
| TEMPERATURE RANGE                 | 65°C (85°F) to + 175°C (+347°F)                                            |
| CORROSION RESISTANT               | 500 hours                                                                  |
| TEST SERVICE RATING (MATED)       | Sea Level = 1300<br>50000 ft. = 800<br>70000 ft. = 800<br>100000 ft. = 800 |
| TEST SERVICE RATING (UNMATED)     | Sea Level = 1300<br>50000 ft. = 550<br>70000 ft. = 350<br>100000 ft. = 200 |
| OPERATING VOLTAGE                 | Vrms = 433<br>Vdc = 613                                                    |