HIS COPY IS PROVIDED ON	A RESTRICTED BASIS AND IS NOT TO BE U	SED IN ANY WAY DETRIMENTAL T	O THE INTE	ERESTS OF PANDUIT CORP.
Material	High Conductivity Seamless Copper Tube			.47 R Ref
Plating	Electro-Tin			
Wire Size	4/0 AWG		¬ H	PANDUIT
Wire Type	Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric	1.06±.04	4/0 STR CU LCC4/0-38WH	
Wire Strip Length	1-5/8 in.			PURPLE DIE P54 (15)
Stud Size	3/8 in.			.41±.02 DIA
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.	.39±.04	− 1.75±.0	(2) PLS — Color coded barrel markings
UL Temperature Rating	90°C			Beveled wire entry .71±.01
C.S.A Certified Wire Connector	Yes			
Panduit Color Code on Barrel	PURPLE			1.56±.04
Panduit Die Index No. on Barrel	P54			1.07.055
Alternate Industry Die Index No. () on Barrel	(15)	Wire ins	pection v	vindow 1.97 REF
		<u> </u>		
CERTIFIE	D LISTED Wire Connector	14±.01		4.06 REF
				PANDUIT CORP. TINLEY PARK, ILLIN
1 9/04 JHNU TLCO	STUD HC	DLE WAS 1/2"	12122	LCC4/0-38WH-X Copper Lug - Two-Hole, Long Barrel with Window, 45° Angle Tong

SCALE N/A

ECN

DRAWING NO / CAD FILE

LCC4_0-38WH-CUST

DESCRIPTION

REV DATE

BY CHK

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

LCC4/0-38WH-X