

SMD Power Inductor CD54


RoHS

Halogen
Free



Description

- Ferrite drum core construction.
- Magnetically unshielded.
- L × W × H: 6.1 × 5.5 × 4.85mm Max.
- Product weight 0.4g(Ref.)
- Moisture Sensitivity Level: 1
- RoHS compliance.
- Halogen Free available.

Dimension - [mm]



Land pattern and Schematics - [mm]



Environmental Data

- Operating temperature range: -40°C ~ +100°C (including coil's self temperature rise)
- Storage temperature range: -40°C ~ +100°C
- Solder reflow temperature: 260 °C peak.

Packaging

- Carrier tape and reel packaging.
- 13.0" diameter reel
- 1500pcs per reel

Applications

- Ideally used in Mobilephone, PDA, MP3, DSC/DVC, portable DVD etc as DC-DC Converter inductors.

SMD Power Inductor CD54




Electrical Characteristics

Part Name	Stamp	Inductance (μ H) [within] ※1	D.C.R (Ω) [Max.] (at 20°C)	Rated Current (A) ※2
CD54NP-100MC	100	$10 \pm 20\%$	0.10	1.44
CD54NP-120MC	120	$12 \pm 20\%$	0.12	1.40
CD54NP-150MC	150	$15 \pm 20\%$	0.14	1.30
CD54NP-180MC	180	$18 \pm 20\%$	0.15	1.23
CD54NP-220MC	220	$22 \pm 20\%$	0.18	1.11
CD54NP-270MC	270	$27 \pm 20\%$	0.20	0.97
CD54NP-330LC	330	$33 \pm 15\%$	0.23	0.88
CD54NP-390LC	390	$39 \pm 15\%$	0.32	0.80
CD54NP-470LC	470	$47 \pm 15\%$	0.37	0.72
CD54NP-560KC	560	$56 \pm 10\%$	0.42	0.68
CD54NP-680KC	680	$68 \pm 10\%$	0.46	0.61
CD54NP-820KC	820	$82 \pm 10\%$	0.60	0.58
CD54NP-101KC	101	$100 \pm 10\%$	0.70	0.52
CD54NP-121KC	121	$120 \pm 10\%$	0.93	0.48
CD54NP-151KC	151	$150 \pm 10\%$	1.10	0.40
CD54NP-181KC	181	$180 \pm 10\%$	1.38	0.38
CD54NP-221KC	221	$220 \pm 10\%$	1.57	0.35

※1: Inductance measuring frequency: 10μ H $\sim 82 \mu$ H , at 2.52MHz.
 100μ H $\sim 220 \mu$ H , at 1 kHz.













※2: Rated current: The DC current at which the inductance decreases to 90 % of it's initial value or when $\Delta t=40^\circ\text{C}$, whichever is lower ($T_a=20^\circ\text{C}$).

SMD Power Inductor CD54



Saturation Current & Temperature Rise Graph






— L (20°C) — L (105°C) — ΔT





SMD Power Inductor CD54

Saturation Current & Temperature Rise Graph

— L (20°C) — L (105°C) — ΔT



Solder Reflow Condition



Please refer to the sales offices on our website - <http://www.sumida.com>

Hong Kong
Tel. +852-2880-6781
FAX. +852-2565-9600
sales@hk.sumida.com
Saitama(Japan)
Tel. +81-48-691-7300
FAX. +81-48-691-7340
sales@jp.sumida.com
Chicago
Tel. +1-847-545-6700
FAX. +1-847-545-6720
sales@us.sumida.com

Shanghai
Tel. +86-21-5836-3299
FAX. +86-21-5836-3266
shanghai.sales@cn.sumida.com
Seoul
Tel. +82-2-6237-0777
FAX. +82-2-6237-0778
sales@kr.sumida.com
Obernzell
Tel. +49-8591-937-0
FAX. +49-8591-937-103
contact@eu.sumida.com

Shenzhen
Tel. +86-755-8291-0228
FAX. +86-755-8291-0338
shenzhen.sales@cn.sumida.com
Singapore
Tel. +65-6296-3388
FAX. +65-6841-4426
sales@sg.sumida.com
Neumarkt
Tel. +49-9181-4509-110
FAX. +49-9181-4509-310
infocomp@eu.sumida.com

Taipei
Tel. +886-2-8751-2737
FAX. +886-2-8751-2738
sales@tw.sumida.com
San Jose
Tel. +1-408-321-9660
FAX. +1-408-321-9308
sales@us.sumida.com