

Normally – OFF Silicon Carbide Super Junction Transistor


V_{DS}	=	1200 V
$V_{DS(ON)}$	=	1.3 V
I_D	=	6 A
$R_{DS(ON)}$	=	220 mΩ

Features


- 175 °C maximum operating temperature
- Temperature independent switching performance
- Gate oxide free SiC switch
- Suitable for connecting an anti-parallel diode
- Positive temperature coefficient for easy paralleling
- Low gate charge
- Low intrinsic capacitance

Package

- RoHS Compliant



TO-247AB



Advantages

- Low switching losses
- Higher efficiency
- High temperature operation
- High short circuit withstand capability

Applications

- Down Hole Oil Drilling, Geothermal Instrumentation
- Hybrid Electric Vehicles (HEV)
- Solar Inverters
- Switched-Mode Power Supply (SMPS)
- Power Factor Correction (PFC)
- Induction Heating
- Uninterruptible Power Supply (UPS)
- Motor Drives

Maximum Ratings unless otherwise specified

Parameter	Symbol	Conditions	Values	Unit
Drain – Source Voltage	V_{DS}	$V_{GS} = 0\text{ V}$	1200	V
Continuous Drain Current	I_D	$T_{C,MAX} = 90\text{ °C}$	6	A
Gate Peak Current	I_{GM}		5	A
Reverse Gate – Source Voltage	V_{SG}		70	V
Reverse Drain – Source Voltage	V_{SD}		40	V
Power Dissipation	P_{tot}	$T_C = 25\text{ °C}$	146	W
Storage Temperature	T_{stg}		-55 to 175	°C

Electrical Characteristics at $T_J = 175\text{ °C}$, unless otherwise specified



Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
On Characteristics						
Drain – Source On Voltage	V _{DS(ON)}	I _D = 6 A, I _G = 500 mA, T _J = 25 °C		1.3		V
		I _D = 6 A, I _G = 1000 mA, T _J = 125 °C		1.7		
		I _D = 6 A, I _G = 1000 mA, T _J = 175 °C		2.2		
Drain – Source On Resistance	R _{DS(ON)}	I _D = 6 A, I _G = 500 mA, T _J = 25 °C		220		mΩ
		I _D = 6 A, I _G = 1000 mA, T _J = 125 °C		280		
		I _D = 6 A, I _G = 1000 mA, T _J = 175 °C		370		
Gate Forward Voltage	V _{GS(FWD)}	I _G = 500 mA, T _J = 25 °C		3.1		V
		I _G = 500 mA, T _J = 175 °C		2.9		
DC Current Gain	β	V _{DS} = 5 V, I _D = 6 A, T _J = 25 °C		53		
		V _{DS} = 5 V, I _D = 6 A, T _J = 175 °C		30		
Off Characteristics						
Drain Leakage Current	I _{DSS}	V _R = 1100 V, V _{GS} = 0 V, T _J = 25 °C		300		nA
		V _R = 1100 V, V _{GS} = 0 V, T _J = 125 °C		350		
		V _R = 1100 V, V _{GS} = 0 V, T _J = 175 °C		450		

Electrical Characteristics at $T_j = 175^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Switching Characteristics						
Turn On Delay Time	$t_{d(on)}$	$V_{DD} = 800\text{ V}$, $I_D = 6\text{ A}$, $R_{G(on)} = R_{G(off)} = 22\ \Omega$, $V_{GS} = -8/15\text{ V}$, $L = 1.052\text{ mH}$, FWD = GB05SLT12-220, $T_j = 25\text{ }^{\circ}\text{C}$		14		ns
Rise Time	t_r			23		ns
Turn Off Delay Time	$t_{d(off)}$			58		ns
Fall Time	t_f			29		ns
Turn-On Energy Per Pulse	E_{on}			175		μJ
Turn-Off Energy Per Pulse	E_{off}	Refer to Figure 13 for gate current waveform		61		μJ
Total Switching Energy	E_{ts}			236		μJ
Turn On Delay Time	$t_{d(on)}$			20		ns
Rise Time	t_r			18		ns
Turn Off Delay Time	$t_{d(off)}$			35		ns
Fall Time	t_f	$V_{DD} = 800\text{ V}$, $I_D = 6\text{ A}$, $R_{G(on)} = R_{G(off)} = 22\ \Omega$, $V_{GS} = -8/15\text{ V}$, $L = 1.052\text{ mH}$, FWD = GB05SLT12-220, $T_j = 175\text{ }^{\circ}\text{C}$		17		ns
Turn-On Energy Per Pulse	E_{on}			108		μJ
Turn-Off Energy Per Pulse	E_{off}			49		μJ
Total Switching Energy	E_{ts}			157		μJ

Thermal Characteristics

Thermal resistance, junction - case	R_{thJC}	1.03	$^\circ\text{C/W}$
-------------------------------------	------------	------	--------------------


Figure 1: Typical Output Characteristics at 25°C

Figure 2: Typical Output Characteristics at 125°C




Figure 3: Typical Output Characteristics at 175 °C




Figure 4: Typical Gate Source I-V Characteristics vs. Temperature




Figure 5: Normalized On-Resistance and Current Gain vs. Temperature




Figure 6: Typical Blocking Characteristics




Figure 7: Typical Hard-switched Turn On Waveforms




Figure 8: Typical Hard-switched Turn Off Waveforms




Figure 9: Typical Turn On Energy Losses and Switching Times vs. Temperature




Figure 10: Typical Turn Off Energy Losses and Switching Times vs. Temperature




Figure 11: Typical Turn On Energy Losses vs. Drain Current




Figure 12: Typical Turn Off Energy Losses vs. Drain Current




Figure 13: Typical Gate Current Waveform

Gate Drive Technique (Option #1)

To drive the GA06JT12-247 with the lowest gate drive losses, a custom-designed, dual voltage source gate drive configuration is recommended [for example, see Figure 5(a) in J. Rabkowski et al., IEEE Trans. Power Electronics 27(5), 2633-2642 (2012)]. More details on using this optimized gate drive technique will be made available shortly. An effective simple alternative for ultra-fast switching of the GA06JT12-247 is available below.

Gate Drive Technique (Option #2)

The GA06JT12-247 can be effectively driven using the IXYS IXDN614 / IXDD614 non-inverting gate driver IC or a comparable product. A typical gate driver configuration along with component values using this driver is offered below. Additional information is available from the manufacturer at www.ixys.com.





Figure 14: Recommended Gate Diver Configuration (Option #2)

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Gate Driver Pins (IXDD614/IXDN614)						
Supply Voltage	V _{CC}		-0.3	15	40	V
Gate Control Input Signal, Low	IN		-5.0	0	0.8	V
Gate Control Input Signal, High	IN		3.0	5.0	V _{CC} +0.3	V
Enable, Low	EN	IXDD614 Only			1/3*V _{CC}	V
Enable, High	EN	IXDD614 Only	2/3*V _{CC}			V
Output Voltage, Low	V _{OUT}				0.025	V
Output Voltage, High	V _{OUT}		V _{CC} -0.025			V
Output Current, Peak	I _{OUT}	Package Limited		4.5	14	A
Output Current, Continuous	I _{OUT}			0.5	4.0	A
Passive Gate Components						
Gate Resistance	R _G	I _G ≈ 0.5 A	5	22		Ω
Gate Capacitance	C _G	I _G ≈ 0.5 A		100		nF

Package Dimensions:

NOTE

1. CONTROLLED DIMENSION IS INCH. DIMENSION IN BRACKET IS MILLIMETER.
2. DIMENSIONS DO NOT INCLUDE END FLASH, MOLD FLASH, MATERIAL PROTRUSIONS

Revision History			
Date	Revision	Comments	Supersedes
2013/02/21	1	Revised electrical characteristics	
2012/11/30	0	Initial release	

Published by

GeneSiC Semiconductor, Inc.
 43670 Trade Center Place Suite 155
 Dulles, VA 20166

GeneSiC Semiconductor, Inc. reserves right to make changes to the product specifications and data in this document without notice.

GeneSiC disclaims all and any warranty and liability arising out of use or application of any product. No license, express or implied to any intellectual property rights is granted by this document.

Unless otherwise expressly indicated, GeneSiC products are not designed, tested or authorized for use in life-saving, medical, aircraft navigation, communication, air traffic control and weapons systems, nor in applications where their failure may result in death, personal injury and/or property damage.